

Bush Hog® TOUGH

2347QT Quick Attach Front-Push Loader

Skid Steer Quick Attach System

BUSH HOG® TOUGH FEATURES

TOUGH Boxed Boom Design

TOUGH Large Diameter Cross Tubes

TOUGH Robotic Welds

TOUGH High Strength Chrome Plated Cylinder Rods

TOUGH Bush Hog Made Buckets

TOUGH Powder Coat Paint



MODEL	Specifications Based on 1997 ASAE STANDARDS	2347QT
Tractor PTO HP Range		25 - 50
2WD/FWA		2WD/FWA
Maximum Lift Height - Measured at Pivot Pin		107 inches
Maximum Lift Height - Under Level Bucket		101 inches
Maximum Dump Angle		50°
Digging Depth		3 inches
Lift Capacity to Maximum Height - At Pivot Pin		1970 lbs
Lift Capacity to Maximum Height - 31.5 inches Forward of Pivot Pin		1270 lbs
Lift Capacity to 59 inch Height - At Pivot Pin		2200 lbs
Lift Capacity to 59 inch Height - 31.5 inches Forward of Pivot Pin		1570 lbs
Breakout Force - At Pivot Pin		2985 lbs
Breakout Force - 31.5 inches - Forward of Pivot Pin		2005 lbs
Rollback Force at Maximum Height - 31.5 inches Forward of Pivot Pin		2640 lbs
Rollback Force at 59 inch Height - 31.5 inches Forward of Pivot Pin		3220 lbs
Rollback Force at Ground Level - 31.5 inches Forward of Pivot Pin		2145 lbs
Raising Time (Ground Level to Full Height)		4 seconds
Lowering Time (Full Height to Ground Level)		2 seconds
Bucket Dumping Time (Full Rollback to Full Dump)		4 seconds
Bucket Rollback Time (Full Dump to Full Rollback)		2 seconds
Hydraulics	Two 2.0 inch Bore, 22.50 inch Stroke Double Acting Bucket Cylinders and Two 2.0 inch Bore, 23.38 inch Stroke Double Acting Lift Cylinders	
Specifications Based on Tractor System of	2450 PSI hyd. Pressure & 9 GPM pump capacity	
Bush Hog Quick Attach Buckets	Available in 48, 60, 72 and 80 inch widths	
Options	Forklift Attachment (36 inch tines), Round Bale Spear, Bucket Tine Teeth, and Grill Guards	
Warranty	1 year limited warranty	
FEATURES	Available in major tractor colors	

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE