

Bush Hog® TOUGH

2610L Single Wing

Flex Series Rotary Cutters

Recommended Tractor HP Minimum 60 PTO

BUSH HOG® TOUGH FEATURES

- TOUGH 10 Gauge Deck Construction
- TOUGH 7 Gauge Strongbacks
- TOUGH 1/4 Inch Sidebands
- TOUGH Heavy Duty Wheel Hubs And Axle Spindles
- TOUGH Independent Spring Cushion At Each Axle Arm
- TOUGH Heavy Duty Axle Turn Buckles
- TOUGH Greaseable Axle Pivot Points
- TOUGH Driveline Safety Retaining Rings
- TOUGH 5 Year Gearbox Limited Warranty
- TOUGH Powder Coat Paint



Model 2610L

MODEL	2610L
Cutting Width	10 ft 6 inches
Cutting Capacity	2 1/2 inch diameter
Cutting Height	2 to 14 inches
Overall Width x Length (from clevis to wheel hub at transport height)	11 ft 8 inches x 14 ft 10 inches
Transport Width (from weight box to wing skid)	8 ft
Tractor PTO	540 RPM/1000 RPM
Minimum Tractor HP	60 PTO
Deck Thickness	10 gauge
Side Bands	1/4 x 10 1/2 inches
Gearbox HP	235/Transfer, 190/Center & Wing
PTO Driveline	Input: Constant Velocity or Cardan/jackshaft - Cat.5 (540 RPM) Cat. 4 or 5 (1000 RPM)
Wing Driveline	ASAE Cat. 4
Slip Clutches	(2) 2 Friction Plates
Blade Tip Speed	16,289 FPM/540 RPM; 16,000 FPM/1000 RPM
Blades	1/2 x 4 inches – Uplift with 6 inch Overlap
Type Hitch	Self Leveling with Perma Level Hitch®, or 2 inch Ball Hitch or Swivel Clevis Hitch
Wing Flex	87° Up to 22° Down
Tires	Laminated, Pneumatic or Aircraft
Axles	Greaseable pivot points
Wheel Shock Protection	Independent Springs/Each Axle
Deflectors	Standard Front Belting and Rear Bands, Optional Chains Front and Rear
Options	Chain Shielding, Tandem Walking Axle, Deck Rings
Warranty	1 year limited warranty with a 5 year gearbox limited warranty

FEATURES

- Perma Level Hitch • Cylinder style anti wrap device around lower gearbox housing
- High blade tip speeds • Deep sidebands • Heavy duty wheel hubs • Quick detach gearbox shields

BUSH HOG EXCLUSIVE:

Driveline safety retaining rings