# SRC-402© /442©

## ASSEMBLY INSTRUCTIONS

©PRINTED IN U.S.A. B61-0520-00(K)(TCA) R0260

KENWOOD CORPORATION

KENWOOD

#### IMPORTANT:

- Before operating your new KENWOOD product, read through this assembly manual carefully to get the most out of it.
- Save this assembly instructions.

#### **Before Assembling**

- Be sure to check that all parts are accounted for before disposing of the packing case.
- A Phillips screwdriver and a mallet are required for assembling.
- · Be carefull not to damage the floor and rack.



### **IMPORTANT SAFEGUARDS**

A Caution : Read this page carefully to keep your safety.

- Please read all of the safety and operating instructions before operating this unit. For bos: { tts. follow all warnings placed on the unit and adhere to the operating and use { uctions. These safety and operating instructions should be retained for { future reference.
- Suffacation After taking the unit out of the polyathylone bag, be sure to dispose of the polyathylene bag out of the reach of children. Otherwise, they may play with the bag, which could cause hazard of suffocation.



 Water and moisture — Do not place a liquid container, such as a vase and water basin, on the unit. Also avoid installing the unit in a place subject to dampness.



3. Heat — Do not install the unit near a source of heat, such as a heater, or under direct sunlight.



#### Notes on Assembling

- During assembling, be sure to verify the numbers stamped on the boards.
  Mount the rear panel after assembling the side panel on the bottom shelf at a right angle.
- When mounting the top shelf and kick plate on the side panel, use glue for adhesive. Be sure to remove any excess glue before it dries.

#### **Handling Precautions**

- Tempered glass is used for the glass doors for providing sufficient strength. However, pay attention not to apply excessive force or to scratch the doors. Cracking or breaking of the glass may occur.
   When moving the cabinet, remove all the components from the rack be-
- When moving the cabinet, remove all the components from the rack before carrying the cabinet. Also do not grasp the top shelf when carrying.
   To allow head radiation from the components, leave a space of 4 inches between the cabinet and wall.
- Do not place the cabinet in a location subject to direct sunlight or near a heater, an air-conditioner, or a place with high humidity.

4. Impact — Avoid placing the unit on an unstable surface. Install it on a horizontal surface not subject to excessive dirt or vibrations



 Modification 
 — Do not attempt to open or modify the unit, for this could cause fire hazard or malfunction.



 Cleaning — Do not use thinner, benzine or alcohol. When cleaning the unit, wipe with a soft, dry cloth.

Abnormal smell — In the event the unit generates smoke or abnormal smell, immediately switch the power OFF and unplug the power cord. After this, please contact your dealer or nearest service station as soon as possible.







