
HOTPOINT

RB790SD– Hotpoint 30" Free-Standing Electric Range

Dimensions (in inches)



Amp Rating	
240V	10.5
208V	7.9
Breaker Size	
40 Amps [†]	

*Note: Check local codes for required breaker size.

Effective January 1, 1996, the National Electrical Code requires that new construction (not existing) utilize a 4-conductor connection to an electric range.

Note: 30" Electric Ranges conform to U.L. requirements for 0" spacing from walls below countertops. Allow 1-1/2" spacing from the side of the range to adjacent vertical walls above the cooktop surface.

Receptacle Locations: Locally approved flexible service cord or conduit must be used because terminals are not accessible after range installation. See shaded area in drawing for location of electrical outlet box. Recommended outlet locations allow range to be installed directly against rear wall.


Installation Information: Before installing, consult installation instructions packed with product for current dimensional data.





HOTPOINT

RB790SD– Hotpoint 30" Free-Standing Electric Range



Features and Benefits

- Self-Clean Oven Conveniently cleans the oven cavity without the need for scrubbing
- Ceramic Glass Cooktop A smooth cooktop surface makes cleaning quick and easy
- Ribbon Heating Elements Provide powerful heat beneath a smooth glass surface to ensure even heat and fast warm-up times
- Super-Large Oven Capacity Provides an impressively large oven interior for cooking more dishes and large meals at one time
- Electronic Oven Controls One-touch electronic pads are easy-to-use and allow for simple oven operation
- Standard Window Provides a convenient viewing area to check the progress of food
- Frameless Glass Oven Door Offers an easy-to-clean and stylish design that blends seamlessly into existing cabinetry
- Model RB790SDSA Silver metallic