

ELITE-15 LINEAR FILTERING AC POWER SOURCE



Unparalleled Power Purification and Protection

FEATURES

- · Linear Filtering Technology for unequaled audio / video clarity
- Series Multi-Stage Protection for virtually maintenance-free AC surge suppression
- Retractable LED lamps illuminate a cabinet or rack full of equipment
- · Zero ground contamination circuitry protects critical digital components
- · Compact chassis design single rack space with removable rack mounts

DESCRIPTION

For over 32 years, Furman has pioneered the development of AC power products for the most demanding audio, video, and broadcast professionals. Though the need for pristine AC power is nothing new, the Elite-15's technology and its unique implementation are revolutionary and without peer.

The extreme AC demands encountered in the professional audio/video arena have required technological developments far in excess of typical home theater/audiophile power products.

In studios, live sound, and broadcast facilities, breakdown is unacceptable. Equipment failure or poor performance is costly. The same is true of today's home theater. Our solution based technology, extensive engineering expertise, and robust build quality have answered the challenge of today's corrupted power lines, and led to the creation of the Elite-15.

Today's power lines are plagued with RF and EMI noise. When connecting sensitive equipment to your home's power outlet,

AC noise couples into your system's critical components. This AC noise masks low level signals and cripples performance. This low level content is critical because it relays the crucial harmonics and ambience in audio, as well as the depth and clarity in video. With Furman's exclusive Linear Filtering Technology, televisions, projectors, DVD players, amplifiers, and processors are fed linearly-filtered AC power. This dramatically reduces noise, ensuring consistent peak operation regardless of load conditions or the time of day. For the first time, you will see and hear your theater or audio system as it should be – uncompromised.

Another critical feature is our exclusive Series Multi-Stage Protection. This virtually maintenance-free surge suppression assures the highest level of AC protection possible, without sacrificing itself when the offending surge is severe – no damaged equipment, no

service calls, no down time. Our digital AC voltage meter allows precise measurement of the incoming AC line voltage, (a valuable asset when monitoring systems that are connected to today's potentially poor power grids). Further, our famous retractable front panel LED lamps allow easy viewing of either a rack or cabinet full of equipment, even when your theater lights are off.

When employing the Elite-15, you will notice far clearer, stunningly focused sound and visual images from your system. Video presentation will be crisp and colors true with greater gray and black scale definition, as well as noticeably improved depth and clarity. Many of the technological advances previously available only in our flagship Reference Conditioners are cornerstones of the Elite series. Now everyone can reap the benefits of unrivaled power purification and unequalled surge protection.



ELITE-15 SPECIFICATIONS

AC Current Capacity:

Input - 15 Amp capacity required

Output - 15 Amps RMS (maximum, all outlets combined - continuous)

Linear Noise Attenuation:

Transverse (Differential) Mode:

>40 dB from 10Khz. - 100 kHz. >80 dB from 100 Khz. - 1GHz.

(Linear attenuation curve from 0.05 – 100 ohms line impedance)

Transient Voltage Surge Suppression:

 $120\,\text{VAC} - \text{Series Multi-Stage Protection} \, - \, \text{Non-Sacrificial with Zero Ground Contamination}.$

(188 V peak clamping @ 6000V 3000A input)

 $Extreme\ Voltage\ Shutdown\ (>135\ VAC)$

Telco

Cable / Satellite (less than .1 dB insertion loss)

Power Consumption:

6 Watts for display and control circuits independent of actual load.

Outlets:

- 1 (linearly filtered outlet front panel
- 2 (linearly filtered outlets rear panel
- 4 (linearly filtered outlets with additional ultrasonic filtering for digital or video components)

Dimensions:

2.15" H x 17" W x 14.75" D (Standard 1 RU height without feet)

Weight:

11 lbs.

Safety Agency Listing:

NRTL-C

3-Year Connected Equipment Warranty:

The Furman ELITE-15 features a three year warranty covering the unit and connected equipment. (See manual for details)

Engineered in the USA

Furman Sound, LLC • 1690 Corporate Circle • Petaluma, CA. 94954 USA Phone: (707) 763-1010 • Fax: (707) 763-1310 • www.FurmanSound.com