

USB Network Adapter

Network Through
Your USB Port!



USB Network Adapter (USB10T)

Benefits

- Connect to Any 10BaseT Ethernet Network Using Your USB Port
- Fast 8Mbps Data Transfer Rate
- Bus Powered – No External Power Supply Needed
- Easy and Fast Installation
- Free Technical Support
- 1-Year Limited Warranty

Features

- One B-type USB Port For a Standard USB Cable
- One RJ-45 10BaseT Port For a 10BaseT Twisted Pair Cable
- Connects to 10BaseT and 10/100 Ports and Any USB Port on a Windows 98 or 2000 PC
- Compatible with Virtually All USB-enabled PCs
- Fast 8Mbps Data Throughput with 6Mbps Burst Transfer
- No External Power Supply Required
- Low Power Consumption Rate of 75mA
- Plug-and-Play Compatible with Windows 98 and Windows 2000 for Easy Installation
- Free Technical Support and Driver Upgrades
- 1-Year Limited Warranty

The USB Network Adapter allows you to instantly connect to a network from any Windows 98, Windows 2000 USB-enabled PC, notebook PC, or a USB hub. Connect a standard Category 5 network cable to one end of the adapter, connect the other end to your PC or USB hub with a standard USB cable, install the driver included, and go. You'll be networked in no time.

USB stands for Universal Serial Bus, a standard for connecting peripherals to your PC with little or no configuration, and without having to open up your computer. The USB Network Adapter also features a low power consumption rate to preserve battery life if you're using a notebook. Connecting to a 10Mbps network has never been easier.

Specifications

Model Number	USB10T
Standards	IEEE 802.3, ISO 8802/3, USB version 1.1
Protocol	CSMA/CD
Ports	1 10BaseT RJ-45 Port, 1 USB Type B (female) Port
Transfer Rate	Maximum 8Mbps (Buffered)
Memory Buffer	32KB
Cabling	Network: UTP/STP Category 3 or 5 100 meters (328 feet) Maximum USB: Standard Shielded USB Cable 5 meters (16.4 feet) Maximum
Speed	10Mbps
Duplex	Half Duplex
LEDs	Link, Transmit/Receive

Environmental

Dimensions	3.2" x 2.1" x 1.0"
Unit Weight	2.0 oz.
Power Input	5V Bus Power from USB Host Controller or USB Hub
Certifications	FCC Class B, CE Mark Commercial
Operating Temp.	32°F to 104°F (0°C to 40°C)
Storage Temp.	-4°F to 158°F (-20°C to 70°C)
Operating Hum.	10% to 85%, Non-Condensing
Storage Hum.	5% to 90%, Non-Condensing

Package Contents

USB Network Adapter

- One USB Network Adapter
- One USB Cable
- One Driver Disk
- One User Guide and Registration Card

(Model No.: USB10T)

Sales	(800) 546-5797
Support	(800) 326-7114
Fax	(949) 261-8868
Email	sales@linksys.com
Web	www.linksys.com

