

**speco technologies™**

## 17" Color LCD A/V Monitor with TV Tuner & Remote Control



**Built-in TV  
Tuner**



Includes remote control

**VM-TV17LCD**

This 17" color active matrix TFT liquid crystal display provides a superior quality picture with a depth of less than 3 inches. The VM-TV17LCD includes a TV tuner and has a multitude of inputs including A/V, antenna/cable, VGA and S-Video.

### Features

- Built-in TV tuner with IR remote control
- High contrast color TFT LCD display supports resolution up to 1280 x 1024 @75Hz
- Compatible with IBM VGA, IBM SXGA and Macintosh standards
- Imbedded audio system provides excellent sound performance
- A/V, S-Video, VGA and antenna/cable inputs
- Power management system conforms to VESA DPMS standards
- Supports DDC 1/2B for Plug & Play compatibility
- Advanced OSD control for picture quality adjustment
- Detachable stand for wall-mounting applications (accessory mount required)

### Package Includes:

|                                   |                           |
|-----------------------------------|---------------------------|
| 17" TFT LCD TV/Monitor with stand | Built-in TV tuner         |
| Multi-function remote control     | 15 pin D-sub signal cable |
| RCA sound card cable              | AC power cable            |
| Power adapter                     | User's manual             |
| Warranty                          |                           |

Specifications subject to change

For more information contact us at:

Speco Technologies 200 New Highway, Amityville, NY 11701 Web: [www.specotech.com](http://www.specotech.com)  
Toll Free: 1-800-645-5516 In Metro NY: 631-957-8700 Fax: 631-957-9142 or 631-957-3880



# VM-TV17LCD

17" Color LCD A/V  
Monitor with TV Tuner &  
Remote Control

## Specifications

|                        |   |
|------------------------|---|
| Max Resolution         | 1280(H) x 1024(V) (SXGA)  |
| LCD Display            | 17" Active Matrix TFT LCD Panel   |
| Pixel Pitch            | 0.264(H) x 0.264(V) mm  |
| Contrast Ratio         | 400:1   |
| Brightness             | 350 cd/m2   |
| Response Time          | Tr 15ms; Tf 10ms  |
| Display Color          | 16.777M   |
| Angle Viewing:         |   |
| Left/Right             | ±85°  |
| Up/Down                | ±85°  |
| PC Interface           | RGB analog or digital, 0.7v peak to peak  |
| Video Sync             | TTL positive or negative  |
| Display Mode           | TV, A/V, VGA, SVGA, XGA, SXGA   |
| Frequency              | (Horizontal) 31.5-80KHZ<br>(Vertical) 56-75 HZ  |
| Signal Connectors      | A/V, S-Video, "F" connector for TV, D-sub 15-pin  |
| Front Controls         | Auto adjust with LED, OSD Menu, +/- Adjustment  |
| OSD Menu               | Contrast, Brightness, Auto Adjust, Clock, Phase,<br>H-Position, V-Position, Input: (PC, TV, A/V, S-Video) |
| Power Adapter Included | AC Input: 100-240V~1.8A, 50-60Hz DC Input: 12V/4.0A   |
| Operating Conditions   | Temperature: 32°F to 122°F<br>Humidity: 20% ~ 95%   |
| Certification          | BSMI, FCC (DOC), CE-B, UL, TUV/GS   |
| Weight                 | 11 lbs.   |
| Dimensions             | 16.25"(H) x 16.30"(V) x 7.68"(D)  |
| Remote Control         | Multi function remote control included  |



For more information contact us at:

Speco Technologies 200 New Highway, Amityville, NY 11701 Web: [www.specotech.com](http://www.specotech.com)  
Toll Free: 1-800-645-5516 In Metro NY: 631-957-8700 Fax: 631-957-9142 or 631-957-3880