

## Commercial Specifications

### Picture/ Display

- Panel Size 15"/ 36 cm
- Phosphor P22
- Recommended Display Area 270 x 202 mm (10.6" x 8.0")
- Dot Pitch 0.28 mm
- Horizontal Dot Pitch 0.24 mm
- White Chromaticity, 9300° K  $x = 0.283 / y = 0.297$
- Max. Resolution 1024 x 768 @ 60 Hz
- Recommended Resolution 800 x 600 @ 85 Hz
- Factory Preset Modes 6 modes:  
720 x 400 @ 70 Hz, 640 x 480 @ 60 Hz,  
640 x 480 @ 75 Hz, 800 x 600 @ 75 Hz,  
800 x 600 @ 85 Hz, 1024 x 768 @ 60 Hz
- Factory Preload Modes 9 modes
- Video Dot Rate 75 MHz
- Horizontal Scanning Frequency 30 - 54 KHz
- Vertical Scanning Frequency 50 - 120 Hz
- Recommended Refresh Rate 85 Hz

### Connectivity

- Cables D-sub Video Cable, Power Cord
- Sync Input Impedance (ohm) 4.7 k
- Video Input Impedance (ohm) 75
- Video Input Signal Levels 0.7 Vpp
- Video Sync Input Signal Separate Sync
- Video Sync Polarities Positive and Negative
- Cable Connection AC Power in

### Convenience

- Convenience Enhancements On-screen Display  
Left/Right, Menu,  
Power On/Off  
DDC 2B  
Windows 98/ME/2000/XP  
CCC
- Monitor Controls +/- 45°  
-4° to 14°
- Plug & Play Compatibility
- Regulatory Approvals
- Swivel
- Tilt

### Accessories

- Included Accessories AC Power Cord  
Yes
- User Manual

### Dimensions

- Depth (with base) 380 mm
- Height (with base) 369 mm
- Width (with base) 360 mm
- Temperature Range (Operation) 0°C to 40°C
- Temperature Range (Storage) -25°C to 65°C
- Weight 11.2 kg

### Power

- Consumption 65 W (Typical)
- Off Mode 5 W
- Power LED Indicator Off, Amber;  
Operation, Green
- Power Supply Built-in



Trademarks owned by Royal Philips Electronics  
 2004 © Royal Philips Electronics - All rights reserved  
 Microsoft and Windows are registered trademarks of Microsoft Corporation.  
 All data subject to change without notice. Release date: April 2004  
[www.philips.com](http://www.philips.com)

# PHILIPS