PARROTT 4 Headset

Features

- Flexible boom
- Ratchet headband
- Accurate microphone adjustment to either side of the head
- Noise canceling microphone
- Ergonomic, high quality look and feel



One Front Street Rollinsford, NH 03869 USA **Toll-free (US):** (800) 742-8588 **Headquarters:** (603) 742-2888 **E-mail:** parrott@vxicorp.com **Website:** www.vxicorp.com



Technical Specifications

Transmit Specifications

Microphone:	Noise canceling electret
	Ambient Noise Suppression: 13 dB @ 1 kHz, typical
Output impedance:	Determined by sound card, usually 2.2 k Ohms
Sensitivity:	-50 dB @ 1 kHz (defined 1" from talk-side, 82 dB SPL)
Operating Current:	300 μA max.
Operating Voltage:	1.0 V DC min. to 20 V DC max.

Mechanical Specifications of VXI Computer/Voice Products

Cable:	Spiral shielded construction with polyethylene insulation and PVC jacket
Connectors:	3.5 mm stereo plug with tip and ring to mic & sleeve to ground.
Microphone boom:	Flexible, with positioning memory; swivels 30 degrees and rotates 360 degrees
Mounting:	Left or right ear placement
Construction:	ABS plastic, soft ear pad
Headband:	#316 stainless steel ratchet positioning