

- Stereo
- Black Line D
- Scart
- Teletext
- · Headphone socket
- 60 Pre-selections
- NICAM reception (4423 model only)









- Stereo
- Black Line D
- Scart
- Teletext
- · Headphone socket
- 60 Pre-selections
- NICAM reception (4423 model only)











- Stereo
- Black Line D
- Scart
- Teletext
- Headphone socket
- 60 Pre-selections
- NICAM reception (4423 model only)











- Stereo
- Black Line D
- Scart
- Teletext
- · Headphone socket
- 60 Pre-selections
- NICAM reception (4423 model only)











- Stereo
- Black Line D
- Scart
- Teletext
- · Headphone socket
- 60 Pre-selections
- NICAM reception (4423 model only)











- Stereo
- Black Line D
- Scart
- Teletext
- · Headphone socket
- 60 Pre-selections
- NICAM reception (4423 model only)











- Stereo
- Black Line D
- Scart
- Teletext
- · Headphone socket
- 60 Pre-selections
- NICAM reception (4423 model only)


Black Line D







- Stereo
- Black Line D
- Scart
- Teletext
- · Headphone socket
- 60 Pre-selections
- NICAM reception (4423 model only)












- Stereo
- Black Line D
- Scart
- Teletext
- · Headphone socket
- 60 Pre-selections
- NICAM reception (4423 model only)












- Stereo
- Black Line D
- Scart
- Teletext
- · Headphone socket
- 60 Pre-selections
- NICAM reception (4423 model only)










- Stereo
- Black Line D
- Scart
- Teletext
- · Headphone socket
- 60 Pre-selections
- NICAM reception (4423 model only)










- Stereo
- Black Line D
- Scart
- Teletext
- · Headphone socket
- 60 Pre-selections
- NICAM reception (4423 model only)











· Black Line D

For an excellent image with high sharpness and contrast and less reflection; for brillant colours and improved daylight viewing.

Scart

To connect videorecorders, but also games and computers. The scart is fully wired and so is RGB compatible.

Teletext

Easy computer controlled teletext for quick and easy access to the information transmitted by the TV broadcaster.

· NICAM reception (4423 model only).

Supporting Features

- · Headphone socket
- · 60 Pre-selections
- Automatic switch-off
- · Low standby power 6 watts
- Remote control for installation and operation
- · Menu driven operation
- Hyperband Reception
- · Multistandard Reception Optional

Technical specifications

Chassis

• Type : L6.2

Picture

Screen Diameter : 25" / 28"
 Visual Screen : 59 / 66 cm

Sound

• RMS output : 2 x 3W

• Loudspeakers : Two 4" full range side

firing

Operation

Remote control : RC8205Settings via OSD of : Volume

Brightness Contrast Colour Sleep timer : 120 minutes

Timer
 Programs
 120 minutes
 60 pre-selections

Teletext

Reception standards : WSTMemories : 1-page

Reception

• Tuning system : 60 fold VST

 Transmission system: /00, /11

/00,/11 PAL B/G
/01 PAL BG
SECAM LL'
/58 PAL BG DK

SECAM BG DK

Channel selections

/00,/01,/11,/58 VHF, UHF, S, H

Sound system

/00,/58 2 carriers FM /01,/11 Nicam

Connections

 Rear
 Euro A/V connector (Cenelec Specified)
 Aerial input
 75 Ohm (Coax)
 Front
 Headphone (3.5 mm jack)

Miscellaneous

• Mains : AC220-240V ±10%

Power consumption : 73WStand-by power : 6W

- with stand (wxhxd) :

Weight (excl. pack.) : 25.2kg / 29.7kg
 Weight (incl. pack.) : 29.7kg / 34.4kg
 Weight (incl. stand) : 36.3kg / 41.1kg

Dimensions:

- TV (wxhxd) : 65.0x50.6x43.5cm/25" 71.3x54.9x46.1cm/28"

- Packaging (wxhxd) : 76.9x62.7x56.2cm/25" 83.1x67.0x59.0cm/28"

> 76.9x70.7x56.2cm/25" 83.1x75.0x59.0cm/28"

• Cabinet Painting : Mid Grey 10763



RC 8205

Release date : June 1997

Predecessor(s) : 25PT4401/28PT4401

Date of issue : May 1997

Features and specifications subject to change without notice







· Black Line D

For an excellent image with high sharpness and contrast and less reflection; for brillant colours and improved daylight viewing.

Scart

To connect videorecorders, but also games and computers. The scart is fully wired and so is RGB compatible.

Easy computer controlled teletext for quick and easy access to the information transmitted by the TV broadcaster.

· NICAM reception (4423 model only).

Supporting Features

- Headphone socket
- 60 Pre-selections
- Automatic switch-off
- Low standby power 6 watts
- Remote control for installation and operation
- Menu driven operation
- Hyperband Reception
- Multistandard Reception Optional

Technical specifications

Chassis

: L6.2 Type

Picture

 Screen Diameter : 25" / 28" · Visual Screen : 59 / 66 cm

Sound

· RMS output 2 x 3W

Two 4" full range side Loudspeakers

firing

Operation

Remote control RC8205 Settings via OSD of Volume

Brightness Contrast Colour Sleep timer 120 minutes

Timer Programs 60 pre-selections

Teletext

Release date

Predecessor(s)

· Reception standards : WST Memories : 1-page Reception

 Tuning system : 60 fold VST

• Transmission system : /00, /11

PAL B/G PAL BG /01 SECAM LL' PAL BG DK /58

SECAM BG DK

· Channel selections

/00./01./11./58 VHF, UHF, S, H

Sound system

/00,/58 2 carriers FM /01,/11 Nicam

Connections

: Euro A/V connector Rear (Cenelec Specified) Aerial input 75 Ohm (Coax) Front

Headphone (3.5 mm jack)

Miscellaneous

AC220-240V ±10% Mains

Power consumption 73W Stand-by power 6W

Weight (excl. pack.) 25.2kg / 29.7kg Weight (incl. pack.) 29.7kg / 34.4kg Weight (incl. stand) 36.3kg / 41.1kg

Dimensions:

- TV (wxhxd) 65.0x50.6x43.5cm/25" 71.3x54.9x46.1cm/28"

- Packaging (wxhxd) : 76.9x62.7x56.2cm/25" 83.1x67.0x59.0cm/28"

76.9x70.7x56.2cm/25"

- with stand (wxhxd) : 83.1x75.0x59.0cm/28"

: Mid Grey 10763 · Cabinet Painting

Features and specifications subject to change without notice



6



: June 1997

25PT4401/28PT4401







· Black Line D

For an excellent image with high sharpness and contrast and less reflection; for brillant colours and improved daylight viewing.

Scart

To connect videorecorders, but also games and computers. The scart is fully wired and so is RGB

Easy computer controlled teletext for quick and easy access to the information transmitted by the TV broadcaster.

· NICAM reception (4423 model only).

Supporting Features

- Headphone socket
- 60 Pre-selections
- Automatic switch-off
- Low standby power 6 watts
- Remote control for installation and operation
- Menu driven operation
- Hyperband Reception
- Multistandard Reception Optional

Technical specifications

Chassis

: L6.2 Type

Picture

 Screen Diameter : 25" / 28" · Visual Screen : 59 / 66 cm

Sound

· RMS output 2 x 3W

Two 4" full range side Loudspeakers

firing

Operation

Remote control RC8205 Settings via OSD of Volume

Brightness Contrast Colour Sleep timer 120 minutes

: June 1997

: May 1997

25PT4401/28PT4401

Timer Programs 60 pre-selections

Teletext

Release date

Predecessor(s) Date of issue

· Reception standards : WST Memories : 1-page Reception

/58

 Tuning system : 60 fold VST

• Transmission system : /00, /11

PAL B/G PAL BG /01 SECAM LL'

PAL BG DK

SECAM BG DK

· Channel selections

/00./01./11./58 VHF, UHF, S, H Sound system

/00,/58

2 carriers FM /01,/11 Nicam

Connections

: Euro A/V connector Rear (Cenelec Specified) Aerial input 75 Ohm (Coax)

 Front Headphone (3.5 mm jack)

Miscellaneous

 Mains AC220-240V ±10%

Power consumption 73W Stand-by power 6W

Weight (excl. pack.) 25.2kg / 29.7kg Weight (incl. pack.) 29.7kg / 34.4kg Weight (incl. stand) 36.3kg / 41.1kg

Dimensions:

- TV (wxhxd) 65.0x50.6x43.5cm/25" 71.3x54.9x46.1cm/28"

- Packaging (wxhxd) : 76.9x62.7x56.2cm/25"

83.1x67.0x59.0cm/28"

- with stand (wxhxd) : 76.9x70.7x56.2cm/25"

83.1x75.0x59.0cm/28"

· Cabinet Painting : Mid Grey 10763

Features and specifications subject to change without notice









RC 8205

- Menu +

1-11

PHILIPS



· Black Line D

For an excellent image with high sharpness and contrast and less reflection; for brillant colours and improved daylight viewing.

Scart

To connect videorecorders, but also games and computers. The scart is fully wired and so is RGB compatible.

Teletext

Easy computer controlled teletext for quick and easy access to the information transmitted by the TV broadcaster.

· NICAM reception (4423 model only).

Supporting Features

- · Headphone socket
- · 60 Pre-selections
- Automatic switch-off
- · Low standby power 6 watts
- · Remote control for installation and operation
- · Menu driven operation
- Hyperband Reception
- · Multistandard Reception Optional

Technical specifications

Chassis

• Type : L6.2

Picture

Screen Diameter : 25" / 28"
 Visual Screen : 59 / 66 cm

Sound

• RMS output : 2 x 3W

Loudspeakers : Two 4" full range side

firing

Operation

Remote control : RC8205Settings via OSD of : Volume

Brightness Contrast Colour Sleep timer : 120 minutes

Timer : 120 minutesPrograms : 60 pre-selections

Teletext

Reception standards : WSTMemories : 1-page

Reception

/58

• Tuning system : 60 fold VST

• Transmission system :

/00, /11 PAL B/G /01 PAL BG SECAM LL'

PAL BG DK SECAM BG DK

Channel selections

/00,/01,/11,/58 VHF, UHF, S, H

Sound system

/00,/58 2 carriers FM /01,/11 Nicam

Connections

 Rear
 : Euro A/V connector (Cenelec Specified)
 Aerial input
 : 75 Ohm (Coax)

• Front : Headphone (3.5 mm jack)

Miscellaneous

• Mains : AC220-240V ±10%

Power consumption : 73WStand-by power : 6W

- with stand (wxhxd) :

Weight (excl. pack.) : 25.2kg / 29.7kg
 Weight (incl. pack.) : 29.7kg / 34.4kg
 Weight (incl. stand) : 36.3kg / 41.1kg

Dimensions:

- TV (wxhxd) : 65.0x50.6x43.5cm/25" 71.3x54.9x46.1cm/28"

- Packaging (wxhxd) : 76.9x62.7x56.2cm/25" 83.1x67.0x59.0cm/28"

76.9x70.7x56.2cm/25"

• Cabinet Painting 83.1x75.0x59.0cm/28"
• Cabinet Painting : Mid Grey 10763



RC 8205

Release date : June 1997

Predecessor(s) : 25PT4401/28PT4401

Date of issue : May 1997

Features and specifications subject to change without notice







· Black Line D

For an excellent image with high sharpness and contrast and less reflection; for brillant colours and improved daylight viewing.

Scart

To connect videorecorders, but also games and computers. The scart is fully wired and so is RGB compatible.

Easy computer controlled teletext for quick and easy access to the information transmitted by the TV broadcaster.

· NICAM reception (4423 model only).

Supporting Features

- Headphone socket
- 60 Pre-selections
- Automatic switch-off
- Low standby power 6 watts
- Remote control for installation and operation
- Menu driven operation
- Hyperband Reception
- Multistandard Reception Optional

Technical specifications

Chassis

: L6.2 Type

Picture

 Screen Diameter : 25" / 28" · Visual Screen : 59 / 66 cm

Sound

· RMS output 2 x 3W

Two 4" full range side Loudspeakers

firing

Operation

Remote control RC8205 Settings via OSD of Volume

Brightness Contrast Colour Sleep timer 120 minutes

Timer Programs 60 pre-selections

Teletext

Date of issue

· Reception standards : WST Memories : 1-page Reception

 Tuning system : 60 fold VST

· Transmission system : /00, /11

PAL B/G PAL BG /01 SECAM LL' /58

PAL BG DK

SECAM BG DK

· Channel selections

/00./01./11./58 VHF, UHF, S, H Sound system

/00,/58

2 carriers FM /01,/11 Nicam

Connections

: Euro A/V connector Rear (Cenelec Specified) Aerial input 75 Ohm (Coax)

 Front Headphone (3.5 mm jack)

Miscellaneous

 Mains AC220-240V ±10%

Power consumption 73W Stand-by power 6W

Weight (excl. pack.) 25.2kg / 29.7kg Weight (incl. pack.) 29.7kg / 34.4kg Weight (incl. stand) 36.3kg / 41.1kg

Dimensions:

Cabinet Painting

- TV (wxhxd) 65.0x50.6x43.5cm/25" 71.3x54.9x46.1cm/28"

- Packaging (wxhxd) : 76.9x62.7x56.2cm/25" 83.1x67.0x59.0cm/28"

76.9x70.7x56.2cm/25"

: Mid Grey 10763

- with stand (wxhxd) : 83.1x75.0x59.0cm/28"

Features and specifications subject to change without notice





: June 1997 Release date 25PT4401/28PT4401 Predecessor(s)

: May 1997







· Black Line D

For an excellent image with high sharpness and contrast and less reflection; for brillant colours and improved daylight viewing.

Scart

To connect videorecorders, but also games and computers. The scart is fully wired and so is RGB compatible.

Easy computer controlled teletext for quick and easy access to the information transmitted by the TV broadcaster.

· NICAM reception (4423 model only).

Supporting Features

- Headphone socket
- 60 Pre-selections
- Automatic switch-off
- Low standby power 6 watts
- Remote control for installation and operation
- Menu driven operation
- Hyperband Reception
- Multistandard Reception Optional

Technical specifications

Chassis

: L6.2 Type

Picture

 Screen Diameter : 25" / 28" · Visual Screen : 59 / 66 cm

Sound

· RMS output 2 x 3W

Two 4" full range side Loudspeakers

firing

Operation

Remote control RC8205 Settings via OSD of Volume

Brightness Contrast Colour Sleep timer 120 minutes

Timer Programs 60 pre-selections

Teletext

· Reception standards : WST Memories : 1-page Reception

 Tuning system : 60 fold VST

• Transmission system : /00, /11

PAL B/G PAL BG /01 SECAM LL' /58

PAL BG DK

SECAM BG DK

· Channel selections

/00./01./11./58 VHF, UHF, S, H Sound system

/00,/58

2 carriers FM /01,/11 Nicam

Connections

: Euro A/V connector Rear (Cenelec Specified) Aerial input 75 Ohm (Coax) Front Headphone (3.5 mm jack)

Miscellaneous

AC220-240V ±10% Mains

Power consumption 73W Stand-by power 6W

- with stand (wxhxd) :

Weight (excl. pack.) 25.2kg / 29.7kg Weight (incl. pack.) 29.7kg / 34.4kg Weight (incl. stand) 36.3kg / 41.1kg

Dimensions:

- TV (wxhxd) 65.0x50.6x43.5cm/25" 71.3x54.9x46.1cm/28"

- Packaging (wxhxd) : 76.9x62.7x56.2cm/25" 83.1x67.0x59.0cm/28"

> 76.9x70.7x56.2cm/25" 83.1x75.0x59.0cm/28"

: Mid Grey 10763 · Cabinet Painting



RC 8205

: June 1997 Release date

25PT4401/28PT4401 Predecessor(s)

Date of issue : May 1997 Features and specifications subject to change without notice



