Product highlights

- Black Line D picture tube
- Contrast Plus
- Sharpness Control
- Smart Picture
- Smart Sound
- Smart Listening (Delta Volume & AVL)
- Plug & Play
- Easy Tune (ATS/ACI)
- 10 pages Smart Text (Favourite Pages)





Colour Television 25/28PT4255 25/28PT4275







PHILIPS





Product Information

Picture

Screen size

Picture tube Viewing area

Iron Mask

28": 67 cm Smart Picture Modes

Soft, Natural, Rich, Personal

25" (63 cm)

28" (70 cm)

Black Line D

25": 59 cm

Contrast Plus Sharpness Control Color Temperature Control Noise Reduction 4:3 Expand

Sound

Sound output Loudspeakers Smart Sound Modes

2 x 5 Watts RMS Full Range Speakers Movie, Music, Speech, Personal

PLL digital tuning

75 Ohm Coaxial

80 presets

See table NTSC 3.58 / 4.43

See table

UV, S and Hyperband

Ultra Bass Smart Listening (Delta Volume & AVL) Bilingual switch on remote control

Reception

Tuning system Tuner Channel selection Aerial input TV systems Video playback Stereo systems Plug and Play

Easy Tune (ATS / ACI) : UK, FR, BE, NL, CH, DE, AT, ES. PL. IT. ND

Teletext

Reception standards TOP / FLOF 10 page memory Smart Text (4 favourite pages)

Connectors

Stereo headphone out (3.5 mm) Front Ext 1: Scart CVBS In / Out + RGB In Rear Ext 2: Scart CVBS In / Out + Y/C In

Operation

Remote control RC2543/01 Side TV/VCR switch on remote control Program Information Line Sleeptimer (240 minutes)

Measurements

Mains 220 - 240V, 50 Hz Power consumption • 25" - 83Watts (normal operation) • 28" – 97Watts (normal operation) • 25/28" - 7Watts (Standby) Net weight 25" – 28 kg (approx.)
28" – 36 kg (approx.) Gross weight • 25" - 30 kg (approx.) • 28" - 38 kg (approx.)

Set dimension 25" – 690 x 452 x 541 (W x D x H mm)

- 28" 763 x 476 x 580 (W x D x H mm) Box dimension
- 25" 791 x 552 x 686 (W x D x H mm)
- 28" 856 x 597 x 725 (W x D x H mm)

Cabinet Colour

Light Grey (10762)

Product Highlights Black Line D picture tube

The Black Line D picture tube offers excellent images with high sharpness and contrast and less reflection for brilliant colors and improved viewing in daylight conditions.

Contrast Plus

A special circuitry has been incorporated into this receiver to enhance the darker portions of the picture for added realism and overall picture quality.

Smart Picture

A touch of the SMART PICTURE button on the remote control provides the option of selecting one of four preset positions (Soft, Natural, Rich, Personal) to enjoy excellent viewing under different lighting conditions. Select the desired option and all important picture elements are instantly adjusted to optimize viewing pleasure. 'Rich' for bright daylight conditions, 'Soft' for dark room settings, 'Natural' for normal ambient conditions and 'Personal' for individual preference.

Smart Sound

A touch of the SMART SOUND button on the remote control provides the option of selecting one of four preset positions (Movie, Music, Speech, Personal) to optimize each individual sound preference when viewing different programs or sources.

Easy Tune (ATS / ACI)

A no fuss and easy way to install and store channels in any favorite order.

Sleeptimer

The Sleeptimer automatically turns the TV off at a preset time of up to 240 minutes from the time the feature is activated. Sleeptimer settings are programmed in 15, 30 and 60-minute increments.

Plug and Play

No problem anymore to install your new TV. You choose the language you are more famliar with, the country you are in and the TV will install automatically all available programs.

Smart Listening

It is the combination of Delta Volume and AVL. The former avoids undesirable changes in volume, due to different sound modulations of the programs, during channel prowsing. The latter avoids rapid increase in volume like, for exemple, in case of commercials.

stereo system					transmission system						
2CS DK	NICAM DK	2CS BG	NICAM BG	NICAM I	NICAM LL'	PAL BG	PAL DK	PAL I	SECAM BG	SECAM DK	SECAM LL'
		•	•			•					
		•	•	•	•	•		•	•		•
L9SS August	t 1999										
	DK 21PT4 L9SS August	DK DK 21РТ4254	NICAM DK 2CS BG 1000 0 21PT4254 0 L9SS 1999	system 2CS DK NICAM DK 2CS BG NICAM BG 1 0 0 0 21PT-4254 L9SS August 1999 54 54 54	system2CS DKNICAM DKNICAM BGNICAM BG1000100021PT+J254 L9SS August 1999System SystemSystem SystemSystem System	system2CS DKNICAM DK2CS BGNICAM BGNICAM DL'111111111121PT4254 L9SS August 1999111	system2CS DKNICAM DK2CS BGNICAM BGNICAM LL'PAL BGImage: Image: Im	system2CS DKNICAM DK2CS BGNICAM BGNICAM LL'PAL BGPAL DK11111111111111111121PT4254 L9SS August 1999111	system 2CS DK NICAM DK 2CS BG NICAM BG NICAM BG PAL DK PAL DK 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	system2CS DKNICAM DKNICAM BGNICAM INICAM BGPAL BGPAL DKPAL BGPAL BGPAL BGSecAM BG111<	system:2CS DKNICAM DKNICAM BGNICAM NICAM BGNICAM BGPAL BGPAL DKPAL SECAM BGSECAM BG111 </td

Features and specifications subject to change without notice

PHILIPS



