

TW-432F Monolight Specifications

Maximum Watt / Seconds:	400 w/s
Recycle Time:	2.1 Seconds @ full power
Flash Variability:	Full to 1/32 in .5 EV Steps
Voltage Stabilization:	Yes
Built-in Slave Cell:	Yes, Switchable
Fan Cooled:	Yes
Weight:	3.5 lbs
Dimensions:	4-1/4 x 8-7/8
Circuit Sync:	10 VDC Low Voltage / Current
Flashtube:	User replaceable UV Coated Flashtube
Modeling Light Wattage:	150w, User Replaceable
Fuse Rating:	5 amps, User Replaceable



Accepts All CX Series Accessories

Utilize any of the CX Series head accessories with your new Twinkle TW-432F



Warranty

The T4222-PS kit has a limited two year warranty. The manufacturer warranty is void if the unit is opened by anyone other than an authorized Dyna-Lite service station. Dyna-Lite reserves the right to dispute a warranty claim if damage is due to unit being mishandled, dropped, or used in any way other than intended use.

dyna-lite
Flash Equipment

1050 Commerce Ave
Union, NJ 07083
800-722-6638 / Fax 908-686-6682

dyna-lite
Flash Equipment

Instruction Manual

T4222-PS

The power and portability of professional lighting...at an affordable price



TW-432F Monolight

Congratulations on the purchase of your new Dyna-Lite TW432F monolight. You will begin to find out as you begin using your new Twinkle that there are plenty of high end features in the TW-432F's compact 3.5 lb body. From the 2.1 second recycling time to the power variation, there are plenty of professional features that open up a world of possibilities you can explore accomplish with the new 400 w/s Twinkle TW=432F.

T4222-PS Kit Contents



1. 2 - TW-432F Monolights
2. 2 - 6' Light Stands
3. 2 - PC Connection Cords
4. 2 - 40" White / Black Umbrellas
5. 2 - Power Cables
6. Carrying Case

Using Your TW-432F Monolight

