

IR Day/Night Color Weatherproof Cameras

- 12 or 24 LEDs
- 40' or 80' RangeIP67 for Outdoor Use
- Low Power Consumption

Model	Lens	Angle	LEDs
EV-132C-DW2Q	2.9mm	120°	12
EV-1323C12DWQ	4.3mm	78°	12
EV-132C-DWL6Q	6.0mm	53°	24
EV-132C-DWL8Q	8.0mm	39°	24
EV-132C-DWLDQ	12.0mm	26°	24
EV-132C-DWLHQ	16.0mm	19°	24

Viewing angles are approximate

SECO-LARM's IR Day/Night Color Cameras with 12 IR LEDs for up to 40' range or 24 IR LEDs for up to 80' range incorporate the Sony CCD to provide a clear picture and outstanding resolution (420 TV lines) at a very low lux (0.1 lux LED off, 0 lux LED on). They combine a rugged die-cast aluminum construction with a unique weatherproof (IP67) design and sunscreen for indoor or outdoor use.



Copyright 2007 SECO-LARM U.S.A., Inc. All rights reserved. The SECO-LARM policy is one of continual development. For that reason, SECO-LARM reserves the right to change prices and specifications without notice. SECO-LARM is not responsible for misprints.



1.949.261.2999 (CA & Int'l) Email: info@seco-larm.com

Fax: 1.949.261.7326 1.800.662.0800 Website: www.seco-larm.com



S. ENFORCE

Technical Specifications:

/	12 LED Cameras	24 LED Cameras	
Infrared Illumination	Up to 40'	Up to 80'	
Current consumption	60mA (LED off)	90mA (LED off)	
	160mA (LED on)	290mA (LED on)	
Chip	1/3" CCD, Sony		
S/N ratio	50dB (AGC off)		
Resolution	420 TV lines horizontal		
Pickup elements	512 x 492 pixels		
Scanning system	Interlace 2:1		
Sync	Internal		
Video output	1 Vp-p composite output, 75 ohms		
Minimum illumination	0.1 lux (LED off), 0 lux (LED on)		
Backlight compensation	Auto		
Shutter control	Auto, 1/60~1/100,000 sec.		
Gain control	Auto		
Gamma correction	0.45		
White balance	Auto		
Power source	12VDC ±10%		
Enclosure	IP67 Weatherproof		
Ambient temperature	14°~131° F (-10°~55° C)		
Dimensions	3 ¹ / ₁₆ "(L) x 2 ¹ / ₄ "(D) (78 x 57 mm)		
Sunscreen & Bracket	Included		