

Valuable functions, value-priced.

Fax machine. Printer. Copier. Scanner.

At the heart of the Xerox FaxCentre® F116 multifunction device is a robust and powerful fax machine. Yet – with its quick networkcapable printing, convenience copying, color scanning, email and internet access – it opens the door to a multitude of critical desktop resources for the single user or small office. All in a compact and truly affordable package.

FaxCentre[®] F116 / F116L



Call today. For U.S. and Canadian product information, call 1-877-362-6567. To speak to a U.S. Sales Representative, call 1-800-ASK-XEROX. Or visit us at www.xerox.com/office

Specifications

FAX

Compatibility: ITU - T.37 Modem Speed: 33.6 Kbps Compression: MMR/MR/MH/JBIG Super G3 Transmission: 3 seconds per page Dual Lines: Yes on F116L, No on F116

Resolutions

Mono: Standard (100 x 200 dpi) Fine (200 x 200 dpi) Super Fine (400 x 200 dpi) Photo Mode (200 x 200 dpi) Color. Standard (100 x 100 dpi) Fine (200 x 200 dpi) Super Fine (300 x 300 dpi) Halftones: 256 levels Fax Memory: 8 MB (500 pages of ITU-T chart 1 with standard resolution) Memory Receive: Yes (Receive faxes while printing other jobs from direct connect or network) Set Prefix Option: Yes One Touch Dials: 26 Speed Dials: 500 entries with Alphanumeric search Battery Back up: None reg'd. Constant. battery = free memory for jobs Auto reduction receive: Yes, Documents automatically reduced to fit the recording (loaded) paper size Device Access/Security (Secure fax): 32 mailboxes (1 public, 31 private password-protected)

Up to 98 user codes or Dept. codes Can Also.

Lock printing of received faxes Lock Keyboard Lock number keypad Lock internet settings

CONVENIENCE PRINTING

Technology: Laser Monochrome Speed: 16 pages per minute (ppm) Resolution: 600 x 600 dpi Print Memory: 32 MB Duplex: No Connectivity - Standard: Direct connect – via USB Connectivity - Optional: Internal Network Printing Kit

CONVENIENCE COPYING

Speed: 16 ppm Resolution: 300 x 300 dpi Reduce/Enlarge: 25-400% in 1% increments Multiple Copies: Up to 99 copies Productivity: Scan Once/Print Many



CONFIGURATIONS	FaxCentre [®] F116	FaxCentre® F116/L
Copy/Print Speed	16 ppm	
First copy out time	17 seconds	
Resolution	300 x 300 dpi copy / 600 x 600 dpi print	
Processor	92 Mhz	
Connectivity	Direct Connect via USB; optional internal NIC	
Scan Resolution	300×300 dpi optical; 600×600 dpi interpolated	
Scan to e-mail	yes	
Fax Speed	33.6 Kbps	
Resolution	up to 400 x 200 dpi monochrome or up to 300 x 300 dpi color	
Transmission	3 seconds per page	
Dual Lines	No	Yes
Paper Handling Paper input capability	250 sheets	
Paper output	100 sheets	
Productivity Special features	Color scan to email	
Optional Accessories	Optional 500-sheet paper tray	
Duty Cycle	2500 pages / month	

SCANNING (Color and Monochrome) Avg. Scan Speeds:

100 x 200 dpi: 1.8 seconds per page 300 x 300 dpi: 5.4 seconds per page Color: 16 seconds per page Maximum Resolution: Optical 300 x 300 600 x 600 Interpolated Scan Driver: TWAIN Standard Scanning Software Document Management and OCR: ScanSoft® PaperPort[®] and OmniPage[®] Software

EMAIL

Compatibility: ITU T37 Mail Protocol - sending: SMTP SMTP Authentication: Yes (only RFC 1734) Mono email format: TIFF-F, PDF Color email Format: JPEG

LAN ACCESS

Ethernet: 10 BaseT/100BaseT Plug & Play configuration: Yes (DHCP and BOOTP) Internet Protocol: TCP/IP DNS Queries: Yes (2 DNS servers access) NETBIOS compatibility (for name management): Yes Respond to PING request: Yes

MEDIA HANDLING

Input Paper Capacity Main Tray: 250 sheets, A4, Legal, Letter, A5, B5-JIS, or Executive Weights: 60 x 90 gsm / 16-24 lb bond Bypass Tray: 1 sheet, A4, Legal, Letter, A5, B5-JIS, or Executive Envelope feeding: Yes (using bypass tray) Additional Tray 2 (optional): 500 sheets Automatic Document Feeder. 35 sheets Output Capacity: 100 sheets

PHYSICAL CHARACTERISTICS

Footprint: 15 3/8 x 18 1/8 x 15 3/8 in. / 389 x 460 x 390 mm Weight: 24.3 lb / 11 kg (machine only)

ELECTRICAL

Power Switch: Yes Power Requirements: 220 to 240 VAC, 50/60 Hz (Europe) 100 to 127 VAC, 50/60 Hz (N. America & Latin America) Maximum Power Consumption: 850 watts Normal Operation: 580W Ready Mode: 80W Power Saver Mode: 15 watts or less Energy Saver: ENERGY STAR® Compliant

OPERATING ENVIRONMENT

Temperature: 50°- 89.6°F, 10°- 32°C Humidity: 20 - 80%

GENERAL SPECIFICATIONS

Total Device Memory: 32 MB SDRAM; 64 MB Flash Memory Device Management: Companion Pro Software

SUPPLIES

Approximate Yields Toner-Starter Kit: 2,000 prints*; Replacement Kit: 6,000 prints* Drum Cartridge-Starter: 4,000 prints*; Replacement Photoreceptor/Drum Cartridge: 20,000 prints*

* Capacities are approximate, based on 5% coverage on an A-size page and dependent on customer job mode run length

AGENCY APPROVALS **UL** Safety

Reduce operating costs and save space by consolidating functions into one powerful, office machine.

Robust and affordable All the essentials at one low price.

- 33.6 Kbps faxing provides quick transmission of multi-page documents in as little as 3 seconds a page
- Secure fax with 31 passwordprotected mailboxes to receive documents confidentially
- Dual-line fax capabilities on F116L means that two lines are always available for transmission and/or reception
- Outstanding laser technology and PCL6 printing from PC or network for highest quality documents
- · Scanning in full color (or blackand-white) to email via the internet

Productivity-boosting High-tech features do it all.

- Faxes can be scanned and sent electronically to recipients with verification of sender
- Thanks to protected memory, saved faxes and device settings are never lost if power is interrupted
- When receiving data, the F116 automatically reduces a document to fit the loaded paper size in tray
- "Intelligent" consumables let users know when toner is low

Compact and convenient Efficiency simplifies your workday.

- · Well suited for a countertop or desktop use in offices where space is at a premium
- · Extra tray option meets the needs of high-volume users
- Easy-to-use keypad makes it a breeze to perform any function
- Text messaging to fax for communication convenience

© 2004 Xerox Corporation. All rights reserved. XEROX^{est} and FaxCentre® are trademarks of Xerox Corporation. In support of Xerox's environmental leadership goals, these models may contain some recycled components that are reconditioned. ENERGY STAR^{el} is a U.S. registered trademark. As an ENERGY STAR^{el} Partner, Xerox has determined that these products meet the ENERGY STAR^{el} guidelines for energy efficiency. Product information and/or specifications are subject to change without notice. 8/06 610P720820B F16BR-01UC