HOTPOINT

HDA2000G - Hotpoint Built-In Dishwasher

Dishwasher Dimensions (in inches)



Electrical Rating

Voltage AC120					
Hertz60					
Total connected load amperage8.6					
Calrod® heater watts500					
For use on adequately wired 120-volt, 15-amp					
circuit having 2-wire service with a separate					
ground wire. This appliance must be grounded					
for safe operation.					

Installation Information (in inches)



Note: Dishwasher must not be installed more than 10' from sink for proper drainage. All plumbing and electrical work must be in accordance with local codes. Dishwasher includes drain hose and leveling legs.

Installation Information: Before installing, consult installation instructions packed with product for current dimensional data.

Wood Insert Cut-Out Dimensions (in inches)



				Panel	
Models/Kits	A	В	С	Thickness	
GPF325 Kit	18-7/8″	23-9/16"	3-11/16"	1/4"	
			3-3/4" to 4-1/4"**		
GPF375 Kit	18-15/16"	23-5/8"*	4-1/4"**	3/4"	

*Bottom of panel must be notched 1-1/2" x 1/2" to clear access panel. (See illustration above)

**Adjustment required to match adjcent cabinets fronts due to leveling leg adjustment, 4" nominal.



HOTPOINT

HDA2000G - Hotpoint Built-In Dishwasher



Features and Benefits

- Energy Star Qualified
- 2 Wash Levels
- Standard Upper Rack
- Deluxe Lower Rack
- Deluxe Silverware Basket
- Dial Controls (with Rocker)
- 4 Cycle / 9 Option Selections: Heavy Wash (Dial), Normal Wash (Dial), Water Saver (Dial), Rinse Only (Dial); Heated Dry (Rocker), Hi-Temp Wash and Hot PreWash Option (Dial)
- Rinse Aid Dispenser
- Steel Door
- QuietPower[™] Motor
- Standard Sound Insulation Package
- Model HDA2000GWW White on white
- Model HDA2000GBB Black on black
- Model HDA2000GCC Bisque on bisque
- Model HDA2000GAA Almond on almond