

TURBOCHARGER GASKET KIT (For Turbocharger Kit #1500) Catalog #15003 INSTALLATION INSTRUCTIONS

PLEASE study these instructions carefully before installing your new Edelbrock Turbocharger Gasket Kit. If you have any questions or problems, do not hesitate to contact our Technical Hotline at: 1-800-416-8628, from 7am-5pm, Monday-Friday, Pacific Standard Time or via e-mail at: Edelbrock@Edelbrock.com. Please fill out and mail your warranty card.

| • | Description: | This ga | ısket kit | contains | the stainle | ess |
|---|------------------|------------|-----------|-----------|-------------|-----|
| | steel gaskets | that are | used to | seal the | turbochar | ger |
| | turbine inlet ar | nd outlet. | They car | n also be | used with a | any |
| | Garrett T25 or | T28 Turb | ocharger. | | | |

Kit Contents:

Qty. Description

Gasket, Turbocharger to Exhaust Manifold

☐ 1 Gasket, Turbocharger to Outlet Elbow

Installation Notes

- 1. When attaching the turbocharger to exhaust manifold, tighten the nuts in a criss-cross pattern. This will evenly compress the gasket. Tighten the nuts in a few increments until the gasket is fully compressed.
- 2. Repeat on the exhaust outlet elbow.
- 3. Torque the 8mm x 1.25 nuts to 190 inch/lbs. (approximately 16 ft/lbs).

Edelbrock Corporation, 2700 California St., Torrance, CA 90503 Tech Line: 1-800-416-8628; Office: (310) 781-2222 E-Mail: Edelbrock@Edelbrock.com

© 2004 Edelbrock Corporation Rev. 1/04 - RS/mc Catalog #15003 Brochure #63-0243



TURBOCHARGER GASKET KIT (For Turbocharger Kit #1500) Catalog #15003 INSTALLATION INSTRUCTIONS

PLEASE study these instructions carefully before installing your new Edelbrock Turbocharger Gasket Kit. If you have any questions or problems, do not hesitate to contact our Technical Hotline at: 1-800-416-8628, from 7am-5pm, Monday-Friday, Pacific Standard Time or via e-mail at: Edelbrock@Edelbrock.com. Please fill out and mail your warranty card.

- Description: This gasket kit contains the stainless steel gaskets that are used to seal the turbocharger turbine inlet and outlet. They can also be used with any Garrett T25 or T28 Turbocharger.
- · Kit Contents:

Qty. Description

Gasket, Turbocharger to Exhaust Manifold
Gasket, Turbocharger to Outlet Elbow

Installation Notes

- 1. When attaching the turbocharger to exhaust manifold, tighten the nuts in a criss-cross pattern. This will evenly compress the gasket. Tighten the nuts in a few increments until the gasket is fully compressed.
- 2. Repeat on the exhaust outlet elbow.
- 3. Torque the 8mm x 1.25 nuts to 190 inch/lbs. (approximately 16 ft/lbs).

Edelbrock Corporation, 2700 California St., Torrance, CA 90503 Tech Line: 1-800-416-8628; Office: (310) 781-2222 E-Mail: Edelbrock@Edelbrock.com

© 2004 Edelbrock Corporation Rev. 1/04 - RS/mc