

## COMPETITION SUBS

### FEATURES

- High Excursion Butyl Rubber Surround
- Expanded Polypropylene Cone
- Non-Linear Spider
- Rugged Dual Voice Coils
- Optimized Magnet/Motor Structure
- Rigid Cast Aluminum Frame
- Heavy Duty Rubber Gasket
- Performance Design



### NEW

#### 10" COMPETITION SUBWOOFER

RSdC102 / RSdC104

#### SPECIFICATIONS

Power Handling (RMS/Peak): 600W/1200W  
Impedance (RSdC102): 2/2  $\Omega$   
Impedance (RSdC104): 4/4  $\Omega$   
Frequency Response: 29Hz - 300Hz  
Sensitivity (RSdC102): 93dB @ 2.83V/1M<sup>2</sup>  
Sensitivity (RSdC104): 89dB @ 2.83V/1M<sup>2</sup>  
Mounting Diameter: 8 <sup>15</sup>/<sub>16</sub>"  
Mounting Depth: 5 <sup>3</sup>/<sub>4</sub>"

### NEW

#### 12" COMPETITION SUBWOOFER

RSdC122 / RSdC124

#### SPECIFICATIONS

Power Handling (RMS/Peak): 600W/1200W  
Impedance (RSdC122): 2/2  $\Omega$   
Impedance (RSdC124): 4/4  $\Omega$   
Frequency Response: 27Hz - 250Hz  
Sensitivity (RSdC122): 94dB @ 2.83V/1M<sup>2</sup>  
Sensitivity (RSdC124): 92dB @ 2.83V/1M<sup>2</sup>  
Mounting Diameter: 10 <sup>3</sup>/<sub>4</sub>"  
Mounting Depth: 6 <sup>1</sup>/<sub>4</sub>"

## SUBWOOFERS

### FEATURES

- Available in Dual or Single Coil
- CAE/CAD Performance Design
- Injection Molded Aluminum Plated Polypropylene Cone
- Butyl Rubber Surround
- Flat Linear Roll Spider
- Optimized Magnet/Motor Structure
- Reversible Rubber Mounting Gasket
- Rigid Powder Coated Anti-Resonant Steel Frame
- Grill Sold Separately - RSd G10/G12



#### 10" SUBWOOFER RSd10 / RSd10d

#### SPECIFICATIONS

Power Handling (RMS/Peak): 350W/700W  
Impedance (RSd10): 4  $\Omega$   
Impedance (RSd10d): 4/4  $\Omega$   
Frequency Response: 25Hz - 200Hz  
Sensitivity (RSd10): 88dB @ 2.83V/1M  
Sensitivity (RSd10d): 91dB @ 2.83V/1M<sup>2</sup>  
Mounting Diameter: 9 <sup>1</sup>/<sub>8</sub>"  
Mounting Depth: 5 <sup>3</sup>/<sub>4</sub>"

#### 12" SUBWOOFER RSd12 / RSd12d

#### SPECIFICATIONS

Power Handling (RMS/Peak): 350W/700W  
Impedance (RSd12): 4  $\Omega$   
Impedance (RSd12d): 4/4  $\Omega$   
Frequency Response: 25Hz - 200Hz  
Sensitivity (RSd12): 88dB @ 2.83V/1M  
Sensitivity (RSd12d): 91dB @ 2.83V/1M<sup>2</sup>  
Mounting Diameter: 10 <sup>15</sup>/<sub>16</sub>"  
Mounting Depth: 6 <sup>1</sup>/<sub>4</sub>"