

ADDENDUM

Addendum No.: C633M

Date: January 8, 2003

Manuals Affected: DX9000 Series Manuals – **C662M-A, C684M-D, and C685M-C**

Manual Update: Installation Guidelines

You must adhere to the following guidelines for optimum system performance.

- The DX9000 recorders and storage units require connection to an Uninterruptible Power Supply (UPS) to ensure no corruption of data during a power loss.
- The DX9000 system must be installed in a climate-controlled room. The temperature range should be 41° to 85°F (5° to 29°C).
- All network devices that will transport DX9000 video must be capable of moving multicast traffic.
- Pelco recommends that the DX9000 recorder and storage units be installed in a ventilated rack enclosure. Never secure the recorder or storage units to the rack enclosure using only the front handles.
- Make sure the rack enclosure is properly grounded.
- Pelco recommends that a spare phone line be installed and connected to a primary DX9000 viewstation to allow the Pelco Technical Support Group to dial into the site upon customer request. Pelco personnel will not make changes unless authorized by the customer. This phone line can be password protected to prevent unauthorized access.

Lack of adherence to these guidelines gives Pelco discretion in honoring product warranty.



Pelco World Headquarters • 3500 Pelco Way, Clovis, California 93612-5699 USA • www.pelco.com

USA & Canada: Tel: 800/289-9100 • Fax: 800/289-9150

International: Tel: 1-559/292-1981 • Fax: 1-559/348-1120