

Philips
Subwoofer Cable

25 ft

SWA3725



Turn up your listening experience

Experience a new level of listening while transferring audio signals between your components. Superior construction delivers improved sound performance.

Enjoy better audio quality

- 24 carat gold-plated connectors optimize signal
- High purity copper conductor for reliable signal transfer

Protects against signal loss

- Copper braided reinforced aluminum shielding

Easy installation

- Color coded connectors for instant recognition
- Non-slip ergonomic grip for easy use
- Plug and play for easy use

Enjoy extended durability

- Protective metal shell for extended durability
- Flexible PVC jacket
- Rubber strain relief

PHILIPS

sense and simplicity

Subwoofer Cable
25 ft

Specifications

Packaging

- EAN/UPC/GTIN: 6 09585 12074 7
- Quantity: 1
- Gross Weight: 0.40 kg
- Tare Weight: 0.06 kg
- Net Weight: 0.34 kg
- Length: 27.9 cm
- Width: 17.7 cm
- Height: 5.3 cm

Outer Carton

- Quantity: 6
- Net Weight: 2.02 kg
- Length (cm): 34.7 cm
- Width (cm): 31.7 cm
- Height (cm): 19.0 cm
- Gross weight: 2.45 kg
- Tare weight: 0.43 kg

SWA3725/17

Product highlights

Color-coded connectors

Color coded connections make it easy to install your cable into the correct inputs and outputs

Easy grip

This non-slip grip makes connecting your components easy and ergonomically comfortable.

24 carat gold-plated connector

24 carat gold-plated connectors ensure the best signal quality for your components.

Braided shielding

Copper braided reinforced aluminum shielding protects against signal loss and interference.

Metal shell

The metal shell protects the internal connection of the cable. It ensures durability and the reliability of your connection.

Flexible PVC Jacket

Flexible PVC jacket provided protection to the delicate core of the cable. It also offers extended durability and ease of installation.

High purity copper

This copper conductor provides high accuracy in signal transfer with minimal resistance.

Plug and play

Plug and play offers easy installation of components without time-consuming installations.

Rubber strain relief

Rubber strain relief provides a secure, yet flexible juncture between the cable and the plug.



Issue date 2007-12-01

Version: 1.0

12 NC: 8670 000 24759
UPC: 6 09585 12074 7

© 2007 Koninklijke Philips Electronics N.V.
All Rights reserved.

Specifications are subject to change without notice.
Trademarks are the property of Koninklijke Philips
Electronics N.V. or their respective owners.

www.philips.com