

Explorer® 3250HD™ High-Definition Interactive Set-Top

Description

Scientific-Atlanta's Explorer® 3250HD™ High-Definition Interactive Set-Top merges high-definition video capability and broadband digital video services to deliver a broad range of entertainment, information, and communications services.



The 3250HD decodes all 18 ATSC digital video formats, including the 6 high-definition (HD) digital formats for HDTV. All standard-definition digital formats and all analog video services are decoded as well. This comprehensive level of decoding capability in one set-top box enables cable service providers to quickly scale HDTV video services for both analog and digital consumers.

The 3250HD can output video to the HDTV display in four resolutions: 480i, 480p, 720p, or 1080i. These resolutions, or scan rates, allow consumers to select the scan rate best suited for their HDTV set. Consumers can stretch and zoom the video picture to maximize its viewable area on the HDTV display.

For added connectivity, the 3250HD offers optional loop-through that provides a set of component HDTV inputs, a composite video input, and both analog audio and optical digital audio inputs. A consumer with limited inputs on their HDTV can use the loop-through connectivity feature on the 3250HD to connect additional electronic devices.

(continued on page 2)

Features

- 166 MIPS Processor
- Integrated DAVIC Cable Modem
- 8 MB Flash Memory, or 16 MB available as an option
- 16 MB Applications DRAM, or 32 MB available as an option
- 16 MB Media DRAM
- 4 KB NVM
- Analog Component HDTV Outputs
- Composite Audio/Video Outputs
- S-Video Output
- Digital Audio Outputs (RCA and Optical)
- Front Panel USB Port
- Ability to Process All Analog and Digital Services
- IR Port for VCR Commander™ Service

Explorer 3250HD High-Definition Interactive Set-Top



Description, continued

To meet the demands of existing and future network configurations, the 3250HD offers power, capacity, and compatibility. The integrated internal DAVIC cable modem allows the 3250HD to communicate instantly with the cable headend to promote a broad range of interactive entertainment, information, and communications services. Over 40 MB of application and program memory, along with the 166 MHz RISC microprocessor, manage multiple program tasks and applications with speed and power. The USB port offers fast interconnectivity to consumer peripherals.

Optional Features

- 16 MB Flash Memory
- 32 MB Applications DRAM
- DVI 1.0 Digital HDTV Output
- IEEE 1394 Digital Outputs
- Loop-Through Connections for Component HDTV, Composite Video, and Analog and Digital Audio
- IR Blaster Cable
- IR Extender Cable
- RF Bypass
- Universal AllTouch® Remote Control: AT8400, AT8450, *AT8550, AT2400, or AT2300




3250HD rear panel showing optional loop-through connections



3250HD rear panel showing optional IEEE 1394 digital outputs

Taping an HD broadcast to an analog VCR is seamless with the 3250HD. The set-top simultaneously displays the HD image and downconverts it to SD (standard definition) through the NTSC outputs.

The optional VCR Commander Service integrates the interactive TV program guide with the VCR so that consumers simply point-and-click to setup and record programs.



The 3250HD makes it easy to maximize the screen image for non-HD channels. For a widescreen HDTV set, simply click "stretch" and then "zoom" from the Quick Settings menu on the 3250HD set-top.




To maximize the screen image for a standard 4:3 HDTV set, simply change the scan rate to 480i using the Quick Settings menu on the 3250HD set-top.

Explorer 3250HD High-Definition Interactive Set-Top



Specifications

| Feature | Benefits |
|---|---|
| Analog Component HDTV Outputs | Provides YPbPr outputs for quick and easy connection to most HDTV sets |
| Dual Audio Outputs with Composite Video Output | Allows simultaneous connection to the audio inputs on the HDTV as well as the audio and video inputs on a VCR |
| DAVIC Reverse Path Data Transmitter | Allows IP-based, real-time two-way communication between the 3250HD and the headend |
| | Enables cable service provider to offer two-way services such as Internet browsing, video-on-demand (VOD), subscription VOD (SVOD), e-mail, and real-time chat |
| MPEG-2 MP@HL Digital Video Decompression | Allows decompression and presentation of audio and video |
| | Delivers video resolutions up to 1920 x 1080 |
| Dolby® Digital Audio and MPEG-1 Audio Support | Supports leading digital audio standards |
| PowerKEY® Conditional Access System | Provides digital security using an RSA encryption algorithm that mathematically matches pairs of keys |
| PowerTV® Operating System with HTML Client Engine | Offers stable operating system and open Application Programming Interfaces (APIs) to support native applications and third-party middleware applications |
| | Allows upgrades using a network download |
| Enhanced Graphics Engine | Displays up to 65,000 colors simultaneously |
| | Enables high-resolution 640 x 480 IPG graphics while simultaneously scaling MPEG-2 video |
| Automatic Scaling of MPEG-2 Video for IPG Window |  <p>Scales MPEG-2 video for optimal viewing in the IPG window regardless of whether the subscriber is watching an HD or SD channel on either a widescreen or standard 4:3 TV</p> |
| Powerful 32-bit RISC Processors | Features a 166 MHz (166 MIPS) processor to perform tasks and applications quickly |
| Over 40 MB Memory | 8 MB Flash, or 16 MB available as an option 16 MB Applications DRAM, or 32 MB available as an option 16 MB Media DRAM 4 KB NVM |
| 64 and 256 ITU J.83 Annex B QAM Support | Supports open standards for QAM delivery and demodulation |
| Analog and Digital Service Tuner | Allows both analog and MPEG-2 digital channels to be tuned and displayed |
| DAVIC Compliant Integrated Cable Modem | Provides a high-speed data forward path to the 3250HD |
| Both Internal Security Microprocessor and Smart Card Slot | Provide hardware-assisted conditional access options with capability to upgrade the security, if ever needed |
| Macrovision® Copy Protection Support | Activation allows cable operators to add another layer of copy protection software, called Macrovision, that restricts subscribers from copying protected transmissions such as VOD and SVOD to the analog composite outputs |

(continued on page 4)

Explorer 3250HD High-Definition Interactive Set-Top



Specifications, continued

| Feature | Benefits |
|---|--|
| Universal Serial Bus (USB) Interface | Front panel USB port allows easy interconnection with home consumer devices such as USB keyboards |
| BTSC/SAP Decoder | Provides stereo sound on analog channels through the baseband left and right outputs |
| S/PDIF Digital Audio Interface | Supports interconnection with surround sound receivers using coaxial and optical type connectors |
| Integrated VCR Commander Service | Automates the recording of selected video programs; requires IR Blaster Cable |
| Provision for Name Branding | Allows you to brand the 3250HD with your company name and logo |
| Optional DVI 1.0 Digital HDTV Output with Support for HDCP | Optional DVI 1.0 port with HDCP (High-Bandwidth Digital Content Protection) supports digital connection to an HDTV set supporting the DVI interface |
| | HDCP provides a copy protection interface between the 3250HD and HDTV set |
| Optional Dual IEEE 1394 Digital Outputs with DTCP Copy Protection | Optional dual IEEE 1394 outputs with DTCP (Digital Transmission Content Protection) provide a 400-Mbps digital interconnection to a 1394-equipped HDTV |
| | The 1394 ports provide a copy protection interface between the 3250HD and the connected consumer device |
| Optional Analog Component HDTV Inputs | Provides YPbPr inputs, composite video input, and digital and analog audio loop-through for quick and easy connection to a DVD player |
| Optional RF Bypass | Allows the video signal to internally bypass the 3250HD to an SD input on the HDTV set |
| Optional RGB Adapter | Converts the video from the YPbPr output into an RGB format with horizontal and vertical sync for HDTVs requiring the RGB input signal |

Ordering Information

Contact your Sales Representative for product availability in your area.

| Part Number | Description |
|-------------|---|
| 4000768 | Explorer 3250HD High-Definition Set-Top (8 MB Flash / 16 MB DRAM Memory) with Optional DVI 1.0 Digital HDTV Output |
| 4001332 | Explorer 3250HD High-Definition Set-Top (8 MB Flash / 16 MB DRAM Memory) with Optional DVI 1.0 Digital HDTV and Optional IEEE 1394 Digital Outputs |
| 4004367 | Explorer 3250HD High-Definition Set-Top (16 MB Flash / 32 MB DRAM Memory) with DVI 1.0 Digital HDTV Output |
| 4005726 | Explorer 3250HD High-Definition Set-Top (16 MB Flash / 32 MB DRAM Memory) with DVI 1.0 Digital HDTV and Optional IEEE 1394 Digital Outputs |
| 4006584 | Explorer 3250HD High-Definition Set-Top (16 MB Flash / 32 MB DRAM Memory) with DVI 1.0 Digital HDTV Output and Analog Component Video and Audio Loop-Through Inputs |

(continued on page 5)

Explorer 3250HD High-Definition Interactive Set-Top



Ordering Information, continued

| Description | Product Photo | Part Number |
|---|---------------|------------------------------------|
| Optional IR Blaster Cable (8 ft) | | 735994 |
| Optional IR Extender Cable | | 1001807 (12 ft) 4006725 (25 ft) |
| Optional RF Bypass | | 544345 |
| Optional RGB Adapter, sold in packages of five (cables sold separately) | | 749790 |
| RGB Adapter Cable with RCA-to-RCA Connectors (8 ft) | | 749976 |
| RGB Adapter Cable with RCA-to-VGA Connectors (8 ft) | | 749978 |
| RGB Adapter Cable with RCA-to-BNC Connectors (8 ft) | | 749977 |
| Spare YPbPr and Audio Left/Right Cable Kit (10 ft) | | 1000944 |



AllTouch, Explorer, PowerKEY, PowerTV, Scientific-Atlanta, and the Scientific-Atlanta logo are registered trademarks of Scientific-Atlanta, Inc.
 3250HD and VCR Commander are trademarks of Scientific-Atlanta Inc.
 Dolby is a registered trademark of Dolby Laboratories.
 Macrovision is a registered trademark of Macrovision Corp.
 All other trademarks shown are trademarks of their respective owners.

Specifications and product availability are subject to change without notice.
 © 2004 Scientific-Atlanta, Inc. All rights reserved.

Scientific-Atlanta, Inc.
 1-800-722-2009 or 770-236-6900
www.scientificatlanta.com

Part Number 4005304 Rev B
 August 2004