

SIR-MINI Satellite Radio Magnet Mount Antenna with 21 Foot Cable MINI ROOF MOUNT ANTENNA

TERK

SIRIUS

Specs::

Frequency:	2320 to 2332.5 MHz
Cable Length:	21 feet
Terrestrial Gain:	-4 dBiVp, 1° elevation
Satellite Gain:	+2 dBic, 20° elevation 3 dBic, 25 - 45° elevation 4.5 dBic, 50 - 85° elevation 4.0 dBic, 90° elevation
Gain:	34.5 dB Typical
Operating Temperature:	-40° F to 185° F
SIRIUS approved:	RX0042-0202

Installation instructions printed on the inside of this card::

If the SIR-Mini is being used with an older dual input SIRIUS receiver the SIR-SP, SIRIUS splitter will be required.

TERK

For more information, visit www.terk.com,
For technical support, call 1.800.942.TERK (8375)

For more information about SIRIUS Satellite Radio service,
visit, www.siriusradio.com

Made in China

One year limited warranty

The SIRIUS name and related logos are trademarks of
SIRIUS Satellite Radio Inc.

TERK and TERK Technologies are trademarks of
TERK Technologies Corp. Commack, NY


©2004 TERK Technologies Corp. 138P005



Pre Installation::


- The antenna has a magnetic base and must be installed on a conductive metal surface on the outside of the vehicle.
- Position the antenna in such a way that it will be free of mechanical (i.e. an outward-opening moon roof) and line-of-sight obstructions such as roof racks, luggage boxes, etc. In these instances, consider positioning the antenna offset from the vehicle centerline.
- Recommended installation locations are the roof of the vehicle above the rear window or on the top of the trunk near the rear window. **(as shown in Fig.1)**

Fig.1



Predetermined antenna locations

Fig.2



Push cable under molding

Installation Instructions::

- 1 Make sure the installation location is clean and dry.
- 2 To install the antenna tail, place it against the antenna and route cable into the cable channel. Take the tail adhesive and remove the backing from one side. Place firmly onto the back of the tail over the routed cable. Then, remove the backing from the other side of the adhesive.
- 3 Place the SIR-Mini with tail on your roof or trunk in the predetermined antenna location **(as shown in Fig.1)** and press down firmly to secure antenna tail.
- 4 Route the antenna cable to the SIRIUS receiver. Avoid blocked passages and any obstructions that could kink, crimp, twist, or chafe the cable. If the antenna is located on your vehicle roof then it is necessary to push the cable under the rear window molding. **(as shown in Fig.2)**
- 5 Connect the SIR-Mini into the antenna input on the back of your SIRIUS receiver.
- 6 Please refer to your SIRIUS receiver owner's manual to activate SIRIUS service and complete your SIRIUS system installation.

Limited Warranty

TERK Technologies Corp. (TERK) warrants this product against defects in materials or workmanship for one (1) year from the date of purchase. During this warranty period, this product will be replaced without charge. This warranty does not cover any damage due to acts of nature, commercial use, accident, misuse, abuse or negligence. This warranty is only valid in the USA. Replacement as provided under this warranty is the exclusive remedy of the consumer. TERK shall not be liable for any incidental or consequential damages for breach of any express or implied warranty on this product, except to the extent that limitations of this sort are prohibited by applicable law. THERE ARE NO IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURCHASE EXCEPT TO THE EXTENT THAT IMPLIED WARRANTIES OF EITHER SORT ARE REQUIRED BY APPLICABLE LAW, AND IN SUCH CASE, EACH WARRANTY IS LIMITED IN DURATION TO ONE YEAR.