

FUJIFILM INSTANT CAMERA

INSTAX 200

Specifications

Film	Fujifilm Instant Color Film "instax"
Picture size	99(w) × 62(h)mm
Lens	Collapsible-mount Fujinon lens, 2 components, 2 elements, f=95mm, F=14
Viewfinder	Reverse Galilean style viewfinder
Focusing	Two-range selectable: 0.9 ~ 3m / 3m ~ ∞
Shutter	Programmed electronic shutter, 1/64 ~ 1/200 sec., Electromagnetic release
Exposure control	Automatic (AE) / Coupled meter range: LV10.5 ~ LV15 (ISO 800) Exposure compensation:2/3EV
Film advance	Motorized automatic advance
Film counter	Displays number of remaining exposures
LCD panel	Film counter, Focusing distance range
Flash	Built-in auto flash in low light / Flash range: 0.9 ~ 3m Recycle time: 0.2 ~ 4 sec. (with new batteries) Flash ready indication: LED in viewfinder Fill-in flash by flash-on button
Batteries	4 × AA-size (LR6) alkaline batteries Battery life: Approx. 10 packs of film (under Fujifilm test conditions)
Other features	Auto-retracting lens barrel and auto-closing lens cover when power is turned off Film confirmation window
Size	178.5(w) × 94.5(h) × 117.5(d)mm
Weight	650g (without batteries, strap, and film)

*Specifications are subject to change without notice.