

KE-42TS2

KE-32TS2

Plasma WEGA™ Integrated Plasma Television



NEW FEATURES

- Improved Brightness (Peak)
 - 43% (42")/38% (32")
- Improved Contrast Ratio (1000:1)
- DVI-HDTV Interface





ADDITIONAL FEATURES

Audio/Video Features

- HDTV Monitor
- Built-in NTSC TV Tuner
- Built-in Stereo Speakers
- KE-42TS2 Resolution: 1024(H) x 1024(V) KE-32TS2 Resolution: 852(H) x 1024(V)
- Digital Pixel Generator™ System
- Pixel-by-Pixel I/P Conversion
- Cinemotion™ Reverse 3-2 PullDown Technology
- Visual Size: 42"/32" 16:9
 Plasma Display Panel
- Input Signals: 480i, 480p, 1080i, 720p, Computer RGB
- Dot Phase Adjustment (Computer Input Only)
- Color Temperature Adjustment (5000 - 7500K)
- Auto Wide/Wide Screen Modes

- TruSurround™Sound SRS®
 3D Audio Effect
- Contrast Ratio (1000:1)

Convenience Features


- Wall Mountable (WB PW2)
- Closed Caption (CC)
- Multiple Language (3) On-Screen Display (English, French and Spanish)
- Auto Channel Program
- Caption Vision (CC)
- Channel Skip/Add
- Clock/Timer (Two Event)
- Favorite Channel
- Program Palette[™] Presets
- Sleep Timer
- V Chip Parental Control

KE-42TS2

KE-32TS2

Plasma WEGA™ Integrated Plasma Television

KEY TECHNOLOGY



All-in-One Design This unique flat panel television provides a complete plug and play solution. Once you take it out of the box, you can have the unit up and running in minutes. The unit features a NTSC tuner, stereo speakers and table top pedestal.

Digital Pixel Generator™ System Sony-unique digital signal processing technology that transmits and processes all signals digitally. Maximizes display performance of high-end video sources for natural, rich image reproduction especially high-definition sources.

Pixel by Pixel I/P Conversion This interlace to progressive technology constructs a film or video scene one pixel at a time for fluid, life-like motion along with breathtaking image detail.

CineMotion™ Reverse 3-2 PullDown Technology Minimizes motion artifacts and optimizes film-based content from any video input for the purest reproduction of film originated sources.

TruSurround™ SRS® Audio Processing

Eliminates the need to sit in the "sweet spot." Generates the life-like sound of rear speakers using only the stereo pair built into the television cabinet.

ADDITIONAL FEATURES

Specifications

Inputs and Outputs

- DVI HDTV Interface
- Composite Video Input x 2
- S-Video Input x 2
- RF Input x 1
- HD Component Video Input (Y/P_b/P_r) x 1
- HD Component Video Input (Y/P_b/P_r) with RGB/HV x 1
- Audio Output x 1
- Subwoofer Output x 1
- Control S In x 1
- Control S Out x 1

 Headphone Jack x 1 (Front)

General

- Power Requirements: AC120V, 60Hz
- Power Consumption (Standby):1.7W (32")/2.0W (42")
- Power Consumption (in Operation): 270W (32")/360W (42")

Accessories

Supplied Accessories

- Instruction Manual
- Remote Control
- AA Batteries (2)

Optional Accessories

- A/V Stand: SU-TS1
- Wall Bracket: WB-PW2

Weights & Measures

- Dimensions (W x H x D): KE-42TS2: 41⁵/₈" x 30¹/₈" x 5" (1056 x 764 x 124mm) KE-32TS2: 33³/₄" x 24³/₄" x 5¹/₄" (856 x 627 x 132mm)
- Weight: KE-42TS2: 81.9 lbs. (37.0kgs) KE-32TS2: 56.3 lbs. (25.5kgs)

©2002 Sony Electronics Inc. All rights reserved. Features and specifications are subject to change without notice.