

# H-19D



▶ FEATURES

- Slim and sleek design
- Fast 3ms response time
- High 300 brightness
- Crisp 1000 contrast ratio
- Dual digital and analog inputs
- Built-in speakers
- Easy-to-use friendly OSD
- Auto-adjustment for optimal viewing
- Kensington® security socket
- VESA standard wall mount
- Windows Vista Basic approved
- TCO'03 certified

▶ SPECIFICATION

Panel	<b>Panel Type</b>	TFT LCD	
	<b>Panel Size</b>	19.0" (481mm)	
	<b>Max. Resolution</b>	SXGA 1280 x 1024	
	<b>Pixel Pitch</b>	0.285mm	
	<b>Brightness</b>	300cd/m <sup>2</sup> (Typical)	
	<b>Contrast Ratio</b>	1000:1 (Typical)	
	<b>Surface Treatments</b>	Hard Coating (3H), Anti-glare Treatment	
	<b>Viewing Angle (H/V)</b>	170°/160° (Typical)	
	<b>Display Color</b>	16.7M	
	<b>Response Time</b>	3ms (GTG)	
	<b>Frequency (H/V)</b>	H: 24kHz – 80kHz V: 55Hz – 75Hz	
	<b>Max. Pixel Clock</b>	140MHz	
	<b>Life Time</b>	40,000hrs (Minimum)	
	Input	<b>Analog</b>	15-Pin D-Sub
<b>Digital</b>		24-Pin DVI-D	
Audio	<b>Audio In</b>	3.5mm Audio Line-in	
	<b>Speaker</b>	1W x 2	
Connector	<b>Power</b>	3-Pin AC Plug	
Tilt	<b>Tilt</b>	-5° ~ +20°	
Mounting	<b>VESA FPMPI</b>	Yes (100mm)	
Regulation Approval	<b>Certifications &amp; Compliance</b>	UL/CUL, FCC, NOM, CB, CE, TUV/GS, GOST-R/HYGIENIC, Nordic, BSMI, EPA, TCO'03, WEEE, RoHS	
		<b>VESA</b>	DDC-2B, DDC-CI
		<b>Power AC Consumption</b>	100 – 240V, 50 – 60Hz <42W (On) <2W (Stand-by) <1W (Off)
Dimensions	<b>Net (W x H x D)</b>	408 x 407 x 211 mm (16.3" x 16.3" x 8.4")	
	<b>Packing (W x H x D)</b>	470 x 480 x 148 mm (18.8" x 19.2" x 5.9")	
Weight	<b>Net Weight</b>	4.1 kg (9.1 lbs)	
	<b>Gross Weight</b>	5.3 kg (11.7 lbs)	
Packing	<b>1 Pallet</b>	76 Sets	
	<b>20' Container</b>	760 Sets	
	<b>40' Container</b>	1520 Sets	

All specifications are subject to change without prior notice

