

LCD Widescreen HDTV with HD-PPV Capability

NATIVE DISPLAY RESOLUTION 1366 x 768

MPEG-2

DYNAMIC POWER SAVINGS

HD VOD PPV DECRYPTION Integrated Pro:Idiom™

BUILT-IN TUNERS ATSC/NTSC/QAM Clear

DYNAMIC CONTRAST RATIO 10,000:1

> HIGH BRIGHTNESS 500 cd/m^2

LG'S EXCLUSIVE XD ENGINE®

REAL CINEMA

CLEAR VOICE

CONNECTIONS High-Res Component, HDMITM, RGB, S-Video, AV Inputs

MULTIPLE PROTOCOL INTERFACE (MPITM) SLOT

USB CLONING

ENERGY STAR® COMPLIANT

INVISIBLE SPEAKERS

2-YEAR LIMITED WARRANTY (parts/labor)





ULTRA CONTRAST

AT A BLAZINGLY FAST 370 MILLION PIXELS PER SECOND, THE PROCESSOR USES A HISTOGRAM ANALYZATION TOOL TO CLARIFY THE IMAGE DATA ACCORDING TO SIGNAL BRIGHTNESS LEVELS.










Dramatization

DYNAMIC BLACK STRETCH

THE MINIMUM BLACK LEVEL OF AN IMAGE IS AUTOMATICALLY DETECTED AND ADJUSTED ACCORDING TO BRIGHTNESS.



Dramatization

SPECIAL FEATURES

Pro:Idiem

DIGITAL RIGHTS MANAGEMENT SYSTEM

The Pro:Idiom system's high-quality security unlocks access to premium content availability to help assure rapid, broad deployment of HDTV and other high value digital content. Pro:Idiom™ has been designed specifically for industries that use premium HDTV content from cable, satellite or video on demand (VOD) services and as such, could result in lower costs, and reduced maintenance. This system is one of the leading DRM systems embraced by content providers for both of these key programming sources. By using this embedded approach, security is provided and helps eliminate the possibility of customers tampering with or removing needed components.



VIEWING QUALITY AS THE DIRECTOR INTENDED

24p playback matches the original frame rate of film based content, making your home-cinema experience one step closer to a "Real Cinema" experience as the director intended

Original Film

Original film has a frame rate of 24 frames per second. To be viewed on standard video equipment such as TVs it must be have a pull down solution.



NTCS Pulldown Solution

NTSC corrects the frame rate difference by repeating every 4th frame. Sound must be separated from the film to avoid any distortion.



Real Cinema

Real Cinema uses a 2:3 pull down which takes ever other frame and splits it into three fields of video for a smoother transition from film to video.



Dramatization



BALANCED SOUND TO EMPHASIZE DIALOGUE

Designed to automatically enhance and amplify the sounds of the human voice frequency range, Clear Voice Technology helps keep dialogue audible when background poises swell





Dramatization

invisible

SOUND IS HEARD, NOT SEEN


Breaking through the fixed idea that speaker grills must be exposed, the Invisible Speaker design provides a "fuller sweet spot". Personally tuned by Mr. Mark Levinson, world-renowned audio authority, this unique design has rich and lively sound that can be enjoyed from any angle.






CLEAR SCREEN

USING THE NOISE FILTER INSIDE THE XD ENGINE®
CHIP, THE IMAGE IS ANALYZED FOR TEMPORAL AND
SPATIAL INFORMATION TO REDUCE MPEG NOISE.




ADVANCED VIVID COLOR

COLORS THAT ARE SENSITIVE TO THE HUMAN EYE ARE OPTIMIZED TO THE NEAREST TRUE COLOR BY THE SELECTIVE COLOR CONTROL.



INTELLIGENT EDGE CONTROL

EDGE LINES ARE EMPHASIZED BY IMPROVING THE TRANSITION FROM THE BACKGROUND TO THE MAIN OBJECT.



Dramatization

DIMENSIONS


CLONING PROGRAMER REMOTE


LT2002 (optional)
QUICKSET II CLONE®

The LT2002 allows for custom setup and programming information to be quickly copied from a "master" LG or Zenith brand LCD, Plasma, or CRT TV (with the MPI input)into an unlimited number of identical models. This saves the installers hours of time duplicating the hoteITVsettings, such asminimum volume, maximum volume, start up channel, channel mapping, etc.



32LG3DC





REAR JACK PANEL



USB IN UPDATE © RESET SERVICE ONLY SERVICE ONLY R-AUDIO-L(MONO) VIDEO RGB IN (PC) RGB IN (PC)

SIDE JACK PACK PANEL



PANEL	
LCD Panel Type	32"
Display Area	31.5" diagonal
Aspect Ratio	16:9
MAIN SYSTEM	
MPEG Decoder	MPEG2/AC-3
Max Output Resolution	UXGA/WSXGA+
TUNING SYSTEM	
Number of Tuners	1 (ATSC/NTSC)
NTSC	Yes (Air Ch2~Ch69, CATV 01Ch~135Ch)
QAM Clear	Yes
MODULE	
Colors (RGB)	8 Bit
Brigntness	500 cd/m ²
Dynamic Contrast Ratio	10,000:1
View Angle (H/V)	176°/176°(min.)
VIDEO	, , ,
Display Format	1366×768
All Format Converter	Yes (1080P/1080i/720p/480p/480i » 768p)
Comb Filter	Yes (3D Digital)
Color Temperature Control	Yes (Cool / Normal / Warm, User)
DLTI / DCTI	Yes
Black Stretcher	Yes
Enhanced Line Doubler	Yes
Improved Contrast	Yes
Improved Color	Yes
Enhanced Noise Reduction	Yes
Selectable Gamma	Yes
	Yes
Real Cinema 3:2/2:2 Mode	
Aspect Ratio Control	6 Modes
Picture Control	Con/Bri/Tint/Color/Sharpness
XD Engine EZ Picture	Yes 7.44 Maril Grant Maril
EZ FICTURE	7 Modes (Vivid/Standard/Cinema/
AUDIO	Sports/Game/Expert1/Expert2)
AUDIO	2)4/ 4.5
Speaker System	2 Way 4 Speakers
Dolby Digital Decoder	Yes
Mono/Stereo/Dual (MTS/SAP)	Yes
Surround System	SRS TruSurround XT
Total Audio Watts (RMS)	2 × 10 W
Bass/Treble/Balance	Yes
Clear Voice	Yes
EZ SoundRite (AVL)	Yes
EZ Sound	5 Modes (Standard, Music, Cinema, Sports, Game)
JACKS	
RF In	1 (NTSC+ATSC tuner)
A/V In	1 (Rear), 1 (Side)
S-Video In	1 (Rear)
Component & R/L Audio In	1 (Rear)
RGB In (DB15-RGB)	1 (Rear)
Audio In (Phone Jack)	1 (Rear: PC)
HDMI	1 (Rear)
Speaker Out	Yes (8ohm mono 1W Phone Jack)
Headphone Out	Yes (Side)
RS-232C	1 (Rear) (Service Only)
IR Out	1 (out to MPI Slot)
USB Cloning	Yes
RJ-45	No
MPI Slot	1 Slot (Standard Type)

SPECIAL FEATURES	
Integrated Pro:Idiom	Yes
Trilingual Menus	Yes (English, French, Spanish)
Commercial Installation Menu	Yes (English Only)
Discrete IR	Yes
Auto/Manual Clock	Yes
On/Off Timer	Yes
Sleep Timer	Yes
Screen Adjust	Yes
Input Labeling	Yes
EZ Scan (Auto Programming)	Yes
Channel Add/Delete	Yes
Child Lock	Yes
Channel Labels	Yes
Favorite Channel	Yes
Closed Caption/Subtitle	Analog/Digital
Mute	Yes
RJP Plug&Play Support	No
Flashback (Quick View)	Yes
Parental Control with V-Chip	Yes
EZ Menus	Yes
REQUIRED APPROVALS	
UL, C-UL, NOM	Yes
POWER	
Power Source	110V (220V) 50/60Hz
Power (typ.)	
w/o Dynamic Power Savings	190W
Dynamic Power Savings	Yes
Stand-by Consumption	Under 1W
Energy Star Compliant	Yes
ADDITIONAL INFORMATION	
Dimensions w/stand (W×H×D)	31.57" x 23.78" x 9.13"
Weight w/stand	29.5 lbs.
Dimensions w/o stand (W×H×D)	31.57" x 21.43" x 4.29"
Weight w/o stand	26.2 lbs.
Packaging Dimensions (W×H×D)	38.39" x 26.18" x 7.60"
Shipping Weight	35.1 lbs.
Detachable Stand	±90° swivel
VESA™ Standard Mount Interface	200mm x 100mm, M4 screw
Power Button	Red (Stand-by); Blue (On)
Invisible Speakers	Yes
Cable Management Clip	Yes
UPC	7 19192 17387 3

www.LGcommercial.com



LG Electronics U.S.A., Inc. Commercial Products Division 2000 Millbrook Drive, Lincolnshire, IL 60069

Contact your LG Regional Sales Representative: Hospitality: 800.228.1236 B2B: 800.897.8788

Channel Markets: 800.897.8871

Customer Service: 888.865.3026

All screen images are simulated. Dimensions and weights are approximate. Design, features and specifications subject to change without notice.

C L E A R VOICE

MADICATION TRAVELOR ENGINE DIGITAL INSPEAKER.II

Pro:Idiom TruSurround

© Copyright 2008 LG Electronics USA, Inc. All Rights Reserved. "LG Life's Good" is a registered trademark of LG Corp. XD Engine is a registered trademark of LG Electronics USA, Inc.

VESA is a trademark of Video Electronics Standards Association. Energy Star is a U.S. registered trademark. All other product and brand names are trademarks or registered trademarks of their respective companies.

32LG3DC_LGE040803_PR Printed in the USA. June 2008