User's Guide

M198WA M208WA M228WA

Make sure to read the **Safety Precautions** before using the product. Keep the User's Guide(CD) in an accessible place for furture reference.

See the label attached on the product and give the information to your dealer when you ask for service.



Safety Precautions

Please read these safety precautions carefully before using the product.

/ Warning

If you ignore the warning message, you may be seriously injured or there is a possibility of accident or death.

∕ Cautio

Caution If you ignore the caution message, you may be slightly injured or the product may be damaged



Precautions in installing the Product

∕ Warning

- Keep away from heat sources like electrical heaters.
 - Electrical shock, fire, malfunction or deformation may occur.
- Keep the packing anti-moisture material or vinyl packing out of the reach of children.
 - Anti-moisture material is harmful if swallowed. If swallowed by mistake, force the patient to vomit and visit the nearest hospital. Additionally, vinyl packing can cause suffocation. Keep it out of the reach of children.
- Do not put heavy objects on the product or sit upon it.
 - If the product collapses or is dropped, you may be injured. Children must pay particular attention.
- Do not leave the power or signal cable unattended on the pathway.
 - The passerby can falter, which can cause electrical shock, fire, product breakdown or injury.
- Install the product in a neat and dry place.
 - Dust or moisture can cause electrical shock, fire or product damage.
- If you can smell smoke or other odors or hear a strange sound unplug the power cord and contact the service center.
 - If you continue to use without taking proper measures, electrical shock or fire can occur.
- If you dropped the product or the case is broken, turn off the product and unplug the power cord.
 - If you continue to use without taking proper measures, electrical shock or fire can occur. Contact the service center.
- Do not drop an object on or apply impact to the product. Do not throw any toys or objects on the product screen.
 - It can cause injury to human, problem to product and damage the display.
- Do not let the product fall or drop when connecting it with an external device.
 - This may cause injury and/or damage to the product.
- When connecting it with a game device, keep a distance of four times as long as the diagonal measurement of the screen from the device.
 - If the product falls because of the short cable, this may cause injury and/or damage to the product.
- Leaving a fixed image on the screen for a long time may cause damage to the screen and cause image burn-in. Make sure to use a screen saver on the product.

 Burn-in and related problems are not covered by the warranty on this product.

Caution

- Make sure the product ventilation hole is not blocked. Install the product in a suitably wide place (more than 10cm from the wall)
 - If you install the product too close to the wall, it may be deformed or fire can break out due to internal heat.
- Do not block the ventilation hole of the product by a tablecloth or curtain.
 - The product can be deformed or fire can break out due to overheating inside the product.
- Install the product on a flat and stable place that has no risk of dropping the product.
 - If the product is dropped, you may be injured or the product may be broken.
- Install the product where no EMI occurs.
- Keep the product away from direct sunlight.
 - The product can be damaged.

Safety Precautions



Electrical Power Related Precautions

/N Warning

- Make sure to connect the power cable to the grounded current.
 - You may be electrocuted or injured.
- Use the rated voltage only.
 - The product can be damaged, or you may be electrocuted.
- During a thunder or lightning storm, unplug the power cable or signal cable.
 - You may be electrocuted or a fire can break out.
- Do not connect several extension cords, electrical appliances or electrical heaters to a single outlet. Use a power bar with a grounding terminal designed for exclusive use with the computer.
 - A fire can break out due to overheating.
- Do not touch the power plug with wet hands. Additionally, if the cord pin is wet or covered with dust, dry the power plug completely or wipe dust off.
 - You may be electrocuted due to excess moisture.
- If you don't intend to use the product for a long time, unplug the power cable from the product.
 - Covering dust can cause a fire, or insulation deterioration can cause electric leakage, electric shock or fire.
- Fix the power cable completely.
 - If the power cable is not fixed completely, a fire can break out.
- Hold the plug when pulling out the power cable. Do not bend the power cord with excessive force or put heavy objects on the power cord.
 - The power line can be damaged, which may cause electric shock or fire.
- Do not insert a conductor (like a metal chopstick) into one end of the power cable while the other end is connected to the input terminal on the wall. Additionally, do not touch the power cable right after plugging into the wall input terminal.
 - You may be electrocuted.
- The power supply cord is used as the main disconnection device. Ensure that the socket-outlet is easily accessible after installation.



- Do not unplug the power cord while the product is in use.
 - Electrical shock can damage the product.



Precautions in Moving the Product



- Make sure to turn off the product.
 - You may be electrocuted or the product can be damaged.
- Make sure to remove all cables before moving the product.
 - You may be electrocuted or the product can be damaged.

Safety Precautions

⚠ Caution

- Do not shock the product when moving it.
 - You may be electrocuted or the product can be damaged.
- Do not dispose the product-packing box. Use it when you move.
- Make the panel face forward and hold it with both hands to move.
 - If you drop the product, the damaged product can cause electric shock or fire. Contact with the service center for repair.

Precautions in Using the Product

Marning

- Do not disassemble, repair or modify the product at your own discretion.
 - Fire or electric shock accident can occur.
 - Contact the service center for check, calibration or repair.
- When cleaning the brown tube surface, unplug the power cord and scrub with soft cloth to prevent scratching. Do not clean with a wet cloth.
- Keep the product away from water.
 - Fire or electric shock accident can occur.

⚠ Caution

- Do not put or store inflammable substances near the product.
 - There is a danger of explosion or fire due to careless handling of the inflammable substances.
- When cleaning the brown tube surface, unplug the power cord and scrub with soft cloth to prevent scratching. Do not clean with a wet cloth.
 - The water can sink into the product, which can cause electric shock or serious malfunction.
- Take a rest from time to time to protect your vision.
- Keep the product clean at all times.
- Take a comfortable and natural position when working with a product to relax the muscles.
- Take a regular break when working with a product for a long time.
- Do not press strongly upon the panel with a hand or sharp object such as nail, pencil or pen, or make a scratch on it.
- Keep the proper distance from the product.
 - Your vision may be impaired if you look at the product too closely.
- Set the appropriate resolution and clock by referring to the User's Guide.
 - Your vision can be impaired.
- Use authorized detergent only when cleaning the product. (Do not use benzene, thinner or alcohol.)
 - Product can be deformed.


On Disposal

- The fluorescent lamp used in this product contains a small amount of mercury.
- Do not dispose of this product with general household waste.
 Disposal of this product must be carried out in accordance to the regulations of your local authority.

Before Connecting to the PC

Connecting the stand

- Before setting up the product, ensure that the power supply, the computer system, and other attached devices is turned off.
- 1. Place the monitor with its front facing downward on a soft cloth.
- 2. Connect the Stand Base to the Stand Body and press latches at the button toward each end.
- 3. Connect the Stand, assembled in step 2, to the Monitor Panel until you hear a "Click".
- 4. Once assembled take the monitor up carefully and face the front side



Important


- Once you connect the stand base, try not to disconnect it.
- Do not carry the product upside down holding only the stand base. The product may fall and get damaged or injure your foot.

Before Connecting to the PC

 Before setting up the product, ensure that the power supply, the computer system, and other attached devices is turned off.

Positioning your display

1. Adjust the position of the panel in various ways for maximum comfort.







Warning:

When adjusting the angle of the screen, do not put your finger(s) in between the head of the monitor and the stand body. You can hurt your finger(s).

Theft prevention locking device




Name of the Remote Control Buttons (A Type)





- 1. 2. 3.
 - 1. Take out the battery cap.
 - 2. Insert the batteries with correct polarity (+/-).
 - 3. Close the battery cap.
 - Dispose of used batteries in the recycle bin to prevent environmental pollution.

Name of the Remote Control Buttons



MUTE

Switches the sound on or off.

PSM (Picture Status Memory) Button

Press repeatedly to select ${\bf Dynamic},\,{\bf Standard},\,{\bf Mild},\,{\bf Game}$ or ${\bf User}$ picture mode.

SSM (Sound Status Memory) Button

Use this button to select the sound tone.

Press repeatedly to select Flat, Music, Movie, Sports, User sound tone.



To select the teletext on or off. The main index page or the last selected page appears on the screen together with an information headline and an option line at the bottom of the screen.

PR (▲ ▼) Buttons

Able to change channel.

VOL (◀ ▶) Buttons

Able to adjust sound.

OK Button

Use when functional adjustment is completed.

MENU

Use this button to enter the On Screen Display menu.

SLEEP: SLEEP Timer


You can set a time period after which the

TV / AV / RGB / Component / DVI should switch itself to standby. Press the key repeatedly to select the number of minutes.

$$(off) \longrightarrow 10 \longrightarrow 20 \longrightarrow 30 \longrightarrow 60$$

$$240 \longleftarrow 180 \longleftarrow 120 \longleftarrow 90$$

Name of the Remote Control Buttons



ARC

To select the image size of the screen.

- When TV / AV mode: Spectacle, Original, 4:3, 16:9, 14:9, Zoom1, Zoom2
- When RGB/DVI /Componentmode: 4:3, 16:9

I/II: Bilingual choice and sound mode selection

[TV]

- To switch from **Stereo** to **Mono** sound in case of stereo transmission, or from **Nicam Stereo** to **Nicam Mono**, in case of digital transmission.
- to switch from Nicam Dual I to Nicam Dual II or Nicam Dual II or Nicam Dual II+II in case of Nicam Dual transmission.
- to choose between **Dual I**, **Dual II** or **Dual I**+**II** in case of bilingual transmission:

Dual I sends the primary broadcast language to the loudspeakers:

Dual II sends the secondary broadcast language to the loudspeakers;


Dual I+II sends a separate language to each loudspeakers. **[AV / Component]**

In AV/Component mode, you can select output sound for the left and right loudspeakers. Repeatedly press the **I/II** button to select the sound output.

- L+R: Audio signal from audio L input is sent to left loud-speaker and audio signal from audio R input is sent to right loud-speaker.
- L+L : Audio signal from audio L input is sent to left and right loud-speakers.
- R+R: Audio signal from audio R input is sent to left and right loud-speakers.

Remote Control - Using the Teletext function

Please select your local teletext language. (page 30) If you don't, the teletext may not appear correctly on the screen.



Yellow key

Favourite Program On: Rotate favourite channel
Favourite Program Off: To display the previously
selected TV channel.

E HOLD

Press the button to stop the automatically rotating of the sub pages. Press the button again to continue the automatic rotating again.

∃**♦** SIZE

Press the button repeatedly to display the upper part, the lower part and then to return to the normal page size.


₹] MIX

Display the teletext pages superimposed on the TV picture. To switch the TV picture off press this button again.

∃⊕ TIME

Press this button to select a sub page number. The sub page number is displayed at the bottom of the screen. To hold or change the sub page, press the RED/GREEN, ▲ ▼ or NUMBER buttons. Press again to exit this function.

Remote Control - Using the Teletext function



₹ REVEAL

Press the button to reveal/conceal the hidden information, such as solutions to riddles and puzzles. Press this button again to remove the information from the display.

i INDEX

To display the main index.


∃M MODE

The mode will be switched in the Teletext mode.


EXUPDATE

Press the button to appear the TV programme. At the top of screen indicates that you are still in the teletext mode. Before interrupting teletext, you may select a page number. When the page has been found, the information line appears briefly on your screen. Press the button again to reappear teletext.

Name of the Remote Control Buttons(B Type)



Name of the Remote Control Buttons



I/II: Bilingual choice and sound mode selection

[TV]

- To switch from Stereo to Mono sound in case of stereo transmission, or from Nicam Stereo to Nicam Mono. in case of digital transmission.
- to switch from Nicam Dual I to Nicam Dual II or Nicam Dual I+II in case of Nicam Dual transmission.
- to choose between **Dual I**, **Dual II** or **Dual I**+**II** in case of bilingual transmission:

Dual I sends the primary broadcast language to the loudspeakers; **Dual II** sends the secondary broadcast language to the loudspeakers; **Dual I+II** sends a separate language to each loudspeakers.


[AV / Component]

In AV/Component mode, you can select output sound for the left and right loudspeakers. Repeatedly press the **I/II** button to select the sound output.

- L+R: Audio signal from audio L input is sent to left loud-speaker and audio signal from audio R input is sent to right loud-speaker.
- L+L : Audio signal from audio L input is sent to left and right loud-speakers.
 - R+R: Audio signal from audio R input is sent to left and right loud-speakers.

LIST: Programme list

To display the programme list (0~99).




Note: TV channels displayed in blue have been setup to be skipped in the Programme Edit menu.

Q.VIEW: QUICK VIEW Button

To display the previously selected TV channel

Name of the Remote Control Buttons



PR (▲ ▼) Buttons

Able to change channel.

VOL (◀ ▶) Buttons

Able to adjust sound.

OK Button

Use when functional adjustment is completed.

MENU

Use this button to enter the On Screen Display menu.

SLEEP: SLEEP Timer

You can set a time period after which the

TV / AV / RGB / Component / DVI should switch itself to standby. Press the key repeatedly to select the number of minutes.



ARC

To select the image size of the screen.


- When TV / AV mode: Spectacle, Original, 4:3, 16:9, 14:9, Zoom1, Zoom2
- When RGB/DVI /Componentmode: 4:3, 16:9

TEXT

To select the teletext on or off. The main index page or the last selected page appears on the screen together with an information headline and an option line at the bottom of the screen.

Remote Control - Using the Teletext function

Please select your local teletext language. (page 30) If you don't, the teletext may not appear correctly on the screen.



Yellow key

Favourite Program On : Rotate favourite channel Favourite Program Off : To display the previously selected TV channel.

E HOLD

Press the button to stop the automatically rotating of the sub pages. Press the button again to continue the automatic rotating again.

= ♦ SIZE

Press the button repeatedly to display the upper part, the lower part and then to return to the normal page size.


₹ MIX

Display the teletext pages superimposed on the TV picture. To switch the TV picture off press this button again.

∃⊕ TIME

Press this button to select a sub page number. The sub page number is displayed at the bottom of the screen. To hold or change the sub page, press the RED/GREEN, ▲ ▼ or NUMBER buttons. Press again to exit this function.

Remote Control - Using the Teletext function



₹ REVEAL

Press the button to reveal/conceal the hidden information, such as solutions to riddles and puzzles. Press this button again to remove the information from the display.

∃ i INDEX

To display the main index.


(≡M) MODE


The mode will be switched in the Teletext mode.

∃X UPDATE

Press the button to appear the TV programme. At the top of screen indicates that you are still in the teletext mode. Before interrupting teletext, you may select a page number. When the page has been found, the information line appears briefly on your screen. Press the button again to reappear teletext.


Rear View





- Power Connector : Connect the power cord.
- SCART Input/Output Terminal
- AV Input Terminal
- 4 DVI Digital Signal Connector
- **5** D-Sub Analog Signal Connector
- RGB, DVI Sound Jack: Connect to the jack in the PC sound card or D-TV sound Output Jack.
- TV Tuner Jack : Connect the antenna.
- Headphone/Earphone Connection Terminal
- Component Input Terminal

AV Input Terminal



- **1** Video Input Terminal
- Audio Input Terminal
- **S-Video Input Terminal**


Connecting to your PC

First of all, see if the computer, product and the peripherals are turned off. Then, connect the signal input cable.

Rear side of the product.



(A) Connecting with the D-Sub signal input cable.




(B) Connecting with the DVI signal input cable.



Rear side of the product.

2. Connect the audio cable.




Rear side of the product.


- Make sure to check the sound card connection terminal in the PC before connecting to the product.
 If the PC sound card supports both Speaker Out and Line Out, change it to Line Out by setting the jumper or the PC application. (For more details, refer to the sound card user's guide.)
 - Speaker Out: The terminal connected to the speaker that is not equipped with an amplifier.
 - *Line Out: The terminal connected to the speaker equipped with an amplifier.
 If Audio Out in the PC sound card has only Speaker Out, reduce the PC volume. This product is integrated with an amplifier.

3 Connect the power cord.

Rear side of the product.



1 Turn on power by pressing the power button on the product.



Power button

- 2 Turn on the PC.
- Select an input signal.

 Press the INPUT button on the remote control to select the input signal.

Or, press the INPUT button at the top side of the product.

A • Select RGB







Each time you press the Input button it will change to TV → AV1 → AV2 → Component → RGB → DVI

If nothing is inputted for several seconds the screen will automatically move to the selected menu.




• Directly connect to a grounded power outlet on the wall or a power bar with a ground wire.

■■■ Connecting to VCR/DVD


- Connect the video/audio cable as shown in the figure below and then connect the power cord (See page 19).
 - (A) When using the RCA cable.
 - · Connect the input terminal with a proper colour match.

Rear side of the Product



- (B) When using the S-Video cable.
 - Connect to the S-Video input terminal to watch high image quality movies.


Rear side of the Product





Note • In case the RCA cable is connected simultaneously as S-Video cable is connected, S-Video cable is first.

(C) When using the SCART cable.



Select an input signal.

Press the INPUT button on the remote control to select the input signal.

Or, press the INPUT button at the top side of the product.

- (A) When connecting with a RCA cable.
 - Select AV2
- **B** When connecting with a S-Video cable.
 - Select AV2




- C When connecting with a SCART cable.
 - Select AV1



Each time you press the Input button it will change to TV → AV1 → AV2 → Component → RGB → DVI

- Connecting to Set-top Box /DVD (480p/576p/720p/1080i/480i/576i)
- Connect the video/audio cable as shown in the figure below and then connect the power cord (See page 19).
 - Connect the input terminal with a proper colour match.

Rear side of the Product



Set-top Box /DVD

2 Select an input signal.

Press the INPUT button on the remote control to select the input signal.

Or, press the INPUT button at the top side of the product.


Select Component



Each time you press the Input button it will change to TV \longrightarrow AV1 \longrightarrow AV2 \longrightarrow Component \longrightarrow RGB \longrightarrow DVI

■■■ When watching RGB/DVI from the DVD/Set-top Box

Connect the D-sub cable, RCA/PC cable as shown in the below figure and then connect the power cord. (see page 19)



[Rear side of the Product]

| DVI IN | RESIPCIOTY | IN | RESIDE | RCA-Stereo cable (not included)

| DVI cable | RCA-Stereo cable (not included)

2 Select an input signal.

Press the INPUT button on the remote control to select the input signal.

Or, press the INPUT button at the top side of the product.










Each time you press the Input button it will change to TV → AV1 → AV2 → Component → RGB → DVI

When Watching TV

Check if the antenna cable is connected at the rear side of the product and then, connect the power cord.

Rear Side of the Product



Select an input signal.

Press the INPUT button on the remote control to select the input signal.

Or, press the INPUT button at the top side of the product.


Select TV




Each time you press the Input button it will change to TV → AV1 → AV2 → Component → RGB → DVI

To arrange cables using cable management


Arrange the cables in the center as shown in the following picture.



2 Fit the cable management to the Holder Groove downwards.



* When you want remove it.




Push down slightly.

Push up slightly to remove it.

Warning

- Do not use the cable management as a handle for the Monitor.
- Do not press the cable management.

Name of the Buttons in the Screen Adjustment Unit



- Power Indicator

 This Indicator lights up blue when the display operates normally (On Mode). If the display is in Sleep (Energy Saving) Mode, this indicator colour changes to amber.
- Power Button Use this button to turn the product on and off.
- Use this button to show/hide the OSD (On Screen Display) menu screen.
- OSD Select/Adjust Button) Use this button to select an icon or adjust the setting in the OSD screen.
 - \blacktriangledown \blacktriangle $\:$ Use this button to control the channel for the TV signal.
 - Adjust the volume.

 Volume

 30

Name of the Buttons in the Screen Adjustment Unit



OK Button

OK button is usually used in choosing the MENU.
 When there is no MENU on the screen pushing the OK button will give the information about the current input source.



INPUT Button

TV Television
AV1 SCART
AV2 CVBS, S-Video
Component HDTV, DVD
RGB D-Sub analog signal
DVI Digital signal



Each time you press the Input button it will change to TV → AV1 → AV2 → Component → RGB → DVI

If nothing is inputted for several seconds the screen will automatically move to the selected menu.



IR Receiver

• The unit that receives the signal from the remote control.


OSD (On Screen Display) Menu


Icon	Function Description
Station	Set/Select the channel when using the TV
Picture	Adjusting the picture function.
Sound	Adjusting the sound function.
Time	Adjusting the time function.
Special	Selecting the special function.
Screen	Adjusting the screen function.

Note OSD(On Screen Display)

The OSD function enables you to adjust the screen status conveniently since it provides graphical presentation.

OSD (On Screen Display) Screen Tracking Order





- Press the **MENU** Button, then the main menu of the OSD will appear.
- 2 To access a control, use the ▼ ▲ Buttons.
- When the icon you want becomes highlighted, press the **OK** Button.
- 4 Use the ▼ ▲ ◆ ▶ Buttons to adjust the item to the desired level.
- 5 Accept the changes by pressing the **OK** Button.
- 6 Exit the OSD by pressing the **MENU** Button repeatedly.

On-Screen Menu Language / Country Selection

Installation guide menu appears on product screen when it is turned on for the first time.



- 1. Press the ▼ ▲ ◀ ▶ button and then, **OK** button to select your desired language.
- 2. Press the ▼▲ ◀ ▶ button and then, **OK** button to select your country.
- * If you want to change Language/ Country selection
- 1. Press the **MENU** button and then ▼ ▲ button to select the **Special** menu.
- 2. Press the ▶ button and then ▼ ▲ button to select Language.

 The menus can be shown on the screen in the selected language.

 Or, Press the ▶ button and then ▼ ▲ button to select Country.
- 3. Press the ▶ button and then ▼ ▲ ▼ ▶ button to select your desired language or country.
- 4. Press the **OK** button.
- 5. Press the **MENU** button repeatedly to return to normal TV viewing.

Note

- If you don't finish set up Installation Guide by pressing MENU button or time out of OSD (On Screen Display) display, it will continuously appear until completing set up whenever the set is turned on.
- If you select wrong local country, the teletext may not appear correctly on the screen and some problem may happen during teletext operation.
- Hebrew is added to Country of Installation Guide according to the countries which using Hebrew languages.



STATION ID set/Select the channel when using the TV

Auto programme



System

It should be set before run auto searching.

Press the ▼ ▲ buttons to select the TV system of the country or part of the world from where you want to receive the TV channels.

* Supporting channel: C(V/UHF 02~69) S(Cable 01~41)

BG: PAL B/G, SECAM B/G (Europe/East Europe)

I: PAL I/II (U.K/Ireland)

DK: PAL D/K, SECAM D/K (East Europe)

L: SECAM L/L' (France)

Storage from


To select a programme number or enter the programe number with the number buttons from where you want to start searching for new channels. If e.g. you want to keep the channels 1 to 10 stored earlier, enter programe number 11. Your TV search for new channels from number 11 onwards.

* Numbers available to store: 0~99

Search

Press **OK** or ▶ button to start automatic programming. All available TV channels will be searched and stored automatically. To stop auto programming, press the **MENU** button. When auto programming is completed, the programme list menu appears.

Manual programme



To change the channel. (Change each item in Manual Program and press the "MENU" button to save the settings)

Storage

Press the ◀► buttons to select the channel number or enter the programme number with the number buttons in where you want to store channel.

System

Press the ▼ ▲ buttons to select the TV system of the country or part of the world from where you want to receive the TV channels.

BG: PAL B/G, SECAM B/G (Europe/East Europe)

I: PAL I/II (U.K/Ireland)

DK: PAL D/K, SECAM D/K (East Europe)

L: SECAM L/L' (France)



STATION ID set/Select the channel when using the TV

Band Press the ▼ ▲ buttons to select VHF/UHF for aerial channels or Cable for cable channels.

To select the channel reception type. : VHF/UHF / Cable.

Channel If you know the channel number, enter it directly with the digit buttons 0 to 9.

Fine In case of poor reception, you can improve the reception by fine tuning. Use the ▼ ▲ buttons to fine tune for the best picture and sound.

Search Use the ◀ ▶ buttons to search next channel backward or forward direction.

Name To see the assigned channel name.

It is possible to change the name stored in the memory or to assign a name to a TV channel which has not yet been entered. A name with up 5 letters or numbers can be given to the programme numbers 0 to 99.

Press the ▼ buttons to move cursor to be changed. -> Press the ▼ buttons to select a character.(space, number 0~9, and alphabet A~Z, +,-) -> Press **OK** button or **MENU** button.

Programme edit





Delete Press the ▼ ▲ ◆ ▶ buttons to select a TV channel to be deleted. ->

Press the red key on the remote control -> The background colour of the selected channel will change to red.

Press the Delete button one more time to delete the selected channel. All the following channels are shifted up one position.

Copy Press the ▼ ▲ ◀ ▶ buttons to select a TV channel to be copied. -> Press the green key on the remote control. All the following channel

numbers are shifted down one position.

Move Press the ▼ ▲ ◀ ▶ buttons to select a channel number to be moved. -> Press the yellow key on the remote control. -> Press the ▼ ▲ ◀ ▶ buttons to move the TV channel to the desired channel number. ->

Press the yellow key again to release this function.

Skip Press the ▼ ▲ ◆ ▶ buttons to select a channel number to be skipped. -> Press the blue key on the remote control. The skipped TV channel is

displayed in blue.



STATION ID set/Select the channel when using the TV

Favourite programme



This function lets you select your favourite programmes directly. (8 channel) Press the ▼ ▲ ◆ ▶ buttons to select a channel.

* Yellow key (remote control):

Favourite Program On: Rotate favourite channel

Favourite Program Off: To display the previously selected TV channel.



PICTURE ID adjust the picture function(RGB/DVI)

PSM



The **PSM** function automatically adjusts the screen image quality.

• Dynamic

Select this option to display with a sharp image.

The most general and natural screen display status.

Select this option to display with a mild image.

Select this option to enjoy dynamic image when playing a game.

User

Select this option to use the user-defined settings.

CSM



The CSM function automatically adjusts the screen colour set.

• 9300K

Slightly purplish white.

• 6500K

Slightly bluish white.

• sRGB

Slightly lower brightness.

Select this option to use the user-defined settings. Red / Green / Blue

Set your own colour levels.

ΧD



XD is LG Electronics unique picture improving technology to display a real **HD** source through an advanced digital signal processing algorithm. It's not available to use this function in RGB-PC or **DVI-PC** modes.

Manual is activated after selecting the user of PSM. (It's not working RGB-PC, DVI-PC mode.)

Cinema (Function works in the following mode -TV, AV, Component 480i/576i)

When you watch the movie, this function adjusts the set to the best picture appearance.

(It's not working RGB/DVI mode.)

Return to the default settings PSM, CSM, XD, Cinema at the factory. Reset



PICTURE ID adjust the picture function (TV/Video)

PSM



The **PSM** function automatically adjusts the screen image quality.

• Dynamic

Select this option to display with a sharp image.

Standard

The most general and natural screen display status.

Mild

Select this option to display with a mild image.


• Game

Select this option to enjoy dynamic image when playing a game.

• User

Select this option to use the user-defined settings.

CSM



The **CSM** function automatically adjusts the screen colour set.

Cool

Slightly purplish white.

Normal

Slightly bluish white.

Warm

Slightly reddish white.

• Use

Select this option to use the user-defined settings. Red / Green / Blue

Set your own colour levels.

ΧD



XD is LG Electronics unique picture improving technology to display a real HD source through an advanced digital signal processing algorithm. It's not available to use this function in RGB-PC or DVI-PC modes.

Manual is activated after selecting the user of PSM.

Cinema (Function works in the following mode - TV, AV, Component 480i/576i)

When you watch the movie, this function adjusts the set to the best picture appearance.

Reset Return to the default settings **PSM**, **CSM**, **XD**, **Cinema** at the factory.



SOUND ID to adjust the sound function



SSM

The best sound tone quality will be selected automatically depending on the video type that you're currently watching.

- Flat: The most commanding and natural audio.
- Music: Select this option to enjoy the original sound when listening to the music.
- Movie: Select this option to enjoy sublime sound.
- Sports: Select this option to watch sports broadcasting.
- User : Select this option to use the user-defined audio settings.

AVL

To adjust uneven sound volumes across all channels or signals automatically to the most appropriate level. To use this feature, select **On**.

Balance

Use this function to balance sound from the left and right speakers.



TIME ID to adjust the time function



Clock

This function is used to set up of current time.

You must set the time correctly before using **On/Off time** function.

- 1) Press the **MENU** button and then use **▼** ▲ button to select the **TIME** menu.
- 2) Press the ▶ button and then use ▼ ▲ button to select the Clock menu.
 3) Press ▶ button and then use ▼ ▲ button to set the hour(00~23).
- 4) Press ▶ button and then use ▼ ▲ button to set the minutes(00~59). The default value is --: --.
- 5) Press the OK/MENU button to save.

Off/On time

The **Off time** automatically switches the set to off mode at the pre-set time.

- 1) Press the **MENU** button and then use $\blacktriangledown \blacktriangle$ button to select the **TIME** menu.
- 2) Press the ▶ button and then use ▼ ▲ button to select **Off time** or **On time**.
- 3) Press the ▶ button and then use ▼ ▲ button to set the hour(00~23).
- 4) Press the ▶ button and then use ▼ ▲ button to set the minutes(00~59).
- 5) Press the ▶ button and then use ▼ ▲ button to select **On** or **Off**.
- 6) Only On time function; Press the ► button and then ▼ ▲ button to adjust volume level and programme number.
- 7) Press the **OK/MENU** button to save.

Auto sleep

If **Auto sleep** is active and there is no input signal, the set switches to off mode automatically after 10 minutes. (It is not working in PC)

- 1) Press the **MENU** button and then use ▼ ▲ button to select the **Auto sleep** menu.
- 2) Press the ▶ button and then use ▼ ▲ button to select On or Off.
- 3) Press the OK/MENU button to save .



- In the event of power interruption (disconnection or power failure), the Clock must be reset.
- Two hours after the set is switched on by the **On time** function it will automatically switch back to off mode unless a button has been pressed.
- Once the **On** or **Off time** is set, these functions operate daily at the preset time.
- Off time function overrides On time function if they are set to the same time.
- The set must be in off mode for the **On time** to work.
- On time will move on to auto off if no activity is received in 2hours after setting the On time.



SPECIAL ID to Select the special function



Language To choose the language in which the control names are displayed.

CountryPlease select your local teletext language.

If you don't, the teletext may not appear correctly on the screen.

Try ou don't, the teletext may not appear correctly on the screen

This feature is not available in all countries.

Child lock Use the ▼ ▲ buttons to select On or Off. It can be set up so that it can only be used with

the remote control. This feature can prevent unauthorized viewing.

In order to lock the OSD screen adjustment, set the **Child lock** tab to the '**On**' position. In order to unlock it, do the following:

* Push the **MENU** button on the remote control and set **Child lock** to the '**Off**' position.

DDC-CI DDC/CI(Display Data Channel Command Interface) is communication protocol for

communications between PC and monitor.

DDC/CI makes it possible to adjust and setup detailed functions on PC instead of the monitor

OSD.

Monitor can be adjusted with PC by connecting communication between PC and monitor when DDC/CI is ON, and monitor cannot be adjusted with PC because communication between PC

and monitor is disconnected when DDC/CI is OFF.

XD Demo Use it to see the difference between XD demo on and XD Demo off.

(XD Demo function is not available in RGB PC/ DVI PC mode.)



SCREEN ID to adjust the screen function



Auto config.

This button is for the automatic adjustment of the screen **Position**, **Clock** and **Phase**. (It is not working in RGB-DTV, DVI.)

Manual config.

This button is for the manual adjustment of the screen Position, Clock and Phase.

- H-Position (It is not working In DVI-PC mode.)
 To move the displayed image left or right.
- V-Position (It is not working In DVI-PC mode.)
 To move the displayed image up or down.
- Clock (It is not working In RGB-DTV, DVI mode.)

 To minimize any vertical bars or stripes visible on the

To minimize any vertical bars or stripes visible on the screen background.

The horizontal screen size will also change.

• Phase (It is not working In RGB-DTV, DVI mode.)

To adjust the focus of the display. This item allows you to remove any horizontal noise and clear or sharpen the image of characters.

ARC

To select the image size of the screen.

- When TV/Video mode: Spectacle, Original, 4:3, 16:9, 14:9, Zoom1, Zoom2
- When RGB/DVI/Component mode: 4:3, 16:9

Reset

Use this function to reset the product to the factory default. However, language selection will not be initialized.(It is working in RGB-PC, RGB-DTV, DVI-DTV mode.)

Troubleshooting

No image is displayed

- Is the product's power cord connected?
- Is the power indicator turning on?
- Power is on, power indicator is blue but the screen appears extremely dark.
- Does the power indicator look amber?
- Does the 'Out of range' message appear?

Does the 'Check signal cable' message appear?

- Check if the power cord is properly connected to the outlet
- See if the power switch is turned on.
- · Adjust brightness and contrast again.
- If the product is in power saving mode, move the mouse or press any key.
- In DVD Player or Settop Box, check the power status of connected device.
- The signal from the PC (video card) is out of the vertical or horizontal frequency range of the product. Adjust the frequency range by referring to the Specifications in this user's quide.
 - * Maximum resolution

19 inch: **RGB**: 1440 X 900 @75 Hz **DVI**: 1440 X 900 @60 Hz

20.1 inch: 1680 X 1050 @60 Hz

22 inch: 1680 X1050 @60 Hz

- The signal cable between PC and product is not connected. Check the signal cable.
- Press the 'INPUT' button in the remote control to check the input signal.

'Unknown Product' message appears when the product is connected.

- Did you install the driver?
- Install the product driver, which is provided with the product, or download it from the web site. (http://www.lge.com)
- See if the plug&play function is supported by referring to the video card user's guide.



- * Vertical frequency: To enable the user to watch the product display, screen image should be changed tens of times every second like a fluorescent lamp. The vertical frequency or refresh rate is the times of image display per second. The unit is Hz.
- * Horizontal frequency: The horizontal interval is the time to display one vertical line. When the 1 is divided by horizontal interval, the number of horizontal lines displayed every second can be tabulated as the horizontal frequency. The unit is kHz.

Troubleshooting

The screen image looks abnormal.

- Is the screen position wrong?
- Adjust the Position menu in OSD.
- See if the video card resolution and frequency are supported by the product. If the frequency is out of range, set to the recommended resolution in the Control Panel – Display – Setting menu.
- Do thin lines appear on the background screen?
- Adjust the Clock menu in OSD.
- Horizontal noise appears or the characters look blurred.
- Adjust the Phase menu in OSD.

After-image appears on the product.

- After-image appears when the product is turned off.
- If you use a fixed image for a long time, the pixels may be damaged quickly. Use the screen saver function.

Troubleshooting

The audio function does not work.

No sound?

- Check if the audio cable is connected properly.
- Adjust the volume.
- Check if the sound is set properly.

Sound is too low.

• Adjust the volume.

The TV function does not work.

- The TV signal is not being received.
- See if you have selected the proper channel mode.
- Use the automatic channel setup function.
- Check if the TV antenna is properly connected.

Screen colour is abnormal.

- Screen has poor colour resolution (16 colours).
- Set the colour resolution to more than 24 bits (true colour)
- Select Control Panel Display Settings Colour Table menu in Windows.
- Screen colour is unstable or monocolour.
- Check the connection status of the signal cable. Or, re-insert the PC video card.
- Do black spots appear on the screen?
- Several pixels (red, green, white or black colour) may appear on the screen, which can be attributable to the unique characteristics of the LCD panel. It is not a malfunction of the LCD.

The product specifications can change without prior notice for product improvement.

[19 inch]

LCD Panel	Screen Type	19 inches Wide (48.14 cm) TFT (Thin Film Transistor) LCD (Liquid Crystal Display) Panel Visible diagonal size: 48.14 cm
	Pixel Pitch	0.285 mm
Video Signal	Max. Resolution	RGB : 1440 X 900 @75 Hz DVI : 1440 X 900 @60 Hz
	Recommended Resolution	1440 X 900 @60 Hz
	Horizontal Frequency	28 - 83 kHz
	Vertical Frequency	56 - 75 Hz
	Synchronization Type	Separate Sync, Digital
Input Connector		S-Video, Composite video, TV, D-Sub Analog, DVI-D
		SCART, PC Audio In, Headphone/Earphone, component
Power	Rated Voltage	AC 100-240V~ 50/60Hz 1.0A
	Power Consumption	On Mode : 50 W (Typ.)
		Sleep Mode ≤ 1 W
		Off Mode ≤ 1 W
Tilt	Tilt Range	-3° ~ 10°
	Swivel	350°
Dimension (Mainb	Size (WxLxH)	456.8 mm x 230.0 mm x 395.0 mm
Dimension/Weight	Weight (excl. package)	4.9 kg (10.8 lbs)
Environmental Conditions	Operational Condition Storage Condition	Temperature: 10° C ~ 35° C , Humidity: 20% ~ 80% Temperature: -10° C ~ 60° C , Humidity: 5% ~ 90%

The product specifications can change without prior notice for product improvement.

[20.1 inch]

LCD Panel	Screen Type Pixel Pitch	20.1 inches Wide (51.113 cm) TFT (Thin Film Transistor) LCD (Liquid Crystal Display) Panel Visible diagonal size: 51.113 cm 0.258 mm
Video Signal	Max. Resolution	RGB: 1680 X 1050 @60 Hz DVI: 1680 X 1050 @60 Hz
	Recommended Resolution	1680 X 1050 @60 Hz
	Horizontal Frequency	28 - 83 kHz
	Vertical Frequency	56 - 75 Hz
	Synchronization Type	Separate Sync, Digital
Input Connector		S-Video, Composite video, TV, D-Sub Analog, DVI-D
mpat comoctor		SCART, PC Audio In, Headphone/Earphone, component
Power	Rated Voltage Power Consumption	AC 100-240V~ 50/60Hz 1.0A On Mode : 50 W (Typ.) Sleep Mode ≤ 1 W Off Mode ≤ 1 W
Tilt	Tilt Range Swivel	-3° ~ 10° 350°
Dimension/Weight	Size (WxLxH) Weight (excl. package)	484.3 mm x 230.0 mm x 414.3 mm 4.8 kg (10.58 lbs)
Environmental Conditions	Operational Condition Storage Condition	Temperature: $10^{\circ}\text{C} \sim 35^{\circ}\text{C}$, Humidity: $20\% \sim 80\%$ Temperature: $-10^{\circ}\text{C} \sim 60^{\circ}\text{C}$, Humidity: $5\% \sim 90\%$

The product specifications can change without prior notice for product improvement.

[22 inch]

LCD Panel	Screen Type	22 inches Wide (55.868 cm) TFT (Thin Film Transistor) LCD (Liquid Crystal Display) Panel Visible diagonal size: 55.868 cm		
	Pixel Pitch	0.282 mm		
Video Signal	Max. Resolution	RGB : 1680 X1050 @60 Hz DVI : 1680 X1050 @60 Hz		
	Recommended Resolution	1680 X1050 @60 Hz		
	Horizontal Frequency	28 - 83 kHz		
	Vertical Frequency	56 - 75 Hz		
	Synchronization Type	Separate Sync, Digital		
Input Connector		S-Video, Composite video, TV, D-Sub Analog, DVI-D		
P		SCART, PC Audio In, Headphone/Earphone, component		
Power	Rated Voltage	AC 100-240V~ 50/60Hz 1.0A		
	Power Consumption	On Mode : 50 W (Typ.)		
		Sleep Mode ≤ 1 W Off Mode ≤ 1 W		
		Oil Mode S 1 W		
Tilt	Tilt Range	-3° ~ 10°		
	Swivel	350°		
Dimension/Meight	Size (WxLxH)	525.4 mm x 230.0 mm x 439.0 mm		
Dimension/Weight	Weight (excl. package)	5.82 kg (13 lbs)		
Environmental Conditions	Operational Condition Storage Condition	Temperature: $10^{\circ}\text{C} \sim 35^{\circ}\text{C}$, Humidity: $20\% \sim 80\%$ Temperature: $-10^{\circ}\text{C} \sim 60^{\circ}\text{C}$, Humidity: $5\% \sim 90\%$		

PC Mode – Preset Mode

[19 inch]

	Preset mode	Horizontal Frequency (kHz)	Vertical Frequency (Hz)		Preset mode	Horizontal Frequency (kHz)	Vertical Frequency (Hz)
1	720 x 400	31.468	70	11	1440 x 900	55.5	60
2	640 x 480	31.469	60	12	1440 x 900	55.935	60
3	640 x 480	37.500	75	13	1440 x 900	70.635	75
4	800 x 600	37.879	60				
5	800 x 600	46.875	75				
6	1024 x 768	48.363	60				
7	1024 x 768	60.123	75				
8	1152 x 864	67.500	75				
9	1280 x 1024	63.981	60				
10	1280 x 1024	79.976	75				

[20.1 inch] [22 inch]

	Preset mode	Horizontal Frequency (kHz)	Vertical Frequency (Hz)		Preset mode	Horizontal Frequency (kHz)	Vertical Frequency (Hz)
1	720 x 400	31.468	70	11	1680 x 1050	64.674	60
2	640 x 480	31.469	60	12	1680 x 1050	65.290	60
3	640 x 480	37.500	75				
4	800 x 600	37.879	60				
5	800 x 600	46.875	75				
6	1024 x 768	48.363	60				
7	1024 x 768	60.123	75				
8	1152 x 864	67.500	75				
9	1280 x 1024	63.981	60				
10	1280 x 1024	79.976	75				

DTV -Timming

	Preset mode	Horizontal Frequency (kHz)	Vertical Frequency (Hz)
1	720 x 480/60p	31.47	60
2	720 x 480/60p	31.5	60
3	720 x 576/50p	31.25	50
4	1280 x 720/50p	37.5	50
5	1280 x 720/60p	44.96	60
6	1280 x 720/60p	45	60
7	1920 x 1080/60i	33.72	60
8	1920 x 1080/60i	33.75	60
9	1920 x 1080/50i	28.125	50


Power Indicator

Mode	Product	
On Mode	Blue	
Sleep Mode	Amber	
Off Mode	Off	


VESA wall mounting

This product meets VESA-compliant mounting interface pad specifications.


 $\mathbf{1}_{\,ullet}$ Put the product on a piece of cloth or other soft surface with the front side facing downward.




4. Please pull and remove the stand body while sliding and holding the latches down.




5. Fasten the screw on the backside of the product and the other one in the joint of the stand.



6. Install the VESA standard wall mounting.





VESA wall mounting Connected to another

object (stand type and wall-mounted type).
This product accepts a VESA-compliant mounting interfacepad.
(This has to be purchased separately if required.)
For further information, refer to the VESA Wall Mounting Instruction Guide.