



# Perreaux

Model: PMF4000A

Date of Manufacture: 1980

Product Type: Stereo Power Amplifier

Power Output (*per channel into 8Ω*): 350W<sub>rms</sub>

## Specifications:

### Power Output

350W<sub>rms</sub> minimum per channel both channels driven into 8Ω from 20Hz to 20kHz at no more than 0.06% Total Harmonic Distortion from 0.25W to rated output.

### Output per channel at onset of clipping at 1kHz

Both channels driven into 8Ω ..... 380W<sub>rms</sub>  
Both channels driven into 4Ω ..... 600W<sub>rms</sub>

**Dynamic Headroom** ..... 1.5dB

### Frequency Response

Rated output ..... 10Hz-100kHz ±0.1dB

### Total Harmonic Distortion

350W<sub>rms</sub> into 8Ω from 20Hz to 20kHz ..... < 0.06%  
370W<sub>rms</sub> into 8Ω at 1kHz ..... < 0.006%

### Intermodulation Distortion (*S.M.P.T.E. method 60Hz and 7kHz mixed 4:1*)

3.6W to 36W into 8Ω ..... < 0.005%  
36W to rated output into 8Ω ..... < 0.008%  
Rated power ..... Typically 0.005%

**Slewing Rate** ..... 70V/μs

**Transient Response** ..... 0.8μs

**Phase Response** ..... +1° at 20Hz -1° at 20kHz

**Hum and Noise** ..... 95dB below rated output 20Hz to 20kHz (100dB "A")

### Damping Factor

10Hz-1kHz at 8Ω ..... > 150

**Input Impedance** ..... 10kΩ

### Input Sensitivity

For rated output at 1kHz ..... 1.5V<sub>rms</sub>

### Load Impedance

Rated for 8Ω usage but will safely drive any load from 4Ω up, including reactive loads such as full range electrostatic loudspeakers.

### Dimensions

Width ..... 483mm (19.0")  
Height ..... 266mm (10.5")  
Depth ..... 338mm (13.3")

**Weight** ..... 22.0kg (48.5lb)

Schematic diagram

Product manual