

CAMSHAFT: Performer RPM Roller Hydraulic
CATALOG #2263 & 2264



ENGINE: 1967 & Later Chevrolet 500+ c.i.d. V8
RPM RANGE: 1500-6500

CAUTION: Do not use dual valve springs. Use recommended valve springs with closed pressure of 120-130 lbs., open pressure of 320-340 lbs, and max lift of .700". Use stock ratio rockers only.

Duration at .006" Lift:	Intake 308°	Exhaust 315°
Duration at .050" Lift:	Intake 248°	Exhaust 256°

Lift at cam:	Intake .371"	Exhaust .381"
Lift at valve:	Intake .632"	Exhaust .648"

Timing at .050 Lift:	Open	Close
Intake	14.5° BTDC	62.5° ABDC
Exhaust	53.5° BBDC	13.5° ATDC

Centerlines: Int. 109.5° ATDC Exh. 114.5° BTDC
Lobe Separation: 112°

CAUTION: Use Edelbrock Performer-Link Timing Chain and Gear Set #7810 or Accu-Drive gear drive #7891. Do not use late model timing chain and gear sets that are designed for emission-controlled engines. These timing sets are machined in a retarded position and are not recommended for this camshaft installation. Edelbrock Timing Sets feature three keyways for specified timing selection. Use "0" position for most applications.

Catalog #2263, 2264
Rev. 9/07 - AJ/mc

©2007 Edelbrock Corporation
Brochure #63-2263C

CAMSHAFT: Performer RPM Roller Hydraulic
CATALOG #2263 & 2264



ENGINE: 1967 & Later Chevrolet 500+ c.i.d. V8
RPM RANGE: 1500-6500

CAUTION: Do not use dual valve springs. Use recommended valve springs with closed pressure of 120-130 lbs., open pressure of 320-340 lbs, and max lift of .700". Use stock ratio rockers only.

Duration at .006" Lift:	Intake 308°	Exhaust 315°
Duration at .050" Lift:	Intake 248°	Exhaust 256°

Lift at cam:	Intake .371"	Exhaust .381"
Lift at valve:	Intake .632"	Exhaust .648"

Timing at .050 Lift:	Open	Close
Intake	14.5° BTDC	62.5° ABDC
Exhaust	53.5° BBDC	13.5° ATDC

Centerlines: Int. 109.5° ATDC Exh. 114.5° BTDC
Lobe Separation: 112°

CAUTION: Use Edelbrock Performer-Link Timing Chain and Gear Set #7810 or Accu-Drive gear drive #7891. Do not use late model timing chain and gear sets that are designed for emission-controlled engines. These timing sets are machined in a retarded position and are not recommended for this camshaft installation. Edelbrock Timing Sets feature three keyways for specified timing selection. Use "0" position for most applications.

Catalog #2263, 2264
Rev. 9/07 - AJ/mc

©2007 Edelbrock Corporation
Brochure #63-2263C

CAMSHAFT: Performer RPM Roller Hydraulic
CATALOG #2263 & 2264



ENGINE: 1967 & Later Chevrolet 500+ c.i.d. V8
RPM RANGE: 1500-6500

CAUTION: Do not use dual valve springs. Use recommended valve springs with closed pressure of 120-130 lbs., open pressure of 320-340 lbs, and max lift of .700". Use stock ratio rockers only.

Duration at .006" Lift:	Intake 308°	Exhaust 315°
Duration at .050" Lift:	Intake 248°	Exhaust 256°

Lift at cam:	Intake .371"	Exhaust .381"
Lift at valve:	Intake .632"	Exhaust .648"

Timing at .050 Lift:	Open	Close
Intake	14.5° BTDC	62.5° ABDC
Exhaust	53.5° BBDC	13.5° ATDC

Centerlines: Int. 109.5° ATDC Exh. 114.5° BTDC
Lobe Separation: 112°

CAUTION: Use Edelbrock Performer-Link Timing Chain and Gear Set #7810 or Accu-Drive gear drive #7891. Do not use late model timing chain and gear sets that are designed for emission-controlled engines. These timing sets are machined in a retarded position and are not recommended for this camshaft installation. Edelbrock Timing Sets feature three keyways for specified timing selection. Use "0" position for most applications.

Catalog #2263, 2264
Rev. 9/07 - AJ/mc

©2007 Edelbrock Corporation
Brochure #63-2263C

CAMSHAFT: Performer RPM Roller Hydraulic
CATALOG #2263 & 2264



ENGINE: 1967 & Later Chevrolet 500+ c.i.d. V8
RPM RANGE: 1500-6500

CAUTION: Do not use dual valve springs. Use recommended valve springs with closed pressure of 120-130 lbs., open pressure of 320-340 lbs, and max lift of .700". Use stock ratio rockers only.

Duration at .006" Lift:	Intake 308°	Exhaust 315°
Duration at .050" Lift:	Intake 248°	Exhaust 256°

Lift at cam:	Intake .371"	Exhaust .381"
Lift at valve:	Intake .632"	Exhaust .648"

Timing at .050 Lift:	Open	Close
Intake	14.5° BTDC	62.5° ABDC
Exhaust	53.5° BBDC	13.5° ATDC

Centerlines: Int. 109.5° ATDC Exh. 114.5° BTDC
Lobe Separation: 112°

CAUTION: Use Edelbrock Performer-Link Timing Chain and Gear Set #7810 or Accu-Drive gear drive #7891. Do not use late model timing chain and gear sets that are designed for emission-controlled engines. These timing sets are machined in a retarded position and are not recommended for this camshaft installation. Edelbrock Timing Sets feature three keyways for specified timing selection. Use "0" position for most applications.

Catalog #2263, 2264
Rev. 9/07 - AJ/mc

©2007 Edelbrock Corporation
Brochure #63-2263C