

# Optquest® Q19wb-2

**19" WIDESCREEN LCD**  
**WITH FAST 5MS VIDEO RESPONSE**

## Widescreen, multimedia display.

The Optquest Q19wb-2 19" widescreen LCD integrates high brightness and contrast ratios with super-fast video response. Enhance your productivity with this widescreen display that lets you work in two applications or documents side-by-side. Enjoy the crystal-clear, blur-free video and graphics delivered by broadcast-quality, 5ms video response. Built-in speakers deliver rich, stereo sound. The integrated power supply and VESA® wall-mount compliance reduce clutter and free up valuable desktop real estate. The OSD lock ensures your screen settings are secure and the Kensington® security port provides theft deterrence. Furnish your workplace in style with the budget-friendly, feature-rich Q19wb-2 LCD.



### ELEGANCE AND PERFORMANCE IN AN AFFORDABLE DISPLAY

- > Fast 5ms video response delivers superior picture clarity
- > High brightness and contrast ratio  
300-nit brightness (typ) and 700:1 contrast ratio (typ) for rich, detailed images.
- > 1440x900 optimum resolution  
Incredible image detail for sharp text and graphics.
- > Stylish slim-bezel design  
An ultra-thin bezel lets you see more without taking up valuable desktop real estate.
- > OnView® controls for superior screen adjustability  
Screen adjustments are precisely made via an easy-to-use on-screen menu.
- > Full 19" viewable widescreen  
Displays a full, flat 19" viewable area with crisp detail and fully saturated color.
- > Multimedia enhanced  
Save desk and workspace and enjoy rich stereo sound with two built-in stereo speakers.
- > Integrated power supply
- > VESA® 100mm wall-mount compliant
- > 24/7 free technical and customer support\*
- > PC and Mac® compatible



**VIEWSONIC**  
PRODUCTS, PROGRAMS,  
AND SERVICES

**ViewSonic®**   
See the difference®

# Optquest® Q19wb-2

19" WIDESCREEN LCD WITH FAST 5MS VIDEO RESPONSE



<b>LCD</b>	Type	19" color TFT active matrix SXGA LCD
	Display Area	16.1" horizontal x 10.0" vertical; 19.0" diagonal
	Optimum Resolution	1440x900
	Contrast Ratio	700:1 (typ)
	Viewing Angles	150° horizontal, 140° vertical @ contrast ratio > 10:1
	Response Time	5ms (typ)
	Light Source	Long life, 50,000 hrs. (typ)
	Brightness	300 cd/m2 (typ)
	Panel Surface	Anti-glare
<b>INPUT SIGNAL</b>	Video	RGB analog (75 ohms, 0.7 Vp-p)
	Sync	H/V separated (TTL)
	Frequency	F <sub>H</sub> : 31~81kHz, F <sub>V</sub> : 50~75Hz
<b>COMPATIBILITY</b>	PC	VGA up to 1440x900 non-interlaced
	Mac***	Power Mac™ G3/G4/G5 up to 1152x870
<b>CONNECTOR</b>	Analog PC	15-pin mini D-sub
	Power	3-pin AC plug (CEE22)
<b>POWER</b>	Voltage	AC 100~240V (universal), 50/60Hz (auto switch)
	Consumption	36W (typ)
<b>AUDIO</b>	Speakers	2x1-watt
<b>CONTROLS</b>	Basic	Power, 2, up, down, 1
	OnView®	Auto image adjust, brightness, contrast, ViewMatch® color adjust (sRGB, 9300K, 6500K, 5400K user color), H. position, V. position, H. size, resolution notice, OSD position, OSD timeout, OSD background, fine tune, sharpness, language, recall, volume, mute
<b>OPERATING CONDITIONS</b>	Temperature	32~104°F (0~40°C)
	Humidity	10~90% (non-condensing)
<b>DIMENSIONS (W x H x D)</b>	Physical with stand	17.6" x 14.3" x 8.4" (446mm x 364mm x 213mm)
	Physical without stand	17.6" x 11.5" x 2.6" (446mm x 292mm x 67mm)
<b>WEIGHT</b>	Net with stand	9.7 lb. (4.4 kg)
	Net without stand	8.8 lb. (4.0 kg)
	Gross with stand	11.2 lb. (5.1 kg)
<b>REGULATIONS</b>	UL, cUL, FCC-B, ENERGY STAR®, TCO'99, ICES-003B, RoHS, CB, CE, WEEE, ISO13406-2, TUV-S, NOM, GOST-R	
<b>POWER MANAGEMENT</b>	Meets TCO'99 and ENERGY STAR® standards	
<b>PACKAGE CONTENTS</b>	LCD display, power cable, video cable, audio cable, Quick Start Guide, Wizard CD-ROM	
<b>WARRANTY</b>	One-year limited warranty on parts and backlight	



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

**ViewSonic®**  
See the difference®

Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

\*Excluding major U.S. holidays. \*\*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2008 ViewSonic Corporation. All rights reserved. [14184-00B-10/08] Q19wb-2

For more product information, visit us on the web at ViewSonic.com