



G2016wa1

Cabinet Color	Black
Panel	TFT Active Matrix LCD VIS: 20" Widescreen, Diagonal Hard Coating (3H)
Pixel Pitch	0.258mm x 0.258mm
Display Area	433.44mm x 270.90mm
Brightness	300 cd/m2 (typ)
Contrast Ratio	1000:1 (typ)
Response Time	5ms (typ)
Viewing Angle	Horizontal: 160 Degrees (CR>10) Vertical: 160 Degrees (CR>10)
Compatibility	VESA, WSXGA+, WXGA+, SXGA, XGA, SVGA, VGA Mac® Equipped With Analog VGA Dsub or DVI Port
Scanning Frequency	Horizontal: 30K~83KHz Vertical: 55~75 Hz
Pixel Frequency	146MHz
Maximum Resolution	1680x1050x60Hz
Recommended Resolution	1680x1050@60Hz
Resolutions Supported	720x400@70Hz, 640x480@60, 72, 75Hz 800x600@56, 60, 72, 75Hz, 832x624@75Hz 1024x768@60, 70, 72, 75Hz, 1280x1024@60, 70, 72, 75Hz, 1280x960@60Hz, 1680x1050@60Hz
Color	16.7M
Signal Input	Video: 0.7Vp-p, RGB Analog Separate Sync: TTL Level H/V Sync: Positive / Negative
Digital Input	DVI-D (TMDS) with HDCP*
Connectors	Analog RGB Signal: 15-pin D-sub Male Digital Signal: 24-pin DVI-D Power: (3-Pin Plug CEE22) Audio: 3.5m Stereo
Power Source	Universal 110~240VAC, 50/60Hz
Power Consumption	49Watts (Max)
Plug & Play	DDC2B
EPA ENERGY STAR®	Yes
User Control	Menu, Down/Brightness, Up/Contrast, Confirm, Power On/Off
OSD Function	Auto Adjust, Contrast, Brightness, Color Adjust (sRGB, 9300K, 6500K, 5400K, User Color), Information, Image Adjust (H/V Position, H-Size, Fine Tune, Sharpness), Setup (Language, Resolution Notice, OSD Setup, Input Select), Recall, Audio Setup
OSD Languages	English, French, Spanish
Regulations	cULus, FCC, CE, Windows Vista
Built-in Speakers	1W x 2
Other Features	720p/1080i HD Compatible, VESA 100mm Wall Mount Compliant**, Kensington Security Slot
Dimensions (WxHxD mm)	Monitor: 480.5x391.1x200; Carton 445x530x135
Dimensions (WxHxD inches)	Monitor: 18.9x15.4x7.9; Carton 17.5x20.9x5.3
Monitor Dimensions w/o Base (WxHxD)	480.5x338.7x79.4mm; 18.9x13.3x3.1 inches
Weight	10 lbs (4.56 kgs) Net 12 lbs (5.45 kgs) Gross
Loading Qty w/pallet	20' = 720 pcs.; 40' Std = 1584 pcs.
UPC Code	685417103683