



SkylinkHome™

Specification



TC series Deluxe Remote

TC-434-7, TC-434-10, TC-434-14 (Europe)

TC-318-7, TC-318-10, TC-318-14 (North America)

Product Features:

- Operates 3 to 10 SkylinkHome™ receivers
- Turns lightings on/ off and dim
- Comes with advance features such as Zone On/ Off, Zone Dimming, All On/ Off
- Comes with wall mount bracket

Packaging:

- Clamshell (remote, bracket, battery, manual and mounting accessories)
- 185 x 135 x 31mm, 100gm
- 10 units per inner carton
- 318 x 166 x 210mm, 1.5kg
- 160 units per shipping carton
- 690 x 650 x 460mm, 22.5kg

Radio Frequency:

- Skylink® Rolling Code
- Frequency 433.92MHz (Europe)
318MHz (North America)
- RF output Power EIRP: -12.5dBm
- Operating range of 100m/ 300ft (open area)

Working Environment:

- Operation temperatures -20°C ~ 60°C
- Storage temperatures -40°C ~ 70°C

Battery:

- 3V Lithium battery
- Battery life of 2 to 3 years

Dimension:

- 85 x 54 x 9.2mm
- Weight 32g
- ABS plastic housing

International Approvals:

- CE, FCC, UL

Skylink Group

www.skylinkhome.com

International Sales Office
Room 1303, Block B, Veristrong Industrial Centre,
34-36 Aupui Wan Street, FoTan Hong Kong
Te: 852-2602-1318 Fax: 852-2602-4684
Email: sales@skylinkhome.com

North American Sales Office
17 Sheard Avenue, Brampton,
Ontario, L6Y 1J3, Canada
Tel: 1-905-4568-883 Fax: 1-905-4567-819
Email: Skylink@skylinkhome.com