

MDR-RF950RK

SERVICE MANUAL

Ver 1.0 1998.06

US Model
Canadian Model



MDR-RF950RK is composed of the following models.
As for the service manual, it is issued for each component model,
then, please refer to it.

Headphones	MDR-RF950
Transmitter	TMR-RF950R

SPECIFICATIONS

General

Carrier frequency	913.0 – 915.0 MHz
Channel	Ch1, Ch2, Ch3
Modulation	FM stereo
Frequency response	18 – 22,000 Hz

Headphones

Power source	DC3V: 2 × R6 (size AA) battery or 2 × supplied NC-AA-HJ Ni-Cd rechargeable battery
Mass	Approx. 265 g (9.4 oz.) incl. Ni-Cd batteries

Transmitter

RF power	Less than 94 dB μ V/m at 3 m
Power source	DC9 V: supplied AC power adaptor
Audio input	phono jacks/stereo mini jack
Dimensions	Approx. 120 mm dia × 290 mm (4 ³ / ₄ × 11 ¹ / ₂ in.) (w/h)
Mass	Approx. 155 g (5.5 oz.)

Supplied Ni-Cd rechargeable batteries

Model name	NC-AA (HJ)
Voltage	1.2 V
Capacity	600 mAh

Battery life

Battery	Approx. hours*
Sony alkaline battery SG (LR6)	60
Sony battery SR (R6P)	30

* at 1 kHz, 1 mW + 1 mW output

Design and specifications are subject to change without notice.

ACCESSORIES & PACKING MATERIALS

Ref. No.	Part No.	Description
Δ	1-465-948-21	ADAPTOR, AC (AC-S901)
Δ	1-506-652-11	ADAPTOR, PLUG
	1-528-803-41	BATTERY, NICKEL CADMIUM
	1-575-195-11	CORD, CONNECTION
	3-864-034-11	MANUAL, INSTRUCTION (ENGLISH, SPANISH) (US)
	3-864-034-21	MANUAL, INSTRUCTION (ENGLISH,FRENCH) (Canadian)

The components identified by
mark Δ or dotted line with
mark Δ are critical for safety.
Replace only with part number
specified.

Les composants identifiés par une
marque Δ sont critiques pour la
sécurité.
Ne les remplacer que par une pièce
portant le numéro spécifié.

WIRELESS STEREO HEADPHONE SYSTEM

SONY®

