



# Passport 10G / 20G Headsets



- Compatible with GN Netcom® and VXI Passport G-series amplifiers and direct connect cords. *Note: Headset connects to the quick disconnect on the amplifier's headset cord.*
- Noise-canceling microphone greatly reduces background noise for a professional sounding call
- Durable construction to endure the stress of the 24/7 call center
- Virtually indestructible, highly flexible gooseneck boom. Rotates for left or right ear placement. Maintains position for consistent voice quality
- Sturdy quick disconnect allows fast and easy detachment from lower cord for greater mobility
- Adjustable headband secures positional adjustment, won't slide out of position
- Concave ear cushion for greater comfort and improved sound



Passport 10G



Passport 20G

**2** YEAR *Unconditional* WARRANTY

### TRANSMIT SPECIFICATIONS

Microphone: Noise canceling electret  
 Ambient noise suppression: 13db @ 1kHz, typical  
 Output impedance: 1.8k Ohms typical  
 Sensitivity: -44dB @ 1kHz (defined 1" from talk-side, 82dB SPL)  
 Frequency response: 20Hz to 15 kHz.  
 Operating Current: 320 mA max.  
 Operating Voltage: DC 1.0V min. to 20V max.

### RECEIVE SPECIFICATIONS

Speaker: Dynamic; 36mm diameter  
 SPL: 90db @ 1kHz, 0.55V input  
 Impedance: 300 Ohms  
 Frequency response: 200Hz to 5 kHz  
 Rated input: 10mW continuous, 100mW peak

### MECHANICAL SPECIFICATIONS

Cables: Standard wire, PVC insulation, polyurethane jacket  
 Connectors: Gold-plated; quick disconnect  
 Microphone boom: Flexible with positioning memory; swivels 300 degrees; left or right ear placement  
 Headband: Nylon plastic and #316 stainless;