


Outdoor Receiver
WV-RC150



- Outdoor receiver unit for pan/tilt mechanism
- Supplies 24V AC to a camera and a pan/tilt mechanism

DIMENSIONS



Unit : mm (inches)

SPECIFICATIONS

Power Source	120V AC $\pm$ 10% 60Hz
Input Signal	
Camera Input	1V[p-p]/75 Ω (Multiplexed video signal)(BNC)
Mic Input	600 Ω Balanced, -78dBV (1/4-type phone jack) (possible to use 600 Ω Unbalanced)
Output Signal	
Video Output	1V[p-p]/75 Ω (Multiplexed video signal)(BNC)
Audio Output	-10dBV, 10k Ω Minimum Load Impedance
Speaker Output	8 Ω , 1W Max.
Control Terminal	Aux-1: 125V AC, 3.5A (cos ϕ = 0.4) Aux-2: 125V AC, 3.5A (cos ϕ = 0.4)
Lens Voltage Supply	6V DC or 12V DC switchable (Fine adjustable)
Ambient Operating Temperature	-30°C - +50°C (-22°F - +122°F)
Dimensions (W x H x D)	200 x 85 x 425 mm (7-7/8" x 3-3/8" x 16-3/4")
Weight	8.3 kg (18.5 lbs.)