#### **ENFORCER®** PUSH-TO-EXIT PLATES

#### SD-7202GC-PE

- Stainless-steel, single-gang.
- 2" square, green, illuminated, momentary push button.
- Includes: "PUSH TO EXIT" & "PRESIONE PARA SALIR."
- N.O./N.C. contacts rated 10 Amps @ 125 ~ 250 VAC.
- Includes color-coded leads.

### SD-7103GC-PE

- Stainless-steel slimline plate.
- ► Green illuminated momentary button (<sup>15</sup>/<sub>16</sub> x <sup>11</sup>/<sub>16</sub>").
- Long-life green 12V LED.
  Includes: "PUSH TO EXIT" &
- "PRESIONE PARA SALIR." N.O./N.C. contacts rated
- 5 Amps @ 125 ~ 250 VAC.

### Spanish & English messages included

EXIT

NEW

## SD-7202BC-HC

- Stainless-steel, single-gang plate.
- 2" square, blue, illuminated, momentary push button.
- Handicap symbol.
- N.O./N.C. contacts rated 10 A @ 125 ~ 250 VAC.
- Includes color-coded leads.



## SD-7201GC-PE1

- Stainless-steel single-gang plate.
- ► Green, 1<sup>1</sup>/<sub>2</sub>" dia., mushroom-cap push button.
- "Exit" and "Salida" silkscreened on plate.
- ► N.O./N.C. contact rated 5A @ 125VAC.



- Stainless-steel single-gang plate.
- ► Vandal-resistant, 1¾" dia., stainless-steel pushbutton.
- "Exit" and "Salida" silk-screened on plate.
- N.O./N.C. contact rated 5A @ 250VAC.



### SD-7101KB-PE1

- Stainless-steel slimline plate.
- Black momentary push-button switch.
- "Exit" and "Salida" silk-screened on plate.
- N.C. contact rated 1A @ 125VAC.



# SD-7104SC-PE1

Stainless-steel slimline plate.

NFW

- Vandal-resistant, 1<sup>3</sup>/<sub>4</sub>" dia., stainless-steel pushbutton.
- "Exit" and "Salida" silk-screened on plate.
- ► N.O./N.C. contact rated 5A @ 250VAC.



The SECO-LARM policy is one of continual development. For that reason, SECO-LARM reserves the right to change prices and specifications without notice. SECO-LARM is not responsible for misprints.