



## VL647iLT


2.8-12mm DC Auto Iris Varifocal Lens  
Weather/Tamper resistant dome (IP67 rating)  
Day/Night camera without using IR LEDs

### Features

- 580 TV lines
- 0.00001 lux (Intense Light @ 256x)
- Featuring HLC for enhanced backlight operation
- Digital image stabilization
- Advanced noise reduction circuitry eliminates blur
- Chameleon™ Cover - snaps on and can be painted to match any décor!
- 5 year warranty



Camera shown with snap-on  
Chameleon™ Cover



### Specifications

Image Pick-Up Device..... 1/3" Sony Super HAD II™ CCD  
Total Pixels ..... 811(H) \* 508(V)  
Effective Pixels ..... 768(H) \* 494(V)  
Scanning System ..... 2:1 Interlace  
Synchronization ..... Internal  
OSD ..... Available  
Backlight ..... SLC / HLC / OFF selectable  
Resolution ..... 580 TV lines  
S/N (Y signal) ..... 52dB (AGC Off, Weight On)  
Minimum Illumination ..... 0.00001 Lux (Intense Light x256)  
White Balance ..... ATW / AWB / AWC - SET /Manual/  
Indoor / Outdoor  
Electronic Shutter Speed ..... Auto (1/50 sec, 1/60sec~1/100,000sec)  
Intense-LT ..... Off/ Auto (Selectable limit x2 ~ x256)  
Gain Control ..... High / Middle / Low / Off - selectable  
S-DNR ..... On / Off (0 ~ 100 level adjustable)  
S-WDR ..... Indoor / Outdoor / Off  
Motion Detection ..... On / Off (4 zone)

Privacy ..... On / Off (8 zone)  
Mirror ..... Off / Mirror / V-Rev / Rotate  
Freeze ..... On / Off  
Sharpness ..... 0 ~ 31' (level adjustable)  
D&N Selection ..... Color / BW / Auto  
Digital Zoom ..... On (x32) / Off  
Power ..... DC 12V  
Power Consumption ..... 200mA  
Operational Temp. .... 14° F ~ 122° F RH 95% Max.  
Storage Temp. .... - 4° F ~ 140° F RH 95% Max  
Dimension ..... 3.23"(H) \* 4.33"(D)  
Weight ..... 1.54 lbs.



Speco Technologies is constantly developing and improving products.  
We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Rev. 9/6/11