

ENFORCER[®]

Burglar

SM-431-T Quick-Connect Surface Mount

SM-433-T Concealed Screws Surface Mount

SM-407-5T Quick-Connect Recessed Mount

SM-431-T

- ▶ Miniature surface-mount magnetic contact with magnet.
 - ▶ For normally closed (N.C.) circuits.
 - ▶ Quick-connect terminal block. External screw terminals.
 - ▶ Tape to cover screw terminals included.
 - ▶ Screw mount using side flanges, or break off flange for adhesive mounting.
 - ▶ 1" (25mm) gap. 2" x 3/8" x 1/4".
 - ▶ **Gold-plated terminals** for longer life.
- SM-431-T/W: White color
SM-431-T/B: Brown color



SM-433-T

- ▶ Miniature surface-mount magnetic contact with magnet.
 - ▶ For normally closed (N.C.) circuits.
 - ▶ Cover hides mounting screws and terminal block.
 - ▶ Mount with included screws.
 - ▶ 1-1/4" (31mm) gap. 2" x 9/16" x 1/2".
 - ▶ **Gold-plated terminals** for longer life.
- SM-433-T/W: White color
SM-433-T/B: Brown color



SM-407-5T

- ▶ Stubby 3/8" press-fit magnetic contact with magnet.
 - ▶ For normally closed (N.C.) circuits.
 - ▶ Quick-connect terminal block.
 - ▶ Switch and magnet have ribs for securing in holes.
 - ▶ 3/4" (18mm) gap. 1" x 7/16" x 3/8" (switch).
 - ▶ **Gold-plated terminals** for longer life.
- SM-407-5T/W: White color
SM-407-5T/B: Brown color



*These SECO-LARM contacts incorporate **Gold-Plated Terminals** to help increase the life of the contact. In addition, most SECO-LARM magnetic contacts incorporate reed switches with a superior breakdown voltage and a deactivated rhodium plating to eliminate absorption of organic impurities, polymer growth during operation, and the possibility of contact freezing, especially at the lower voltage levels normally used in security systems. SECO-LARM offers the most reliable contacts.*

Copyright © 2008 SECO-LARM

The SECO-LARM policy is one of continual development. For that reason, SECO-LARM reserves the right to change prices and specifications without notice. SECO-LARM is not responsible for misprints.

SECO-LARM[®]
16842 Millikan Avenue, Irvine, CA 92606

1.949.261.2999 (CA & Int'l)
Email: info@seco-larm.com

1.800.662.0800 Fax: 1.949.261.7326
Website: www.seco-larm.com


MagneticContactseMail.cdr