

DHT-488XP

Home Theater System

DENON

5.1 Home Theater System featuring AVR-488 HDMI 1.3a-A/V Receiver and Acoustically Matched Speaker System.



Bullet points

AVR-488 Receiver Features

The Latest HD Video Support

- HDMI 1.3a switching*
- Deep Color up to 36-bit and xvYCC broader color space support
- 1080p video pass through

*No audio support

Denon Design Solutions for Maximizing Content Quality

- Identical quality and power for all 7 channels, 75W x 5ch
- New 32-bit floating point DSP
- Minimum signal path design
- Direct Mechanical Ground for stable drive
- Dual power transformer
- Denon customised block capacitor
- Separate unit design

Digital Media Connectivity

- Network Audio/Photo Ready (optional ASD-3N/3W)
- iPod Audio/Photo and Video playback (optional ASD-1R/3N/3W)
- XM Ready



Compressed Audio Restorer

*Shown ASD-3W

Denon's new audio technology for MP3/WMA/AAC compressed audio formats to reproduce higher frequency range and deeper bass sound.

Ease-of-Use

- 3 Quick Select Buttons
- New back panel layout

SYS-57HT 5.1 Speaker System Features

Two way design satellite speakers

- 3.6" mid-bass drivers and 3/4" tweeter
- MDF wooden cabinet
- Magnetically shielded
- Built-in wall mount brackets
- Removable grilles

Center speaker

- Dual 3.6" mid-bass drivers
- 3/4" soft dome tweeter
- MDF wooden cabinet
- Magnetically shielded
- Built-in wall mount brackets
- Removable grilles

Matching Subwoofer

- 8" down-firing design
- 100 watt power amplifier
- LF Direct mode
- Volume adjustment
- Cross over frequency adjustment

Receiver AVR-488 Input / Output terminals

IN			OUT		
HDMI		2	HDMI Monitor		1
Component		3	Component Monitor		1
S-Video		3	S-Video REC		1
Composite		4	Monitor		1
Analog audio (Tuner included)		8	Composite REC		1
Analog EXT. Input		5.1ch	Monitor		1
Digital OPTICAL		2			
Digital COAXIAL		2	Analog audio REC		2
Dock control for iPod		1	Analog Preout		1

AVR-488 Specifications

Power Amplifier Section

Rated output	*THD figures are power amp stage values.
Front	75 W + 75 W (8 ohms, 20Hz - 20kHz) 110W + 110W (6 ohms, 1kHz)
Center	75 W (8 ohms, 20Hz - 20kHz) 110W (6 ohms, 1kHz)
Surround	75 W + 75 W (8 ohms, 20Hz - 20kHz) 110W + 110W (6 ohms, 1kHz)

General

Power supply	AC 120 V, 60 Hz
Dimensions (WxHxD)	434 x 171 x 377 mm 17-3/32" x 6-47/64" x 14-27/32"
Weight	10.4 kg, 22.9 lbs

SYS-57HT Specifications

Satellite speakers

Nominal Impedance	6 ohms
Dimensions (WxHxD)	120 x 180 x 156 mm 4-23/32" x 7-3/32" x 6-9/64"
Weight	1.6 kg, 3.5lbs / each

Center speaker

Nominal Impedance	6 ohms
Dimensions (WxHxD)	266 x 120 x 156 mm 10-3/64" x 4-23/32" x 6-9/64"
Weight	2.1 kg, 4.6 lbs

Subwoofer

Power supply	AC 120 V, 60 Hz
Dimensions (WxHxD)	262 x 357 x 434 mm 10-1/32" x 14-1/64" x 17-1/64"
Weight	11.7 kg, 25.7 lbs

Accessories

AVR-488		SYS-57HT	
Remote	1	Spkare wires	5
Batteries	2	Pln cable for subwoofer	1
FM antenna	1	Wall mount bracket	5
AM loop antenna	1		
Quick setup sheet	1		



- Design and specifications are subject to change without notice.
- Dolby and the double-D symbol are registered trademarks of Dolby Laboratories.
- DTS is a registered trademark & the DTS logos and symbol are trademarks of DTS, Inc.
- ©2007 XM Satellite Radio Inc. All rights reserved.