

Accessories

Straight head Part No. 192440-7

(For E-form bit)





(For C-form bit) Part No. 135200-4










Angle wrench head


9.5mm (3/8") square drive

Part No. 135201-2





9.5mm (3/8") square drive Part No. 134745-9





Part No. 134746-7



Use with Ratchet head Size:17x 31 Part No. 134743-3

Size:19x 33 Part No. 134744-1



Cordless Angle Impact Driver / Cordless Angle Impact Wrench BTL060 / BTL061 BTL062 / BTL063 Variable Speed Machine screw M4 - M8 (5/32" - 5/16") Reversing M4 - M12 (5/32" - 1/2") Standard bolt Electric Brake High tensile bolt M4 - M8 (5/32" - 5/16") M4 - M8 (5/32" - 5/16") Coarse thread (in length) 22 - 75mm (7/8" - 2-31/32") Carrying Case Driving shank 6.35mm (1/4") Hex 9.5mm (3/8") Square 0-3,000 Impacts per minute (ipm) 0-3,000 Built-in Job Light No load speed (rpm) 0-2,000 Max. fastening torque 60N.m (531in.lbs) 60N.m (531in.lbs) 387 x 78 x 97mm (BTL060) 387 x 78 x 97mm (BTL062) (15-1/4" x 3-1/16" x 3-13/16") (15-1/4" x 3-1/16" x 3-13/16") (L x W x H) 387 x 78 x 116mm (BTL061) 387 x 78 x 116mm (BTL063) (15-1/4" x 3-1/16" x 4-9/16") (15-1/4" x 3-1/16" x 4-9/16") 1.6kg (3.5lbs) (BTL060) 1.6kg (3.5lbs) (BTL062) 1 7kg (3 7lbs) (BTI 061) 1.7kg (3.7lbs) (BTL063) Voltage 14.4V (BTL060), 18V (BTL061) 14.4V (BTL062), 18V (BTL063) Standard Equipment Fast Charger, Battery Cartridge, Phillips Bit (BTL060, BTL061) (Tool does not come with socket: BTL062, BTL063)

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN Z23339-2 2007-10





Compact & Slim for Easy Handling

Compact Angle Head

Easy fastening in close and wall-to-close spots with Smallest - in-class Head Height and 360 degrees (8 positions in 45-degree increments) rotatable Head

Optional attachment Straight Head Rachet Head for versatility Angl wrench head

Ergonomically designed rubberized soft grip

provides more comfort and control while minimizing hand fatigue and pain.

Belt Clip

Phosphorescent Bumper convenient in dark place

LED Job Light with Afterglow Function -

on pulling switch trigger, the light turns on automatically before motor starts turning. Keeps on illuminating about 12-13 sec. after trigger release.







Variable speed contorl by trigger

makita

ensures optimum fastening speed.

Electric brake for quick stop

Conveniently located push button type Reverse Switch

Slim Circumference Grip

Fits comfortably in the palm of a hand for various applications with ergonomically rubberized grip and easy-to-pull switch lever, and provides comfortable operation in horizontal and overhead applications.





Photo: BTL060



Cordless Angle Impact Drivers









