Thakita 18V LXT LITHIUM-ION 3/8" ANGLE IMPACT WRENCH

COMPACT RIGHT ANGLE IMPACT WRENCH FOR FASTENING AND LOOSENING IN TIGHT SPACES Makita Built Motor and Impact Mechanism Produces 530 in. lbs. of Maximum

Torque and 0-3,000 IPM

Variable Speed (0-2,000 RPM) for a Range of Applications from Auto Repair to Product Assembly

Large Conveniently Located Paddle Switch for Comfortable Operation

Over One Foot of Tool Extension for Extra Reach Into Tight Spaces



18V POWER. 12V WEIGHT.

Models BTL063

BTL063Z

POWER



Makita built motor and impact mechanism produces 530 in.lbs. of torque and 3,000 IPM

CONVENIENCE



Compact angle head design for use in close quarter applications





Large conveniently located paddle switch for comfortable operation



LXT battery and optimum charging system produces 430% total lifetime work

LXT POWER IN TIGHT SPACES

makitatools.com

18V LXT LITHIUM-ION 3/8" ANGLE IMPACT WRENCH

Models BTL063 / BTL063Z

FEATURES & BENEFITS

- n Compact right angle impact wrench for fastening and loosening in tight spaces
- n Makita built motor and impact mechanism produces 530 in. lbs. of maximum torgue and 0-3,000 IPM
- n Variable speed (0-2,000 RPM) for a range of applications from auto repair to product assembly
- n Large conveniently located paddle switch for comfortable operation
- n Over one foot of tool extension for extra reach into tight spaces
- n L.E.D. light illuminates the work area
- n Soft grip handle provides increased comfort on the job
- n Convenient belt clip mounts on either side of the tool
- n Phosphorescent bumper ring for locating tool in dark work areas
- n LXT Lithium-Ion battery provides longer run time, 5x lower self-discharge (for use any time) and 16 firm holding contact terminals (for constant high power)
- 30-Minute Rapid Optimum Charger communicates with the battery's built-in n chip throughout the charging process to optimize battery life by actively controlling current, voltage and temperature
- n 3-year warranty on tool and 1-year warranty on battery and charger

STANDARD EQUIPMENT

- n 2 ea. 18V LXT Lithium-Ion 3.0Ah battery (BL1830)
- n 30-Minute Rapid Optimum Charger (DC18RA)
- Tool belt clip and screw (324705-1 and 251314-2) n
- n Contractor bag (821007-X)
- n Battery cover (450128-8)

SPECIFICATIONS

Square drive	3/8"
No load speed	0 - 2,000 RPM
Impact per minute	0 - 3,000 IPM
Maximum torque	530 in.lbs.
Battery	18VDC (3.0Ah)
Overall length	15-1/4"
Net weight (w/ battery)	3.7 lbs.
Shipping weight	12.4 lbs.
UPC	(BTL063) 088381-089104
	(BTL063Z) 088381-089081

OPTIONAL ACCESSORIES

- Straight attachment (192440-7)
- n Ratchet attachment (192439-2)
- n Socket set (785508-A-A)





192440-7

192439-2



785508-A-A



our website at makitatools.com, or call 1-800-4MAKITA. All specifications subject to change without prior notice. All models and accessories subject to stock on hand, NTF-1207-5M MA-1019-07 For more information, call 1-800-4MAKITA or visit makitatools.com

Makita U.S.A., 14930 Northam St., La Mirada, CA 90638







Model BTL063



