

AFWALL™ FloWise® ADA RETROFIT

- Wall-mounted flushometer valve toilet
- Vitreous china
- Meets definition for HET (High Efficiency Toilet)
- High Efficiency (4.8 Lpf/1.28 gpf)
- EverClean® surface inhibits the growth of stain- and odor-causing bacteria, mold, and mildew on the surface
- Elongated bowl
- Powerful direct-fed siphon jet action
- Fully-glazed 2-1/8" trapway
- 10" x 12" water surface area
- Condensation channel
- 1-1/2" inlet spud
- 100% factory flush tested

- 3355.128** Elongated bowl only, top spud
- 3356.128** Elongated bowl only, top spud with slotted rim for bedpan holding (White only)
- 3357.128** Elongated bowl only, back spud
- 3358.128** Elongated bowl only, back spud with slotted rim for bedpan holding (White only)

Afwall ADA 1.28 replaces standard wall-hung 3.5 or 1.6 models and roughs-in at 410mm (16-1/8") rim height **to meet ADA with no need to modify the existing carrier or through wall supply** (providing centerline of current outlet is 133mm [5-1/4"] above finished floor).

Component Parts:

- 047007-0070A** Inlet spud (furnished with bowl)
- 736046-100** Flushometer valve rough-in adapter kit (furnished with bowl)

Nominal Dimensions:

660 x 356 x 419mm
(26" x 14" x 16-1/2")

For Top spud bowls, American Standard kit #736046-100 Flushometer Valve Conversion Kit containing a 25mm (1") chrome-plated street ell, a vacuum breaker, and a 330mm (13") tail piece included to meet minimum 152mm (6") code between bowl and vacuum breaker.

Recommended working pressure—between 25 psi at valve when flushing and 80 psi static

Fixture only, less seat, carrier, bolt caps, and flushometer valve

Compliance Certifications -

Meets or Exceeds the Following Specifications:

- ASME A112.19.2 for Vitreous China Fixtures
- CAN/CSA International B45



SEE REVERSE FOR ROUGHING-IN DIMENSIONS

To Be Specified:

- Color: White Bone Silver Linen Black
- Seat:
 - American Standard #5901.100 Heavy duty open front less cover
 - American Standard #5905.100 Extra heavy duty open front less cover
- Flushometer Valve:
 - American Standard Selectronic™ #6065.121.002 DC Power (Top Spud)
 - American Standard Selectronic™ #6065.222.007 DC Power (Concealed Back Spud)
 - American Standard Selectronic™ #6067.222.007 AC Power (Concealed Back Spud)
 - American Standard Selectronic™ #6068.222.007 Multi AC Power (Concealed Back Spud)



MEETS THE AMERICANS WITH DISABILITIES ACT GUIDELINES AND ANSI A117.1 REQUIREMENTS FOR ACCESSIBLE AND USABLE BUILDING FACILITIES - CHECK LOCAL CODES.

- When installed so top of seat is 432 to 483mm (17" to 19") from the finished floor.



