American Standard

COMPACT™ SPACE SAVING ELONGATED TOILET

2149.012

- Vitreous china
- Low-consumption (6.0 Lpf/1.6 gpf)
- Exclusive space saving feature
- Elongated siphon action bowl
- · Fits into same space as a conventional round front toilet
- Fully glazed trapway
- Close-coupled tank
- Sanitary bar
- 2 bolt caps
- 100% factory flush tested

3027.012 Bowl

4010.012 Tank

Nominal Dimensions:

699 x 483 x 756mm (27-1/2" x 19" x 29-3/4")

Fixture only, seat and supply by others

Compliance Certifications -Meets or Exceeds the Following Specifications:

• ASME A112.19.2M for Vitreous China Fixtures includes Flush Performance, Ball Pass Diameter, Trap Seal Depth and all Dimensions



COMPACT[™] SPACE SAVING

FINISHED WALL 699mm (27-1/2) 25mm ± 6mm (1 ± 1/4) 483mi (19) C/L OF SEAT POST HOLES 140mm (5-1/2) CENTERS 187mm (7-3/4) .470mm (18-1/2) 756mm (29-3/4) 83mm (3-1/4) 38 SUPPLY AS REQ'D FINISHED FLOOR . * 222mn (8-3/4)-16mn (5/8) 65mm 6-1/2) *****152mm (6) 248mm (9-3/4) 235mm (9-1/4) 305mm (12) .368mm (14-1/2)

To Be Specified:

- □ Seat: American Standard #5324.019 "Rise and Shine" solid plastic closed front seat with cover.
- □ Seat: American Standard #5311.012 "Laurel" molded closed front seat with cover.
- □ Alternate Seat:
- □ Supply with stop:

NOTES:

NOTES: THIS COMBINATION IS DESIGNED TO ROUGH-IN AT A MINIMUM DIMENSION OF 305MM (12") FROM FINISHED WALL TO C/L OF OUTLET. * DIMENSION SHOWN FOR LOCATION OF SUPPLY IS SUGGESTED. SUPPLY NOT INCLUDED WITH FIXTURE AND MUST BE ORDERED SEPARATELY.

IMPORTANT: Dimensions of fixtures are nominal and may vary within the range of tolerance established by ANSI Standard A112.19.2 These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.