RECESSED AR70 V TRIMLESS

DESCRIPTION:

An adjustable AR70 fixture suitable for multiple downlighting applications with one point of electrical entry. Powder coat finish on housing & lamp assembly. Housing suitable for new construction applications.

CONSTRUCTION:

All aluminum construction. Perforated mesh plaster frame adheres to ceiling compound for seamless trimless mounting. Beveled fixture opening provides easy mudding compound application. Can accommodate 0.50" or 0.625" drywall. Includes butterfly brackets for black iron commercial mounting.

LAMP ASSEMBLY:

2 - AR70 lamps mounted in adjustable bezels. Each lamp can accept up to two optical accessories. 380° x 45° locking adjustment. Fixture provides 45° visual cut-off. Lamp holders retract for added internal adjustment.

SYSTEM PROTECTION:

Thermal protection provided to guard against overheating, and misuse of insulation over and around fixture. Vent holes in housing provide cooler operation

ELECTRICAL:

Integral electronic transformer. Secondary lead is 11.5V. Primary lead is 120V. Dimmable. Junction box is UL listed for through branch wiring, (access above ceiling not required) for 8 #12, 90°C supply conductors or 60°C for end of run. Fused and short circuit protection. Transformers and electrical accessible through ceiling opening via access door on housing sidewall.

ALL RSA COMBOLIGHT PRODUCTS ARE MADE IN THE U.S.A.

120 Volt




Catalog # Type

Project

COMBOLIGHT® LV Series

TWO (2) Light Recessed **Next Generation Trimless** Multi-Lamp Luminaire Low Voltage AR70

Dimensions	A Housing Length	B Housing Height	C Aperture Length	D Aperture Width	E Plaster Frame Width	F Plaster Frame Length	G Above Ceiling Width	Ceiling Cut-Out
	14.75"	6.80"	8.80"	4.00"	9.75"	14.55"	11.75″	12.00" x 7.46"



Other Adders

CC - Two Circuit

CP - Chicago Plenum

ORDERING = Two Ligh

ig example:	LV270	WH	50	120	Optional Acc	essories - Deta	ils on Other Si	de
jht Trimless Rece t	ssed AR70 - W	/hite Interior	- 50 watt lam	ips -	@	0		
					Baffle	Snoots	Louvers	Lenses

Cat. # / Description	Interior Finish	Lamp Wattage	Voltage	
LV270: 2 Light Recessed Next Generation Trimle Combo Fixture	ess BK - Black	20 - 20 Watt AR70	120 - 120 Volt (Standard)	
12V AR70	WH - White	50 - 50 Watt AR70	277 - 277 Volt	
	S - Silver			
	PT - Custom (Specify)			
SPECIFY - LV270				



