RECESSED PAR30 LV TRIMLESS

DESCRIPTION:

An adjustable PAR30 fixture suitable for multiple downlighting applications with one point of electrical entry. Powder coat finish on housing & lamp assembly. Housing suitable for new construction applications.

CONSTRUCTION:

All aluminum construction. Perforated mesh plaster frame adheres to ceiling compound for seamless trimless mounting. Beveled fixture opening provides easy mudding compound application. Can accommodate 0.50" or 0.625" drywall. Includes butterfly brackets for black iron commercial mounting.

LAMP ASSEMBLY:

3 - PAR30 lamps mounted in adjustable bezels. Each lamp can accept up to two optical accessories. 380° x 45° locking adjustment. Fixture provides 45° visual cut-off. Lamp holders retract for added internal adjustment.

SYSTEM PROTECTION:

Thermal protection provided to guard against overheating, and misuse of insulation over and around fixture. Vent holes in housing provide cooler operation

ELECTRICAL:

Junction box is UL listed for through branch wiring, (access above ceiling not required) for 8 #12, 90°C supply conductors or 60°C for end of run. J-Box and wiring accessible through ceiling opening via access door on housing sidewall.

ALL RSA COMBOLIGHT PRODUCTS ARE MADE IN THE U.S.A.




Catalog

Туре

Project

COMBOLIGHT® LV Series

THREE (3) Light Recessed Next Generation Trimless Multi-Lamp Luminaire PAR30 Line Voltage




իստ

Optional A

Other Adders CC - Two Circuit CP - Chicago Plenum

ories - Details on Other Side



WH

ORDERING EXAMPLE: LV3003IS



Specifications and Dimensions subject to change without notice. RSA Lighting • 7945 Orion Ave. • Van Nuys, CA 91406 • 818-349-3030 • FAX 818-349-3031

