COMBOLIGHT® COMBO CLASSIC RECESSED

LAMP GROUP 2 - CONFIGURATION "E"

TWO (2) Metal Halide lamp cells - TWO (2) Fluorescent lamp cells New Construction Recessed Housing - Trim or Trimless

Catalog #		
Туре		
Project		

DESCRIPTION:

An adjustable recessed fixture suitable for multiple downlighting applications with one point of electrical entry. Mixes the use of metal halide lamps with fluorescent lamps. Powder coat finish on housing & lamp assembly.

CONSTRUCTION:

Housing, Plaster Frame & Trim Assembly: 18 gauge CRS. J-Box Assembly: 16 gauge CRS (galvanized). Fixture is offered with a .75" ceiling trim or as a trimless fixture. Can accommodate 0.50" to 1.00" ceiling thickness.

LAMP ASSEMBLY:

Two Metal Halide lamp cells with two fluorescent lamp cells . Can accept up to two optical accessories. 380° x 45° locking lamp adjustment. Provides 45° visual cut-off.

SYSTEM PROTECTION:

Thermal protection provided to guard against overheating, and misuse of insulation over and around fixture. Vent holes in housing provide cooler operation


ELECTRICAL:

Fixture is two circuit. Circuit 1: Integral Aromat® electronic metal halide ballasts for metal halide lamps.

Circuit 2: Integral electronic ballasts for fluorescent lamps. Lutron® dimming ballasts available upon request.

Junction box is UL listed for through branch wiring, for 8 #12, 90°C supply conductors or 60°C for end of run (access above ceiling not required).

Made in the USA.



Custom configurations are available with Combo Classic fixtures. Also available with T8 fluorescent lamps. Consult RSA for details



	Δ	65.18"	65.18"	65 18"	30.18"	31 18"	33 18"	112 18"	136 18"	88.18"	112.18"
Lamp Group 2											
Metal Halide	В	81.98"	81.98"	81.98"	46.98"	47.98"	49.98"	128.98"	152.98"	104.48"	128.98
Inotal Hallas	C	25.50"	25.50"	25.50"	8.00"	8.50"	9.50"	49.00"	61.00"	37.00"	49.00"
ORDERING EXAM	/IPLE	: CR22	OM39	E	BX40	BK	WH	120)		

= Two PAR20 Metal Halide 39W lamps with Two BIAX® 40W Fluorescent • Black Interior • White Trim • 120 volts

Optional Accessories - See RSA Combo Classic accessory page for details.							
	\bigcirc						
Baffle	Snoots	Louvers	Lenses				

Fluorescent Diffusers and Louvers - Please specify						
☐ TWD - Textured White Diffuser	□ CB1 - 2" Parabolic Louver					
☐ MPD - Conical Prism Diffuser	☐ CB2 - 1" Parabolic Louver					

Item # / L	amp Type	Configuration	Fluorescent Lamp Cell	Interior Finish	Trim Finish	Voltage
Lamp	CR220M39 - PAR20MH 39W	E - Two Metal Halide lamp	BX40 - 40W BIAX®	BK - Black	BK - Black	120 - 120 Volts
Group 2	CR230M39 - PAR30MH 39W	cells with Two	BX50 - 50W BIAX®	WH - White	WH - White	277 - 277 Volts
Metal	CR230M70 - PAR30MH 70W	Fluorescent lamp cells	PLL80 - 80W PL-L	S - Silver	S - Silver	
Halide]	PLT26 - 26W PL-T	PT - Custom	PT - Custom	1
			PLT32 - 32W PL-T		TR - Trimless	1
			PLT42 - 42W PL-T			1
			T528 - 28W T5			
			T535 - 35W T5			
			T5H039 - 39VV T5H0			
			T5H054 - 54VV T5H0	1		
	•	•	T8 lamps also available	•	•	

SPECIFY - E