COOPER LIGHTING - SURE-LITES®

DESCRIPTION

Lamp housing is made of corrosion resistant 22 gauge die formed spun aluminum with a powder coat finish. Die cast aluminum swivel assembly allows 80° adjustment from vertical with 358° rotation. Stainless steel mounting plate mounts flush on wall or ceiling and is designed for installation on standard electrical box. (Single head remotes are supplied with single gang plate, double head remotes are supplied with three gang plate). UL 924 Listed, CSA Certified.

| Catalog # | Туре |
|-------------|------|
| | |
| Project | |
| Comments | Date |
| Prepared by | |

SPECIFICATION FEATURES

Electrical

- 12V DC Input Voltage

Lampholder/Mounting Plate Construction

- Lamp housing is made of corrosion resistant 22gauge die formed spun aluminum with a polyester powder coat paint finish
- Die cast aluminum swivel assembly allows 80° adjustment from vertical with 358° rotation
- Stainless steel mounting plate mounts flush on wall or ceiling and is designed for installation on standard electrical box (single head remotes are supplied with single gang plate, double head remotes are supplied with three gang plate)
- Use WG8 Wire Guard for single head remotes
- Use WG9 Wire Guard for double head remotes
- Consult factory for other finishes

Code Compliance

- UL 924 Listed
- CSA Certified

Warranty

- Unit: 1-year

Lamp Data

- 12 Volt Halogen Sealed Beam
- Consult factory for other lamp types (See Technical Information Section)





12 VOLT METAL HEAD

SINGLE AND DOUBLE HEAD REMOTES Emergency Lighting

ORDERING INFORMATION

| Single Metal | Head Rer | notes | | | | |
|-----------------|------------------------------------|---|--|--|---|---|
| Lamp Housing | Mounting Plate | | | | Lamp | Isofootcandle |
| Finish | Finish | Lamp Type | Volts | Watts | No. | Diagram No. |
| White | White | Halogen Sealed Beam | 12 | 12 | 029-79 | 8 |
| White | White | Halogen Sealed Beam | 12 | 50 | 029-135 | - |
| • | Lamp Housing Finish White | Lamp Mounting Housing Plate Finish Finish White White | Housing Plate Finish Lamp Type White White Halogen Sealed Beam | Lamp Mounting Housing Plate Finish Finish Lamp Type Volts White White Halogen Sealed Beam 12 | Lamp Mounting Housing Plate Finish Finish Lamp Type Volts Watts White White Halogen Sealed Beam 12 12 | Lamp Mounting Housing Plate Lamp Finish Finish Lamp Type Volts Watts No. White White Halogen Sealed Beam 12 12 029-79 |

12 Volt Double Metal Head Remotes

| Catalog | Lamp Housing | Mounting Plate | | | | Lamp | Isofootcandle |
|------------|-----------------|-------------------|---------------------|-------|-------|---------|---------------|
| Number | Finish | Finish | Lamp Type | Volts | Watts | No. | Diagram No. |
| 12T12DMHWH | White | White | Halogen Sealed Beam | 12 | 12 | 029-79 | 8 |
| 12T50DMHWH | White | White | Halogen Sealed Beam | 12 | 50 | 029-135 | = |

Alternate Lamps: Consult Cooper Lighting Representative Other Finishes: Consult Cooper Lighting Representative



ENERGY DATA

Power Consumption is equal to lamp wattage.



PHOTOMETRICS 12 VOLT METAL HEAD

Horizontal Distribution

FEET FROM LAMP (Measured on axis)

Diagram No. 8 Lamp No. 029-79 @ 302 Initial Lumens

Vertical Distribution




Diagram No. 8 Lamp No. 029-79

