

### Construction

20-gauge steel housing with 24 ga. steel reflector.

### Shielding

Acrylic linear prism lens backed by precise frost acrylic overlay.

### Electrical

120, 277, 347 or Universal Voltage electronic ballast. Fixtures and electrical components certified to UL and CUL standards

### Finish

Durable, low gloss, white, powder coated acrylic finish.

### Mounting

Recessed.

### ORDERING INFORMATION:

Sample number: 274R-1BX40W-ETG-1EB-SI-EM

#### Series

174=1'x4'                      272=2'x2'                      274=2'x4'

#### Options <sup>2</sup>

A=Air Return                      T=Tannenbaum Reflector  
C=Chicago Plenum

#### Mounting

R=Recessed

#### Number of Lamps (in cross section) (not included)

1=1 Lamp                      2=2 Lamps

#### Lamp Type

T5                      T5H0                      BX40W                      BX50W

#### Ceiling Type

ETG=Exposed T-Grid                      STG=Slot T-Grid                      SR=Sheet Rock

#### Voltage <sup>1</sup>

1=120V                      2=277V                      3=347V                      U=Universal

#### Ballast

EB=Electronic Ballast (Standard)                      DB=Dimming Ballast

#### Switching

SI=Single Switching                      DU=Dual Switching

#### Emergency

EM=Emergency Pack (Consult Factory)


<sup>1</sup> Due to various constraints, some options may not be combined with others.  
<sup>2</sup> Can be left blank or more than one option may be available, consult factory.



**FENESTRA**  
**264**  
**262**

DIRECT-INDIRECT

- Opal white diffuser fully encloses lamp compartment for easy wipe down.
- Perfect for healthcare, educational and other institutional facilities that require simple easy cleaning and minimized contagion accumulation.
- T5 or T8 Lamping
- Highly efficient linear prismatic diffuser offers low glare, broad distribution.
- Combine the three lamp profile with dual switching for three levels of lighting through basic switches for complete, trustworthy control.
- Consult factory for dimming and emergency options.
- Recessed Mounting for T-grid, sheet rock ceiling and
- 9/16" slot T-grid.
- Can be mounted end-to-end and side-to-side.



Tannenbaum Reflector

### STANDARD LUMINAIRE PLAN - VIEW - VIEW



24" x 48"  
(610mm x 1219mm)  
(2, 3, 4 or 6 Lamps)


264




24" x 24"  
(610mm x 610mm)  
(2 or 3 Lamps)

262


### MOUNTING INFORMATION



ETG  
EXPOSED TEE GRID



STG  
SLOT TEE GRID



SR  
SHEET ROCK

NOTES: For complete product data, refer to the Neo-Ray Specification Binder. Specifications and dimensions subject to change without notice. Products may be modified for use in international markets. Please contact your Cooper Lighting Sales Representative for availability and ordering information.