## **RECESSED GRID CEILING MOUNT**

w/ OPEN HOUSING MR16

#### **DESCRIPTION:**

An adjustable MR16 fixture suitable for multiple downlighting applications with one point of electrical entry. For use in lay-in t-bar grid style ceilings. Powder coat finish on housing & lamp assembly.

#### CONSTRUCTION:

Housing Assembly: 18 gauge CRS. J-Box Assembly: 16 gauge CRS (galvanized). Fixture utilizes specially developed retaining clips for snap-in mounting directly to t-bar supports. Tabs on housing top accommodate above ceiling aircraft cable support for added stability.

#### LAMP ASSEMBLY:

Three MR16 lamps mounted in adjustable bezels. Each lamp can accept up to two optical accessories. 380° x 45° locking lamp adjustment. Provides 45° visual cut-off.

#### SYSTEM PROTECTION:

Thermal protection provided to guard against overheating, and misuse of insulation over and around fixture. Vent holes in housing provide cooler operation

#### **ELECTRICAL**:

Integral electronic transformers. Fused and short circuit protection. Junction box is UL listed for through branch wiring, (access above ceiling not required) for 8 #12, 90°C supply conductors or 60°C for end of run.

Transformers and electrical wiring accessible through ceiling opening.

# ALL RSA COMBOLIGHT PRODUCTS ARE MADE IN THE U.S.A.






Catalog #

Type

Project

### COMBOLIGHT® GR Series

THREE (3) Light Recessed Multi-Lamp Luminaire for Lay-in, T-Bar Grid Style Ceiling Open Housing Aperture Low Voltage MR16



Lamp Wattage	Interior Finish	Lamp Holder	Voltage
<b>50 -</b> 50 Watt 12 Volt MR16	<b>BK</b> - Black	YK - Regular Yoke (Standard)	<b>120</b> - 120 Volt
<b>75</b> - 75 Watt 12 Volt MR16	WH - White	RT - Retractable Yoke	<b>277</b> - 277 Volt
	S - Silver		
	PT - Custom		
	<b>50 -</b> 50 Watt 12 Volt MR16	50 - 50 Watt 12 Volt MR16  BK - Black  75 - 75 Watt 12 Volt MR16  WH - White  S - Silver	50 - 50 Watt 12 Volt MR16  BK - Black  YK - Regular Yoke (Standard)  75 - 75 Watt 12 Volt MR16  WH - White  S - Silver