



Oversized Trim Rings

OT400P
6" ID x 9 1/4" OD
Oversized white metal trim ring.

OT403P
6" ID x 8" OD
Oversized white plastic trim ring.

For use when ceiling opening is cut too large. Compatible with 310, 312, 376, 378, 400, 404, 405, 406 (SC and RG only), 409, 410, 416, 419, 420, 424, 425, 426, 429, 446, 448, 477, 478, 1412, 1416, 1475, 2412, 2416, 2475.



H277

Transformer

Steps 277V line voltage down to 120V fixture operating voltage. 150VA max. Not compatible with box type IC fixtures (such as H274IC) due to physical interference with the housing.

H347

Same as above but changes 347V to 120V



Oversized Trim Rings

OT999P
4" ID x 5 3/4" OD

Oversized white metal trim ring. Compatible with 990, 992, 993, 994, 996, 998, 999, 1419, 1420, 1421, 1493 and 1498.



Optical Lenses

For low voltage MR16 units.

L110 Diffuse Sand Blasted Lens

L111 Soft Focus Textured Lens

L113 Prismatic Lens

L115 Linear Spread Lens



Oversized Trim Ring

OT460P
7 1/2" ID x 11 1/4" OD

Oversized white metal trim ring compatible with 466, 468 and 480 trims.

800PGR
H800 oversized trim ring.
7 1/2" ID x 8 5/8" OD.



H930

R Lamp Accessory

R/PAR lamp aiming accessory for H7T and H7RT housing with 310 and 426 trims. Allows lamp to be aimed up to 30° from vertical and rotated 358°.



Oversized Trim Ring

OT500P
6" ID x 7-1/4" OD

Oversized white polymer trim ring for use with H5 series straight sided trims



Mounting Clips

TB7

T-Bar attachment clips for use with H1, H2 and ALL-Pro Hanger Bars on suspended ceiling systems—set of four. Order one set per fixture. Can also be used with HB424 and HB224 Hanger Bars.

RK7

Hold down clips for non-remodel fixtures when hanger bars are not used. Set of four.



H1999

Socket Extender

For use with selected trims and housings. Extends lamp 1" (25mm).



SD2925

Screwdriver

Screwdriver for tamper resistant screws supplied with H2925 and H2926 brick lights.


RS7H

Set of 4 coil springs for use with 301, 310, 401 and 426 trims in the H7 recessed housing family.



GA-ATTRIM-6PK

For California Title 24 an additional trim gasket between the finished ceiling and flange ring of an AIR-TITE trim is required to qualify for an IR-TITE installation. For compliance, use the GA-ATTRIM



Slope Adapters

White .050 spun aluminum. Available as shown in following table. Items in **BOLD** face are stocked

Slope	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°
6" for H44*		HSA65	HSA610	HSA615	HSA620	HSA625	HSA630	HSA635	HSA640	
8" for H46	HSA680	HSA85	HSA810	HSA815	HSA820	HSA825	HSA830	HSA835	HSA840	HSA845



Hanger Bars


HB224

One piece hanger bar for 24" maximum joist spacing. Set of two.

HB424

Two piece hanger bar for 24" maximum joist spacing. Set of four pieces. Order one HB424 per fixture.

Hanger bars are compatible with the following housing families: M700, H800, H801, H802, H803, H870 and H880E.



LAMPS

INCANDESCENT

Lamps

- Z7** 20W T 6 1/2" IF
- Z9** 40W R16 FL
- Z10** 100W BR25
- Z28** 120V GU10 25°



LOW VOLTAGE

- Z21** 12V Q50W MR16 NSP
- Z26** 12V Q50W MR16 NFL
- Z31** 12V Q50W MR16 FL
- Z40** 12V Q75W MR16 NSP
- Z45** 12V Q75W MR16 FL
- Z121** 50W MR16/Q/10°/TL (GE TURN-AND-LOCK BASE)

- Z131** 50W MR16/Q/20°/TL (GE TURN-AND-LOCK BASE)
- Z124** 50W MR16/Q/40°/TL (GE TURN-AND-LOCK BASE)



COMPACT FLUORESCENT

- Z62** 22W 15mm PL-C, Gx32d-2 Double Twin Tube Compact Fluorescent (2700°K)
- Z128** 28W 15mm PL-C Gx32d-3 Double Twin Tube (DTT) 2-Pin Compact Fluorescent (2700°K)
- Z63** 13W Twin Tube Compact Fluorescent, 2-pin, Gx23 (2700°K)
- Z64** 13W Double Twin Tube Compact Fluorescent, 2-pin, Gx23-2l (2700°K)
- Z113E** 13W Double Twin Tube (DTT) 4-Pin Compact Fluorescent, G24q-1 (2700°K)
- Z118** 18W Double Twin Tube (DTT) 2-Pin Compact Fluorescent, G24d-2 (2700°K)
- Z118E** 18W Double Twin Tube (DTT) 4-Pin Compact Fluorescent G24q-2 (2700°K)
- Z126** 26W Double Twin Tube (DTT) 2-Pin Compact Fluorescent, G24d-3 (2700°K)

- Z126E** 26W Double Twin Tube (DTT) 4-Pin Compact Fluorescent, G24q-3 (2700°K)
- Z118T27** 18W Triple Twin Tube (TTT) 2-Pin Compact Fluorescent, G24d-2 (2700°K)
- Z126T27** 26W Triple Twin Tube (TTT) 2-Pin Compact Fluorescent, G24d-3 (2700°K)
- Z126P30** 26W Triple Twin Tube (TTT) 4-Pin Compact Fluorescent, GX24q-3 (3000°K)
- Z132P30** 32W Triple Twin Tube (TTT) 4-Pin Compact Fluorescent, GX24q-3 (3000°K)
- Z142P30** 42W Triple Twin Tube(TTT) 4-Pin Compact Fluorescent, GX24q-4 (3000°K)
- Z118TE30** 18W Triple Twin Tube(TTT) 4-Pin Compact Fluorescent, GX24q-2 (3000°K)
- Z126TE30** 26W Triple Twin Tube(TTT) 4-Pin Compact Fluorescent, GX24q-3 (3000°K)

