

DESCRIPTION

641-WP Quarter Sphere Wall Sconce features indirect illumination.

Catalog #	Type
Project	
Comments	Date
Prepared by	

SPECIFICATION FEATURES

Material

Painted aluminum or solid bronze. Internal lamp assembly is cast aluminum with clear acrylic lense for CFL and tempered clear lense for incandescent and metal halide.

Finish

Natural bronze or premium TGIC polyester powder coat paint, 2.5 mil nominal thickness for superior protection against fade and wear. Standard: Natural Bronze (NBZ) [Sustainable Design]. Note: Bronze will weather to a dark bronze patina. Premium: Black (BK), Grey (GY), White (WH), Dark Platinum (DP), Graphite Metallic (GRM), Silver Metallic (SM), Gold Metallic (GM), Bronze Metallic (BM), Verdigris (VG), Lacquered Satin Chrome (SCL), Lacquered Satin Nickel (SNL) or Custom Color (CC).

Optics

Refer to www.shaperlighting.com for complete photometrics.

Ballast

Integral electronic HPF, multi-volt 120/277V (347V Canada), thermally protected with end-of-life circuitry to accommodate the specified lamp wattage. Metal halide ballasts are electronic HPF, multi-volt 120/277V for the specified lamp wattage. 347V ballast for metal halide - Contact factory.

Lamp/Socket

One (1) 26W, 32W (GX24q-3) or 42W (GX24q-4) 4-pin triple tube CFL lamp, one (1) 50W or 70W metal halide ED-17 lamp, or one (1) 150W A-21 lamp. CFL socket injection molded plastic. INC socket fired ceramic rated for 660W-250V. Metal halide socket is ceramic pulse-rated, 4KV. Lamps furnished by others.

Installation

Supplied with a universal circular strap for a standard 4" J-box or stucco ring. Optional rear (through wall) feed conduit mounting.

Options


Rear (through wall) Feed Conduit Mounting (C). Energy Star Rating - consult factory.

Labels

U.L. and C.U.L. approved for wet location.

Modifications

Shaper's skilled craftspeople with their depth of experience offer the designer the flexibility to modify standard exterior wall luminaires for project specific solutions. Contact the factory regarding scale options, unique finishes, mounting, additional materials/colors, or decorative detailing.



641-WP SERIES

Exterior Wall Luminaire
Quarter Sphere



ORDERING INFORMATION

Sample Number: 641-WP-MH/1/70-277V-BK

Series	Lamp	Voltage	Finish ^{3,4}	Options
641-WP= Quarter Sphere	CFL/1 (26/32/42W-Triple) INC/1/150 MH/1/50 MH/1/70	120V 277V ¹ 347V ²	<u>Standard</u> NBZ = Natural Bronze <u>Premium</u> BK = Black BM = Bronze Metallic CC = Custom Color DP = Dark Platinum GM = Gold Metallic GRM = Graphite Metallic GY = Grey SCL = Lacquered Satin Chrome SM = Silver Metallic SNL = Lacquered Satin Nickel VG = Verdigris WH = White	C = Rear (through wall) Feed Conduit Mounting

Notes:

- ¹ CFL and MH only.
- ² Available with CFL only.
- ³ Premium TGIC polyester powder coat paint, 2.5 mil nominal thickness for superior protection against fade and wear.
- ⁴ Bronze will weather to a dark bronze patina.



Shaper now offers a wide variety of fixtures that can be provided with an Energy Star Rating.



Shaper has a long-standing history of offering environmentally-friendly fixtures. The copper and bronze alloys used in our exterior luminaires feature up to 98% recycled content, contribute less undesirable air emissions compared to painted aluminum and are easy to recycle.

Refer to the Icon Legend
Link on shaperlighting.com.

DIMENSIONS

